CISSP Cheat Sheet Series Domain 1: Security & Risk Management **Achieving CIA - Best Practices CIA Triad** Preserving authorized restrictions on information Job Separation Mandatory Least Vacations Rotation access and disclosure, including means for protecting of Duties Privileges Confidentiality personal privacy and proprietary information. Note -**Availability** Encryption (At transit – TLS) (At rest - AES – 256) RTO/MTD/RPO, MTBF, SLA **Measuring Metrics** Guarding against improper information modification or Integrity destruction and includes ensuring information non-repudiation and authenticity. IAAAA Ensuring timely and reliable access to and use of **Availability** Identification Unique user identification information by authorized users. *Citation: https://www.isc2.org/Certifications/CISSP/CISSP-Student-Glossary **Authentication** Validation of identification Verification of privileges and permissions for Authorization D.A.D. authenticated user Only authorized users are accessing and use the **Disclosure Alteration Destruction** Accountability system accordingly Opposite of Tools, processes, and activities used to achieve and Opposite of Integrity Opposite of Availability **Auditing** Confidentiality maintain compliance **Plans Protection Mechanisms Duration Type Example** Layering Abstractions **Data Hiding** Strategic Plan up to 5 Years Risk Assessment Data classification **Tactical Plan** Maximum of 1 year Project budget, staffing etc Patching computers Entails analyzing the data that the organization retains, determining its **Operational Plan** A few months **Updating AV signatures** importance and value, and then assigning it to a category. Daily network administration Risk Management Risk Terminology No risk can be completely avoided. Asset Anything of value to the company. Risks can be minimized and controlled to avoid impact of damages. Risk management is the process of identifying, examining, measuring, mitigating, or transferring risk *Citation:https://resources.infosecinstitute.com/category/certifications-traini ng/cissp/domains/security-and-risk-management/ **Solution** – Keep risks at a tolerable and acceptable level. Risk management constraints - Time, budget Risk Manag **Preventive Deterrent**

Vulnerability	A weakness; the absence o	f a safeguard				
Threat	Things that could pose a ris	sk to all or part of an asset				
Threat Agent	The entity which carries ou	The entity which carries out the attack				
Exploit	An instance of compromise	9				
Risk	The probability of a threat r	naterializing				
*Citation:https://resource /security-and-risk-manag	es.infosecinstitute.com/category/ceement/	ertifications-training/cissp/domains				
gement Fram	eworks					
Detective	Corrective	Recovery				
	Alarms	Backups				
ity Cameras	Antivirus Solutions	Server Clustering				
ion Detection Systems	Intrucion Detection Systems	Fault Tolorant Drive Systems				

Patents

Trade Secrets

Licensing

Need to

know

Dual Control

Encryption

Ex ISO 27001		Ex ISO 27000		Stective	Conectiv	C	Recovery
Security Policies	Secu	rity Personnel	Logs		Alarms		Backups
Security Cameras	Guar	ds	Security Ca	ameras	Antivirus Solutions		Server Clustering
Callback	Secu	rity Cameras	Intrusion D	etection Systems	Intrusion Detection	Systems	Fault Tolerant Drive Systems
Security Awareness Training	Sepa	ration of Duties	Honey Pots	3	Business Continuit	y Plans	Database Shadowing
Job Rotation	Intru	sion Alarms	Audit Trails	3			Antivirus Software
Encryption	Awar	eness Training	Mandatory	Vacations			
Data Classification	Firew	valls				Risk	Framework Types
Smart Cards	Encry	yption				Security	and Risk Management
	Riel	k Managemen	t Lifa C	vole		Asset Se	ecurity
	Misi	· Managemen	t Life O	ycie		Security	Engineering
Assessment		Analysis		Mitigation	/ Response	Commu	nications and Network Security
Categorize, Classify & Evalu Assets	ate	Qualitative vs Quar	ntitative	Reduce, Tra	nsfer, Accept	Identity	and Access Management
THE TANK TOOL 20.		Overlite tive I veleme en				Security	Assessment and Testing
as per NIST 800-30:				Reduce / Avoid		Security	Operations
System Characterization		Quantitative – Main ter	rms	Transfer		Softwar	e Develonment Security

				occurry operations	
System Characterization		Quantitative - Main terms	Transfer	Software Development Security	
Threat Identification		AV – Asset Value	Accept / Reject	TI 60: 6:1 D. I	
Vulnerability Identification		EF – Exposure Factor		The 6 Steps of the Risk Management Framework	
Control Analysis		ARO – Annual Rate of Occurrence	Security		
			Governance	Categorize	
Likelihood Determinatio	n	Single Loss Expectancy = AV * EF		Select	
Impact Analysis		Annual Loss Expectancy = SLE*ARO	BS 7799	Implement	
		SLE ARO	ISO 17799 & 2700 Series	•	
Risk Determination		Risk Value = Probability * Impact	COBIT & COSO	Asses	
Control Recommendatio	n		OCTAVE	Authorize	
Results Documentation			ITIL	Monitor	
		Threat Ident	ification Models		
S.T.R.I.D.E.	S poofii	ng - Tampering - Repudiation - I	nformation Disclosure - D enial of	Service - Escalation of Privilege	
D.R.E.A.D.	Damage - Reproducibility - Exploitability - Affected - Discoverability				

D.R.E.A.D.	Damage - Rep	roducibility - Exploitability - Affected - Discoverability	
M.A.R.T.	Mitigate - Acce	pt - R eject - T ransfer	
Disaster Re	covery /	Types of Law	Intellectual Property
Business Cont	inuity Plan	Criminal law	intellectual Froperty
Continuity plan goals	8	Civil Law	Copyright
Statement of importa	ance	Administrative Law	Сорунди
Statement of prioritie	es	Comprehensive Crime Control Act (1984)	Trademarks
Statement of organiz	zation	Computer Froud and Abuse Act (1096)	

Government Information Security Reform Act (2000)

Federal Information Security Management Act (2002)

Computer Fraud and Abuse Act (1986)

Computer Security Act (1987)

responsibility

Risk assessment

Statement of urgency and timing

Risk acceptance / mitigation

Classification Levels Military Sector Private Sector Top Secret Sensitive Confidential Private Company Sensitive but unclassified Company confidential

Public

Unclassified

Typical Data Retention Durations				
Business documents	7 years			
Invoices	5 years			
Accounts Payable / Receivable	7 years			
Human Resources - Hired	7 years			
Human Resources - Unhired	3 years			
Tax records	4 years			
Legal correspondence	Permanently			

Data Security Controls			
Data in Use	Scoping & tailoring		
Data at Rest	Encryption		
Data in Motion	Secure protocols e.g. https		

	Data Owr	ership
Data Ownership	Data Custodian	Syste
Top level/Primary responsibility for data Define level of classification Define controls for levels of classification Define baseline security standards Impact analysis Decide when to destroy information	Grant permissions on daily basis Ensure compliance with data policy and data ownership guidelines Ensure accessibility, maintain and monitor security Data archive Data documentation Take regular backups, restore to check validations Ensure CIA Conduct user authorization Implement security controls	Sanit Degau Eras
		_

Data Classification Criteria

Value - Usefulness - Age - Association

Data Retention Policies

The State of Florida Electronic Records and Records Management Practices, 2010

The European Documents Retention Guide, 2012

Security Policies, Standards & Guidelines

Regulatory	Required by law and industrial standards
Advisory	Not compulsory, but advisable
Informative	As guidance to others
Information Policy	Define best practices for information handling and usage -Security policies: Technical details of the policies i.e. SYSTEM security policy: lists hardware / software in use and steps for using policies
Standards	Define usage levels
Guidelines	Non-compulsory standards
Procedures	Steps for carrying out tasls and policies
Baseline	Minimum level of security

Systems Owners	Administrators	Ena User
Apply Security Controls	Grant permission for data handling	Uses information for their job / tasks Adhere to security policies and guidelines
Data	Remanenc	e

	Data Remanence
Sanitizing	Series of processes that removes data, completely
Degaussing	Erase form magnetic tapes etc to ensure not recoverable
Erasing	Deletion of files or media
Overwriting	Writing over files, shredding
Zero fill	Overwrite all data on drives with zeros
Destruction	Physical destruction of data hardware device
Encryption	Make data unreadable without special keys or algorithm

Standards				
NIST	National Institute of Standards Technology			
NIST SP 800 Series	Computer security in a variety of areas			
800-14 NIST SP	Securing Information Technology systems			
800-18 NIST	Develop security plans			
800-27 NIST SP	Baseline for achieving security			
800-88 NIST	Guidelines for sanitation and disposition, prevents data remanence			
800-137	Continuous monitoring program: define, establish, implement, analyze and report			
800-145	Cloud computing standards			
FIPS	Federal Information Processing Standards			

CISSP Cheat Sheet Series Domain 3: Security Engineering Security Models and Concepts **Security Models** System Evaluation and Assurance Levels Hardware architecture Security architecture frameworks - Provides access rights including discretionary access control Evaluates operating systems, application and systems. But not Simultaneous running of **Trusted Computer** Multitasking MATRIX to subjects for different objects. network part. Consider only about confidentiality. Operational two or more tasks. A 2D model considering interrogations such as what, where System Evaluation (Access control model) - Read, write and execute access defined in ACL as matrix assurance requirements for TCSEC are: System Architecture, Simultaneous running of Zachman Framework and when with, etc. With various views such as planner, owner, Criteria Multi programming columns and rows as capability lists. System Integrity, Covert Channel analysis, Trusted Facility two or more programs designer etc. (TCSEC) Management and Trusted recovery. -A subject cannot read data at a higher security level. (A.K.A. CPU consists or more Sherwood Applied Multi-processing simple security rule) A collection of criteria based on the Bell-LaPadula model used than one processor **Business Security** To facilitate communication between stakeholders Subject in a defined security level cannot write to a lower Orange Book to grade or rate the security offered by a computer system Architecture (SABSA) **Processing Types** security level unless it is a trusted subject. (A.K.A *-property Information Technology One security level at a **BELL-LAPADULA** (star property) rule Single State Similar to the Orange Book but addresses network security. Red Book Infrastructure Library Set of best practices for IT service management (Confidentiality model) - Access matrix specifies discretionary access control. Green Book Password Management (ITIL) Multiple security levels at - subject with read and write access should write and read at Multi State Evaluates operating systems, application and systems. But not Security architecture documentation a time. the same security level (A.K.A Strong star rule :) **Trusted Computer** network part. Consider only about confidentiality. Operational Establish security controls published by Standardization (ISO) - Tranquility prevents security level of subjects change between Software built in to in the System Evaluation ISO/IEC 27000 Series assurance requirements for TCSEC are: System Architecture, Firmware and the Electrotechnical Commission (IEC) ROM Criteria System Integrity, Covert Channel analysis, Trusted Facility (TCSEC) Control Objectives for Cannot read data from a lower integrity level (A.K.A The **Base Input Output** Set of instructions used to Management and Trusted recovery. Define goals and requirements for security controls and the Information and Related simple integrity axiom) System (BIOS) load OS by the computer. mapping of IT security controls to business objectives. Consider all 3 CIA (integrity and availability as well as Technology (CobiT) - Cannot write data to an object at a higher integrity level. ITSEC confidentiality **Mobile Security** BIBA (A.K.A the * (star) integrity axiom) Types of security models (Integrity model) - Cannot invoke service at higher integrity. (A.K.A The **TCSEC** Explanation Device Encryption • Remote wiping • Remote lock out Check each of the possible system state and ensure the proper invocation property) D Minimal protection Internal locks (voice, face recognition, pattern, pin, State Machine Models security relationship between objects and subjects in each - Consider preventing information flow from a low security level password) • Application installation control • Asset state. DAC; Discretionary Protection (identification, authentication C1 to a high security level. tracking (IMIE) · Mobile Device Management · resource protection) Allocate each security subject a security label defining the User: An active agent Removable storage (SD CARD, Micro SD etc.) C2 highest and lowest boundaries of the subject's access to the DAC; Controlled access protection Multilevel Lattice Models • Transformation Procedure (TP): An abstract operation, such system. Enforce controls to all objects by dividing them into B1 IoT & Internet Security MAC; Labeled security (process isolation, devices) as read, writes, and modify, implemented through levels known as lattices. B2 MAC; Structured protection Programming Network Segmentation (Isolation) • Logical Isolation Arrange tables known as matrix which includes subjects and · Constrained Data Item (CDI): An item that can be manipulated В3 MAC; security domain (VLAN) • Physical isolation (Network segments) • Matrix Based Models objects defining what actions subjects can take upon another only through a TP MAC; verified protection Application firewalls • Firmware updates Α • Unconstrained Data Item (UDI): An item that can be **CLARK WILSON** Common criteria assurance levels Consider the state of the system at a point in time for a manipulated by a user via read and write operations **Physical Security** (Integrity model) EAL0 Inadequate assurance Noninterference Models subject, it consider preventing the actions that take place at Enforces separation of duty Internal vs external threat and mitigation one level which can alter the state of another level. EAL1 Functionality tested Requires auditing EAL2 Hurricanes, tornadoes, earthquakes Structurally tested Commercial use Try to avoid the flow of information from one entity to another Natural threats Information Flow Models floods, tsunami, fire, etc - Data item whose integrity need to be preserved should be EAL3 which can violate the security policy. Methodically tested and checked Politically EAL4 Methodically designed, tested and reviewed Read and Write are allowed or restricted using a specific Confinement - An integrity verification procedure (IVP) -scans data items and motivated Bombs, terrorist actions, etc EAL5 memory location, e.g. Sandboxing. Semi-formally designed and tested confirms their integrity against external threats threats EAL6 Semi-formally verified, designed and tested Data in Use Scoping & tailoring Information is restricted to flow in the directions that are Power/utility General infrastructure damage EAL7 Formally verified, designed and tested Information flow model permitted by the security policy. Thus flow of information from Security Modes supply threats (electricity telecom, water, gas, etc) ITSEC security evaluation criteria - required levels one security level to another. (Bell & Biba). Man Made D + E0 Minimum Protection Use a single classification level. All objects can access all Sabotage, vandalism, fraud, theft - Use a dynamic access control based on objects previous threats Dedicated Security Mode subjects, but users they must sign an NDA and approved prior C1 + E1 Discretionary Protection (DAC) Liquids, heat, gases, viruses, to access on need-to-know basis C2 + E2 Controlled Access Protection (Media cleansing for reusability) Major sources Subject can write to an object if, and only if, the subject bacteria, movement: (earthquakes), Brewer and Nash All users get the same access level but all of them do not get B1 + E3 to check Labelled Security (Labelling of data) cannot read another object in a different dataset. System High Security radiation, etc (A.K.A Chinese wall the need-to-know clearance for all the information in the B2 + E4 Structured Domain (Addresses Covert channel) Prevents conflict of interests among objects. Mode **Natural threat control measures** model) B3 + E5 Security Domain (Isolation) Move or check location, frequency of Hurricanes, In addition to system high security level all the users should https://ipspecialist.net/fundamental-concepts-of-security-mod A + E6 Verified Protection (B3 + Dev Cycle) Compartmented Securit Tornadoes, occurrence, and impact. Allocate have need-to-know clearance and an NDA, and formal approval els-how-they-work/ Common criteria protection profile components Mode Earthquakes budget. for all access required information. Lipner Model Commercial mode (Confidentiality and Integrity,) -BLP + Biba Descriptive Elements • Rationale • Functional Requirements • Development assurance Raised flooring server rooms and Use two classification levels as System Evaluation and Floods Rule 1: Transfer Access, Rule 2: Grant Access, Rule 3: Delete Graham-Denning Model requirements • Evaluation assurance requirements Multilevel Security Mode offices to keep computer devices **Assurance Levels** Objects, subjects and 8 Access, Rule 4: Read Object, Rule 5: Create Object, Rule 6: **Certification & Accreditation** Electrical UPS, Onsite generators destroy Object, Rule 7: Create Subject, Rule 8: Destroy Evaluation of security and technical/non-technical features to ensure Virtualization Certification Fix temperature sensors inside Harrison-Ruzzo-Ullman Restricts operations able to perform on an object to a defined if it meets specified requirements to achieve accreditation. server rooms, Communications Guest operating systems run on virtual machines and hypervisors run on one or more Model set to preserve integrity. Declare that an IT system is approved to operate in predefined Accreditation Redundant internet links, mobile host physical machines. conditions defined as a set of safety measures at given risk level. Web Security communication links as a back up to Virtualization security **NIACAP Accreditation Process** Trojan infected VMs, misconfigured hypervisor cable internet. threats Open-source application security project. OWASP creates Phase 1: Definition • Phase 2: Verification • Phase 3: Validation • Phase 4: Post **Man-Made Threats OWASP** Software as A Service (SaaS), Infrastructure As A Service guidelines, testing procedures, and tools to use with web Accreditation Cloud computing models Avoid areas where explosions can (laaS), Platform As A Service (PaaS) Accreditation Types **Explosions** occur Eg. Mining, Military training Injection / SQL Injection, Broken Authentication, Sensitive Data Account hijack, malware infections, data breach, loss of data Cloud computing threats Type Accreditation Evaluates a system distributed in different locations. etc. Exposure, XML External Entity, Broken Access Control, Security Minimum 2 hour fire rating for walls, System Accreditation Evaluates an application system. **OWASP Top 10** Misconfiguration, Cross-Site Scripting (XSS), Insecure Fire **Memory Protection** Fire alarms, Fire extinguishers. Site Accreditation Evaluates the system at a specific location. Deserialization, Using Components with Known Vulnerabilities, Deploy perimeter security, double Insufficient Logging and Monitoring Vandalism Directly access inbuilt CPU memory to access CPU and ALU Register Symmetric vs. Asymmetric Encryption locks, security camera etc. Attackers try to exploit by allowing user input to modify the Stack Memory Segment Used by processors for intercommunication. Use measures to avoid physical back-end/server of the web application or execute harmful Use a private key which is a secret key between two parties. SQL Injections: Monolithic Operating Fraud/Theft access to critical systems. Eg. code which includes special characters inside SQL codes All of the code working in kernel mode/system. Each party needs a unique and separate private key. System Architecture Fingerprint scanning for doors. results in deleting database tables etc. Symmetric Algorithms Number of keys = x(x-1)/2 where x is the number of users. Eq. Memory Addressing Identification of memory locations by the processor. SQL Injection prevention: Validate the inputs and parameters. DES, AES, IDEA, Skipjack, Blowfish, Twofish, RC4/5/6, and Site Selection Register Addressing CPU access registry to get information. **Cross-Site Scripting** Attacks carryout by inputting invalidated scripts inside Immediate Addressing Part of an instruction during information supply to CPU. **Deter Criminal Activity - Delay** (XSS) Stream Based Symmetric Encryption done bitwise and use keystream generators Eg. **Physical** Intruders - Detect Intruders - Assess Actual address of the memory location is used by CPU. Direct Addressing Attackers use POST/GET requests of the http web pages with Cipher security goals Situation - Respond to Intrusion HTML forms to carry out malicious activity with user accounts. Indirect Addressing Same as direct addressing but not the actual memory location Encryption done by dividing the message into fixed-length **Block Symmetric Cipher** Visibility - External Entities -**Cross-Request Forgery** Prevention can be done by authorization user accounts to carry blocks Eg. IDEA, Blowfish and, RC5/6. Base + Offset Addressing Value stored in registry is used as based value by the CPU Site selection Accessibility - Construction - Internal the actions. Eq. using a Random string in the form, and store it Use public and private key where both parties know the public *Citation CISSP SUMMARY BY Maarten De Frankrijker issues on the server. Compartments and the private key known by the owner . Public key encrypts · Middle of the building (Middle Cryptographic Terminology the message, and private key decrypts the message. 2x is total Cryptography Asymmetric Algorithms floor) number of keys where x is number of users. Eg. Diffie-Hellman, Convert data from plaintext to cipher text. **Encryption** Single access door or entry point • P - Privacy (Confidentiality) RSA, El Gamal, ECC, Knapsack, DSA, and Zero Knowledge Decryption Convert from ciphertext to plaintext. Fire detection and suppression A – Authentication Server room Proof. Cryptography Goals • I - Integrity security systems Key A value used in encryption conversion process. Symmetric Algorithms Asymmetric Algorithms Hybrid Cryptography (P.A.I.N.) · N - Non-Repudiation. Raised flooring Synchronous Encryption or decryption happens simultaneously. Use of both Symmetric and Redundant power supplies Use of private key which is a Use of public and private key Asymmetric encryption. Eg. Encryption or decryption requests done subsequently or after a Key space = 2n. (n is number of key bits) Solid /Unbreakable doors **Asynchronous** secret key SSL/TLS Confidentiality 8 feet and taller with razor wire. Single private key use for encryption and decryption. Fences and Symmetric Provide integrity. One way Integrity Remote controlled underground Provides confidentiality but Provides confidentiality. Gates Proof of origin function divides a message Key pair use for encrypting and decrypting. (One private and Use of Cryptography integrity, authentication, and concealed gates. not authentication or **Asymmetrical** or a data file into a smaller Non-repudiation one public key) nonrepudiation nonrepudiation Infrared Sensors - Electromechanical Perimeter fixed length chunks. Protect data at rest Use to verify authentication and message integrity of the Intrusion Systems - Acoustical Systems Protect data in transit One key encrypts and One key encrypts and other Encrypted with the private **Digital Signature** sender. The message use as an input to a hash functions for CCTV - Smart cards -Detection key decrypts key of the sender. decrypts validating user authentication. Codes vs. Ciphers **Systems** Fingerprint/retina scanning Message Authentication A one-way function, convert message to a hash value used to Continuous Lighting - Standby Lighting Substitution cipher, Transposition cipher, Caesar Cipher, Code (MAC) used to encrypt Larger key size. Bulk Hash verify message integrity by comparing sender and receiver **Classical Ciphers** Lighting - Movable Lighting Small blocks and key sizes the hash function with a **Systems** encryptions Emergency Lighting symmetric key. **Modern Ciphers** Block cipher, Stream cipher, Steganography, Combination. **Digital Certificate** An electronic document that authenticate certification owner. Offsite media storage - redundant Faster and less complex. Not Slower. More scalable. Allows for more trade-offs Media storage Cipher converts Plaintext to another written text to hide original Simple text message. Plaintext backups and storage Concealment Cipher between speed, complexity, scalable Normal text converted to special format where it is unreadable Faraday Cage to avoid and scalability. Ciphertext Uses a key to substitute letters or blocks of letters with without reconversion using keys. electromagnetic emissions - White Hash Functions and Digital **Substitution Ciphers** different letters or block of letters. I.e. One-time pad, **Electricity** noise results in signal interference The set of components used for encryption. Includes Certificates Cryptosystem stenography. Control Zone: Faraday cage + White algorithm, key and key management functions Out-of-band key exchange In-band key exchange Hashing use message Reorder or scramble the letters of the original message where noise Breaking decrypting ciphertext without knowledge of digests. Cryptanalysis Transposition Ciphers the key used to decide the positions to which the letters are Use anti-static spray, mats and cryptosystem used. moved **Key Escrow and Recovery** wristbands when handling electrical Static **Cryptographic Algorithm** Procedure of enciphers plaintext and deciphers cipher text.

Common Algorithms

Lucifer

DES

algorithm

128,192 or Rijndael

256 bit

algorithm substitution

EDE2)

blocks

Structure

64 bit cipher block size and 56 bit key

· Slower than DES but higher security

(DES EE3, DES EDE3 ,DES EEE2, DES

Examples Bitlocker, Microsoft EFS

each block divide to 16 smaller

Each block undergo 8 rounds of

• 16 rounds of transposition and

(ECB, CBC, CFB, OFB, CTR)

Use 3 different bit size keys

Fast, secure 10,12, and 14

transformation rounds

64 bit cipher blocks

transformation

64 bit Block cipher

64 bit Block cipher

Example SSL and WEP

256 Rounds of transformation

64 bit block 12 transformation rounds

No confidentiality, authentication, or

Public key and one-way function for

Private key and one-way function for

Used for encryption, key exchange

Used for encryption, key exchange

Used for encryption, key exchange

Speed and efficiency and better

encryption and digital signature

decryption and digital signature

255 rounds transformation

128 bit block 48 rounds

transformation

non-repudiation

Uses 1024 keys

verification

generation

Slower

security

Attacker assumes substitution and transposition ciphers use repeated

Assumes figuring out two messages with the same hash value is

easier than message with its own hash value

Replay Attacks Attacker sends the same data repeatedly to trick the receiver.

Statistical Attack | An attacker uses known statistical weaknesses of the algorithm

Use a cryptographic device to decrypt the key

Dictionary Attacks Uses all the words in the dictionary to find out correct key

Analytic Attack An attacker uses known weaknesses of the algorithm

Factoring Attack By using the solutions of factoring large numbers in RSA

Secure key transfer

and digital signatures

and digital signatures

and digital signatures

· 32, 64 & 128 bit block sizes

128 bit blocks

Stream cipher

Example PGP

with 8 bits parity.

3 * 56 bit keys

Symmetric/

DES

3 DES or

(Triple DES)

TDES

AES

IDEA

Skipjack

Blowfish

TwoFish

RC4

RC5

CAST

Diffie -

RSA

Elgamal

Elliptic

Curve

m (ECC)

Cryptographic Attacks

Cryptosyste

Frequency

Analysis

Birthday Attack

Engineering

Hellman

Algorithm Asymmetric Key length Based on

Symmetric 64 bit

Symmetric 56 bit*3

symmetric 128 bit

Symmetric 80 bit

Symmetric

Symmetric

Asymmetric

Asymmetric 4096 bit

Asymmetric Any key size Hellman

Asymmetric Any key size

Algebraic Attack Uses known words to find out the keys

patterns in ciphertext.

algorithm

Symmetric 32-448bit

Symmetric 40-2048

Symmetric 2048

128, 192,

CAST 128

(40 to 128

CAST 256

bit)

(128 to 256

Symmetric

The science of hiding the communication messages from

Convert the message as unreadable or meaningless.

Encipher all of the characters with separate unique keys.

A mathematical function used in encryption and decryption of

Rearranging the plaintext to hide the original message; A.K.A.

Exchanging or repeating characters (1 byte) in a message with

Key of a random set of non-repeating characters. A.K.A. One

Changing a key value during each circle of the encryption.

Changing the location of the plaintext inside the cipher text.

When any change in the key or plaintext significantly change

The time and resources needed to break the encryption.

Arbitrary number to provide randomness to cryptographic

Dividing plaintext into blocks and assign similar encryption

Encrypt bit wise - one bit at a time with corresponding digit of

Unauthorized access a trash to find confidential information.

Mislead a person to provide confidential information.

Requirements for Hashing Message Digest

Variable length input - easy to compute - one way function - digital signatures - fixed

length output

MD Hash Algorithms

Merkle-Damgård construction

well funded attackers)

1 hr on standard PC) Retired by NIST

128-bit hash, 18 rounds of computations

Variable, 0<d≤512 bits, Merkle tree structure

with Davies-Meyer compression function

attempting to break encryption keys, algorithm.

Ciphertext-Only An attacker uses multiple encrypted texts to find out the key used for

Known Plaintext An attacker uses plain text and cipher text to find out the key used for

Social Engineering An attacker attempts to trick users into giving their attacker try to

forward that message as cipher text.

device. A.K.A. Side-Channel attacks

Uses linear approximation

Use eavesdropping or packet sniffing to find or gain access to

encryption using reverse engineering or brute force encryption.

impersonate another user to obtain the cryptographic key used.

Try all possible patterns and combinations to find correct key.

An attacker sends a message to another user expecting the user will

Calculate the execution times and power required by the cryptographic

Attacker tries different methods such as message or file modification

Sending spoofed messages as originate from a trusted source.

A moderate level hacker that uses readily found code from the

128-bit hash. 3 rounds of computations, 512 bits block sizes

128-bit hash. 4 rounds of computations, 512 bits block sizes,

Phased out, collision found with a complexity of 2³³.6 (approx

160-bit MD, 80 rounds of computations, 512 bits block sizes,

Merkle-Damgård construction (not considered safe against

224, 256, 384, or 512 bits, 64 or 80 rounds of computations,

512 or 1024 bits block sizes, Merkle-Damgård construction

Segregation of Duties and Dual Control.

Different encryption keys generate the same plaintext

Every possible key value for a specific algorithm.

unauthorized recipients.

data; A.K.A. cipher.

another message.

the ciphertext.

function.

algorithm and key.

the keystream.

The science of encryption.

Cryptography + Cryptanalysis

Convert the message as readable

Cryptography

Cryptology

Decipher

Encipher

One-time pad (OTP)

Key Clustering

Key Space

Algorithm

Cryptology

Transposition

Substitution

Vernam

Confusion

Diffusion

Avalanche Effect

Split Knowledge

Work factor

Nonce

Block Cipher

Stream Cipher

Dumpster Diving

Phishing

Social Engineering

Script kiddie

MD2

MD4

MD5

MD6

SHA-0

SHA-1

SHA-2

Passive Attacks

Active Attacks

Attack

Attack

Chosen Plaintext

Attack

Attack

Brute Force

Differential

Cryptanalysis

Linear

Cryptanalysis

equipment - Monitor and maintain

Heat - High Humidity - Low Humidity

100F can damage storage media

175 F can cause computer and

• 350 F can result in fires due to

HVAC: UPS, and surge protectors

Interference (EMI), Radio Frequency

Computer Rooms should have 15°

C - 23°C temperature and 40 - 60%

40v can damage Circuits, 1000v

cause loss of stored data, 2000v can

cause System shut down or reboot,

Fire proof Safety lockers - Access

control for locking mechanisms

Maintain raised floor and proper

drainage systems. Use of barriers

suppression - Hot Aisle/Cold Aisle

Containment - Fire triangle (Oxygen

Suppression

Water, SODA

acid

CO2, HALON,

SODA acid

CO2, HALON

Dry Powder

Heat - Fuel) - Water, CO2, Halon

such as keys and passwords.

Fire retardant materials - Fire

such as sand bags

Fire extinguishers

Type

Common

combustible

Liquid

Electrical

Metal

· HI VIS clothes

locks

Wet pipes - Dry Pipe - Deluge

Safety garments /Boots

Emergency Plan (OEP)

scanning, Sensors

Passive audio motion

Design and Deploy an Occupant

Programmable multiple control

Electronic Access Control - Digital

Door entry cards and badges for

Motion Detectors- Infrared, Heat

Create, distribute, transmission,

application for key distribution,

should be stored secure by

safety systems to check the

designated person only.

faults.

storage - Automatic integration to

storage, and handling. Backup keys

Pilot testing for all the backups and

working condition and to find any

Based, Wave Pattern, Photoelectric,

Flickering monitors, 1500v can

17000 v can cause complete

electronic circuit damage.

electrical equipment damage

to prevent electric surcharge.

Noise: Electromagnetic

Temperatures, Humidity

Interference

(Humidity)

Static Voltage

humidity levels.

such as tape drives.

paper based products.

Electricity

HVAC control

levels

HVAC

Guidelines

Voltage levels

control

Equipment

safety

Water leakage

Fire safety

Class

Water based

suppression

systems

Personnel

safety

Internal

Security

Key

management

Testing

Secret key is divided into two parts and handover to a third party.

PKI

confidentiality, message integrity, authentication, and nonrepudiation

Receiver's Public Key-Encrypt message

Sender Private Key-Decrypt message

Sender Private Key-Digitally sign

Sender's Public Key - Verify Signature

PKI Structure

certificates.

Help CA with verification.

Valid certificates list

Certificate validity from top level.

Used to check certificate validity online

Digital Signatures

Digital signature is generated by the user's public key and validity period according to

Digital Certificate - Steps

Enrollment - Verification - Revocation

Cryptography Applications & Secure Protocols

• BitLocker: Windows full volume encryption feature (Vista

A hardware chip installed on a motherboard used to manage

Encrypts entire packet components except Data Link Control

Privacy (Encrypt), Authentication (Digital signature), Integrity,

(Hash) and Non-repudiation (Digital signature) Email (Secure

MIME (S/MIME): Encryption for confidentiality, Hashing for

integrity, Public key certificates for authentication, and

SSL/TLS. SSL encryption, authentication and integrity.

(Privacy, authentication, Integrity, Non Repudiation)

Tunnel mode encrypt whole packet (Secure). Transport mode

Authentication Header (AH): Authentication, Integrity, Non-

repudiation. Encapsulated Security Payload (ESP): Privacy

Authentication, and Integrity. Security Association (SA):

Internet Security Association Key Management Protocol

Key exchange used by IPsec .Consists of OAKLEY and

Authentication, use to create and manage SA, key generation.

Internet Security Association and Key Management Protocol

(ISAKMP). IKE use Pre-Shared keys, certificates, and public key

Wired Equivalent Privacy (WEP): 64 & 128 bit encryption. Wi-Fi

Protected Access (WPA): Uses TKIP. More secure than WEP

WPA2: Uses AES. More secure than WEP and WPA.

Create a trust relationship between two CA's

Distinct Identifier of a secure connection.

Message Digests for nonrepudiation.

encrypt payload (Faster)

authentication.

truecrypt: freeware utility for on-the-fly encryption

Symmetric and asymmetric keys, hashes, and digital

certificates. TPM protect passwords, encrypt drives, and

Packet routing, headers, and addresses not encrypted.

Create a trust relationship between two CA's

Provides authorization between the parties verified by CA.

Authority performing verification of identities and provides

Certificates

Certificate Authority

Registration Authority

Certification Path

Validation

Certification Revocation

List

Online Certificate status

protocol (OCSP)

Cross-Certification

Hardware -BitLocker and

truecrypt

Hardware-Trusted

Platform Module (TPM)

Link encryption

End to end encryption

Email (PGP)

Web application

Cross-Certification

IPSEC

IPSEC components

ISAKMP

Internet Key Exchange

(IKE)

Wireless encryption

Sender's private key used to encrypt hash value

Provides authentication, nonrepudiation, and integrity

Public key cryptography used to generate digital signatures

Users register public keys with a certification authority (CA).

the certificate issuer and digital signature algorithm identifier.

(discontinued)

information.

manage digital permissions.

Domain 4: Network and Communication Security		Common TCP Protocols		CISSP Cheat Sheet Series				
C	OSI Reference Model	Port Protocol 20,21 FTP			IP Addresses		Port Ranges	
7 layers, Allow changes bet	etween layers, Standard hardware/software interoperability. Tip, OSI Mnemonics	22 23	SSH TELNET	Public IPv4 address space	• Class A: 0.0.0.0 - 127.255.255.255 • Class B: 128.0.0.0 - 191.255.255.255	Point to Point Tunneling Protoco	Authentication methods: • PAP=Clear text, unencrypted	
	ople Seem To Need Data Processing Do Not Throw Sausage Pizza Away	25	SMTP DNS	Private IPv4	• Class C: 192.0.0.0 - 223.255.255 • Class A: 10.0.0.0 - 10.255.255.255		CHAP=unencrypted, encrypted MS-CHAP=encrypted, encrypted	
Layer Application	Data Security Data C, I, AU, N	53 110	POP3	address space	• Class C: 192.168.0.0 - 192.168.255.255	Challenge-Handshake Authent Protocol (CHAP)	ntication Encrypt username/password and re-authenticate periodically. Use in PPP.	
Presentation Session	Data C, AU, Encryption Data N	80 143	HTTP IMAP	Subnet Masks	• Class A: 255.0.0.0 • Class B: 255.255.0.0 • Class C: 255.255.255.0	Layer 2 Tunneling Protocol (I	, ,	
Transport	Segment C, AU, I	389 443	LDAP HTTPS	IPv4	32 bit octets	Authentication Header (A	AH) Provide authentication and integrity, no confidentiality.	
Network Data link	Packets C, AU, I Frames C	636 445	Secure LDAP ACTIVE DIRECTORY	IPv6	128 bit hexadecimal Network Types	Encapsulating Security Payloa	, ,	
Physical C=Confidentiali	Bits C ity, AU=Authentication, I=Integrity, N=Non repudiation	1433 3389	Microsoft SQL RDP	Local Area	Geographic Distance and are is limited to one	Security Associations (SA	network entities.	
Layer (No) Fun	nctions Protocols Hardware / Formats	137-139	NETBIOS	Network (LAN)	Tiber optics	Transport Mode Tunnel Mode	Payload is protected. IP payload and IP header are protected.	
Physical (1) Electrical sign			in OSI layers	Campus Area Network (CAN)	Multiple buildings connected over fiber or wireless	Internet Key Exchange (IK Remote Authentication Dial-In Us		
Bits to voltage	e Repeaters, ATM	Layer	Attack Phishing - Worms -	Metropolitan Area Network	Metropolitan network span within cities	(RADIUS) SNMP v3	authentication with cleartext. Encrypts the passwords.	
Frames setup Error detection	on and control RARP - SNAP - CHAP - I CP - I aver 2	Application	Trojans Phishing - Worms -	(MAN) Wide Area	Interconnect LANs over large geographic area	Dynamic Ports	49152 - 65535	
-3 - ()	ddress, Frames MLP - Frame Relay - HDLC - Switch -	Presentation Session	Trojans Session hijack	network (WAN) Intranet	such as between countries or regions. A private internal network	Remo	ote Access Services	
use in MAC to conversion.	Ring - FDDI	Transport	SYN flood - fraggle	Extranet	connects external authorized persons access to intranet	Telnet Remote login (rlogin)	Username /Password authentication. No encryption. No password protection.	
Network layer	n, logical BOOTP - DHCP - ICMP Switch -	Network	smurfing flooding - ICMP spoofing - DOS	Internet	Public network	SSH (Secure Shell) Terminal Access Controller	Secure telnet User credentials are stored in a server known as a	
addressing. A	TCP - UDP datagrams.	Data link	Collision - DOS /DDOS - Eavesdropping	Netwo Software	Orking Methods & Standards Decoupling the network control and the	Access-Control System (TACACS)	TACACS server. User authentication requests are handled by this server.	
Transport Segment - Coroniented	nnection transfer - VPN	Physical	Signal Jamming - Wiretapping	defined networking	forwarding functions. Features -Agility, Central management,	TACACS+	More advanced version of TACACS. Use two factor authentication.	
	and error checking rs - Gateway	Hardw	are Devices	(SDN) Converged	Programmatic configuration, Vendor neutrality.	Remote Authentication Dial-In User Service (RADIUS)	Client/server protocol use to enable AAA services for remote access servers.	
Session Data, simplex, Layer dupl Eg. peer	t, half duplex, full connections. TCP - UDP - NSF - SQL - RADIUS - and RPC - PPTP - Gateways	нив	Layer 1 device forward frames via all ports	protocols for media transfer	Transfer voice, data, video, images, over single network.	USEI SEIVICE (KADIUS)	Secure and encrypted communication channel	
Presentation Data	Gateways	Modem	digital to analog conversion	Fibre Channel over Ethernet	Running fiber over Ethernet network.	Virtual private network (VPN)	between two networks or between a user and a network. Use NAT for IP address conversion. Secured with strong encryptions such as L2TP or IPSEC.	
Presentation	/decompression TCP - UDP messages JPEG - TIFF -	Routers	Interconnect networks Interconnect networks in	(FCoE) Multiprotocol				
Application Date	TCP - UDP - FTP - TELNET - TFTP - SMTP - HTTP CDP -	Bridge	Ethernet Inbound/outbound data	Label Switching	Transfer data based on the short path labels instead of the network IP addresses. No need of route table lookups	VPN	• PPP for authentication	
layer	SMB - SNMP - NNTP - SSL - HTTP/HTTPS.	Gateways	entry points for networks Frame forward in local	(MPLS) Internet Small	route table lookups. Standard for connecting data storage sites such	Point-to-Point Tunneling Protocol	No support for EAP	
	TCP/IP Model	Switch	network.	Computer Interface (ISCI)	as storage area networks or storage arrays.	(PPTP)	Connection setup uses plaintextData link layer	
Layers	Action Example Protocols	Load balancers	Share network traffic load by distributing traffic between two	Multilayer	Encryption and different protocols at different levels. Disadvantages are hiding coveted channels	Lover 2 Tuesdie - D	Single connection per session Same as PPTP except more secure	
	Token ring • Frame Relay • FDDI • Ethernet • X.25		devices	Protocols Voice over	and weak encryptions.	Layer 2 Tunneling Protocol (L2TP	Commonly uses IPsec to secure L2TP packets Network layer	
Internet datag	te small data chunks called grams to be transferred via network access layer	Proxies	Hide internal public IP address from external public internet	Internet Protocol (VoIP)	Allows voice signals to be transferred over the public Internet connection.	Internet Protocol Security (IPsec)	Multiple connection per session	
Transport Fl	low control and integrity TCP • UDP	Ploxies	/Connection caching and filtering.	Asynchronous	Packet switching technology with higher	0	• Confidentiality and integrity	
Application	format Telnet • SSH • DNS • HTTP • FTP • SNMP • DHCP		Use to create VPN or aggregate VPN	transfer mode (ATM)	demand bandwidth allocation. Use fiber optics. Popular among ISPs	Divides connec	ication Hardware Devices acted devices into one input signal for transmission over	
T	CP 3-way Handshake	VPNs and VPN concentrators	connections provide using different internet	X25	PTP connection between Data terminal equipment (DTE) and data circuit-terminating equipment	concentrator one output via		
	SYN - SYN/ACK - ACK		links Capture or monitor		(DCE) Use with ISDN interfaces. Faster and use multiple	Hubs Retransmit sign	gnal received from one port to all ports.	
Topology	LAN Topologies Pros Cons	Protocol analyzers	· .	Frame Relay	PVCs, provides CIR. Higher performance. Need to have DTE/DCE at each connection point. Perform	Repeater Amplifies signa	·	
BUS	No redundancy Simple to setup Single point of failure	Unified threat	New generation vulnerability scanning	Synchronous	error correction.	Circuit-switched • Dedicate	Transmission Types ted permanent circuits or communication paths required.	
	Difficult to troubleshoot	management	application Create collision	Data Link Control (SDLC)	IBM proprietary protocol use with permanent dedicated leased lines.	networks • Stable sp • Mostly u	speed. Delay sensitive. used by ISPs for telephony.	
RING Start	 Fault tolerance Fault tolerance Single point of failure 	VLANs	domains. Routers	High-level Data	,	• Fixed siz	ize packets are sending between nodes and share	
			separate broadcast	Link Control	Use DTE/DCE communications. Extended	Packet-switched bandwidth	th.	
Mesh	Fault toleranceRedundantExpensive to setup		separate broadcast domains Intrusion detection and	(HDLC)	protocol for SDLC.	networks • Delay se	th.	
Types of D	Digital Subscriber Lines (DSL)	IDS/IPS	domains	(HDLC) Domain name	protocol for SDLC. Map domain names /host names to IP Address and vice versa.	networks • Delay se • Use virtu	th. ensitive. tual circuits therefore less expensive. ireless Networking	
Types of Day Asymmetric Digital Subscriber Line Na	• Fault tolerance • Expensive to setup Digital Subscriber Lines (DSL) with the setup of the se	Firewall a	Intrusion detection and prevention. and Perimeter	(HDLC) Domain name	protocol for SDLC. Map domain names /host names to IP Address	networks • Delay se • Use virtu	th. ensitive. cual circuits therefore less expensive.	
Types of D Asymmetric Digital Subscriber Line (ADSL) Rate Adaptive DSL • Upl	• Fault tolerance • Expensive to setup Digital Subscriber Lines (DSL) with white the setup of	Firewall a	Intrusion detection and prevention. and Perimeter ecurity	(HDLC) Domain name system (DNS) T1 T3	DIE/DCE communications. Extended protocol for SDLC. Map domain names /host names to IP Address and vice versa. Leased Lines 1.544Mbps via telephone line 45Mbps via telephone line	networks • Delay se • Use virtu Wireless person IEEE 802.15 IEEE 802.3	th. ensitive. tual circuits therefore less expensive. ireless Networking nal area network (WPAN) standards Bluetooth Ethernet	
Types of D Asymmetric Digital	• Expensive to setup Digital Subscriber Lines (DSL) winload speed higher than upload eximum 5500 meters distance via telephone lines. eximum download 8Mbps, upload 800Kbps. load speed adjust based on quality of the transmission line eximum 7Mbps download, 1Mbps upload over 5500 meters. me rate for upstream and downstream transmission rates.	Firewall a Sec DMZ Sec (Demilitarized extension	domains Intrusion detection and prevention. and Perimeter ecurity cure network between ternal internet facing and	(HDLC) Domain name system (DNS) T1 T3 ATM ISDN	Use DTE/DCE communications. Extended protocol for SDLC. Map domain names /host names to IP Address and vice versa. Leased Lines 1.544Mbps via telephone line 45Mbps via telephone line 155Mbps 64 or 128 Kbps REPLACED BY xDSL	networks • Delay se • Use virtu Wireless person IEEE 802.15	th. ensitive. cual circuits therefore less expensive. ireless Networking nal area network (WPAN) standards Bluetooth Ethernet Wi-Fi LTE	
Types of D Asymmetric Digital Subscriber Line (ADSL) Rate Adaptive DSL (RADSL) Symmetric Digital Subscriber Line • Dis	• Fault tolerance • Expensive to setup Digital Subscriber Lines (DSL) with white white the set of	Firewall a Sec (Demilitarized exterior cone)	domains Intrusion detection and prevention. and Perimeter ecurity cure network between	(HDLC) Domain name system (DNS) T1 T3 ATM ISDN Reserved BRI B-chan	Use DTE/DCE communications. Extended protocol for SDLC. Map domain names /host names to IP Address and vice versa. Leased Lines 1.544Mbps via telephone line 45Mbps via telephone line 155Mbps 64 or 128 Kbps REPLACED BY xDSL ad 1024-49151 hnel 64 Kbps	networks • Delay se • Use virtu Wireless person IEEE 802.15 IEEE 802.3 IEEE 802.11	th. ensitive. fual circuits therefore less expensive. ireless Networking nal area network (WPAN) standards Bluetooth Ethernet Wi-Fi	
Types of I Asymmetric Digital Subscriber Line (ADSL) Rate Adaptive DSL (RADSL) Symmetric Digital Subscriber Line (SDSL) Very-high-bit-rate DSL (VDSL)	• Fault tolerance • Expensive to setup Digital Subscriber Lines (DSL) winload speed higher than upload eximum 5500 meters distance via telephone lines. eximum download 8Mbps, upload 800Kbps. Iload speed adjust based on quality of the transmission line eximum 7Mbps download, 1Mbps upload over 5500 meters. Immerate for upstream and downstream transmission rates. Estance 6700 meters via copper telephone cables eximum 2.3Mbps download, 2.3Mbps upload. Igher speeds than standard ADSL Eximum 52Mbps download, 16 Mbps upload up to 1200	DMZ Sec (Demilitarized zone) Section Host - Dua Screened Subnet -	Intrusion detection and prevention. and Perimeter ecurity cure network between ternal internet facing and ternal networks.	(HDLC) Domain name system (DNS) T1 T3 ATM ISDN Reserved	Use DTE/DCE communications. Extended protocol for SDLC. Map domain names /host names to IP Address and vice versa. Leased Lines 1.544Mbps via telephone line 45Mbps via telephone line 155Mbps 64 or 128 Kbps REPLACED BY xDSL ad 1024-49151 annel 64 Kbps annel 16 Kbps	networks • Delay se • Use virtu Wireless person IEEE 802.15 IEEE 802.3 IEEE 802.11 IEEE 802.20 Standard 802.11a	th. ensitive. fual circuits therefore less expensive. ireless Networking nal area network (WPAN) standards Bluetooth Ethernet Wi-Fi LTE Wi-Fi Speed Frequency (GHz) 54 Mbps 2.4	
Types of E Asymmetric Digital Subscriber Line (ADSL) Rate Adaptive DSL (RADSL) Symmetric Digital Subscriber Line (SDSL) Very-high-bit-rate DSL (VDSL) High-bit-rate DSL T1 si	• Fault tolerance • Expensive to setup Digital Subscriber Lines (DSL) ewnload speed higher than upload eximum 5500 meters distance via telephone lines. eximum download 8Mbps, upload 800Kbps. Iload speed adjust based on quality of the transmission line eximum 7Mbps download, 1Mbps upload over 5500 meters. Immerate for upstream and downstream transmission rates. Estance 6700 meters via copper telephone cables eximum 2.3Mbps download, 2.3Mbps upload. Igher speeds than standard ADSL Eximum 52Mbps download, 16 Mbps upload up to 1200 Esters In the setup.	DMZ Sec (Demilitarized zone) Section Host - Dua Screened Subnet -	Intrusion detection and prevention. and Perimeter ecurity cure network between remal internet facing and ernal networks. al-Homed - Three-Legged - Proxy Server - PBX - Honey ot - IDS/IPS	(HDLC) Domain name system (DNS) T1 T3 ATM ISDN Reserved BRI B-chan BRI D-chan PRI B & D cha	Use DTE/DCE communications. Extended protocol for SDLC. Map domain names /host names to IP Address and vice versa. Leased Lines 1.544Mbps via telephone line 45Mbps via telephone line 155Mbps 64 or 128 Kbps REPLACED BY xDSL ed 1024-49151 ennel 64 Kbps ennel 16 Kbps ennel 64 Kbps ennel 64 Kbps	networks • Delay se • Use virtu Wireless person IEEE 802.15 IEEE 802.3 IEEE 802.11 IEEE 802.20 Standard 802.11a 802.11b 802.11g	th. ensitive. tual circuits therefore less expensive. Freless Networking nal area network (WPAN) standards Bluetooth Ethernet Wi-Fi LTE Wi-Fi Speed Frequency (GHz) 54 Mbps 2.4 11 Mbps 5 54 Mbps 2.4	
Types of E Asymmetric Digital Subscriber Line (ADSL) Rate Adaptive DSL (RADSL) Symmetric Digital Subscriber Line (SDSL) Very-high-bit-rate DSL (VDSL) High-bit-rate DSL (HDSL) Committed To over the control of the co	• Expensive to setup Digital Subscriber Lines (DSL) winload speed higher than upload eximum 5500 meters distance via telephone lines. eximum download 8Mbps, upload 800Kbps. Iload speed adjust based on quality of the transmission line eximum 7Mbps download, 1Mbps upload over 5500 meters. Immerate for upstream and downstream transmission rates. Estance 6700 meters via copper telephone cables eximum 2.3Mbps download, 2.3Mbps upload. Igher speeds than standard ADSL Eximum 52Mbps download, 16 Mbps upload up to 1200 Interest of two copper cables for 3650 meters	DMZ Sec (Demilitarized zone) Bastion Host - Dua Screened Subnet - Po	Intrusion detection and prevention. and Perimeter ecurity cure network between ternal internet facing and ternal networks. al-Homed - Three-Legged - Proxy Server - PBX - Honey ot - IDS/IPS Malicious software	(HDLC) Domain name system (DNS) T1 T3 ATM ISDN Reserved BRI B-chan BRI D-chan PRI B & D cha	Use DTE/DCE communications. Extended protocol for SDLC. Map domain names /host names to IP Address and vice versa. Leased Lines 1.544Mbps via telephone line 45Mbps via telephone line 155Mbps 64 or 128 Kbps REPLACED BY xDSL ad 1024-49151 anel 64 Kbps annels 64 Kbps annels 64 Kbps	* Delay se * Use virtu **Wireless person** IEEE 802.15 IEEE 802.3 IEEE 802.11 IEEE 802.20 **Standard** 802.11a 802.11b 802.11g 802.11n 802.11a	th. ensitive. cual circuits therefore less expensive. ireless Networking nal area network (WPAN) standards Bluetooth Ethernet Wi-Fi LTE Wi-Fi Speed Frequency (GHz) 54 Mbps 2.4 11 Mbps 5 54 Mbps 2.4 200+ Mbps 2.4/5 1Gbps 5	
Types of I Asymmetric Digital Subscriber Line (ADSL) Rate Adaptive DSL (RADSL) Symmetric Digital Subscriber Line (SDSL) Very-high-bit-rate DSL (VDSL) High-bit-rate DSL (HDSL) Committed Information Rate (CIR)	• Fault tolerance • Expensive to setup Digital Subscriber Lines (DSL) Invalidad speed higher than upload eximum 5500 meters distance via telephone lines. Eximum download 8Mbps, upload 800Kbps. Iload speed adjust based on quality of the transmission line eximum 7Mbps download, 1Mbps upload over 5500 meters. Immerate for upstream and downstream transmission rates. Estance 6700 meters via copper telephone cables eximum 2.3Mbps download, 2.3Mbps upload. Igher speeds than standard ADSL eximum 52Mbps download, 16 Mbps upload up to 1200 ers Immum guaranteed bandwidth provided by service provider.	DMZ Sec exterior (Demilitarized zone) Bastion Host - Dua Screened Subnet - Po	domains Intrusion detection and prevention. and Perimeter ecurity cure network between dernal internet facing and dernal networks. al-Homed - Three-Legged - Proxy Server - PBX - Honey ot - IDS/IPS No Malicious software Self propagating virit be Time or condition location.	(HDLC) Domain name system (DNS) T1 T3 ATM ISDN Reserved BRI B-chan BRI D-chan PRI B & D cha	Use DTE/DCE communications. Extended protocol for SDLC. Map domain names /host names to IP Address and vice versa. Leased Lines 1.544Mbps via telephone line 45Mbps via telephone line 155Mbps 64 or 128 Kbps REPLACED BY xDSL and 1024-49151 anel 64 Kbps annels 64 Kbps annels 64 Kbps acks ables	networks • Delay se • Use virtu Wireless person IEEE 802.15 IEEE 802.3 IEEE 802.11 IEEE 802.20 Standard 802.11a 802.11b 802.11g 802.11n 802.11ac • 802.11 use CSMA/CA protocol action in the second possible in the second poss	th. ensitive. cual circuits therefore less expensive. ireless Networking nal area network (WPAN) standards Bluetooth Ethernet Wi-Fi LTE Wi-Fi Speed Frequency (GHz) 54 Mbps 2.4 11 Mbps 5 54 Mbps 2.4 200+ Mbps 2.4 200+ Mbps 5 1Gbps 5 I as DSSS or FHSS	
Types of E Asymmetric Digital Subscriber Line (ADSL) Rate Adaptive DSL (RADSL) Symmetric Digital Subscriber Line (SDSL) Very-high-bit-rate DSL (VDSL) High-bit-rate DSL (HDSL) Committed Information Rate (CIR) To over the control of the contro	• Expensive to setup Digital Subscriber Lines (DSL) winload speed higher than upload eximum 5500 meters distance via telephone lines. eximum download 8Mbps, upload 800Kbps. Iload speed adjust based on quality of the transmission line eximum 7Mbps download, 1Mbps upload over 5500 meters. Immerate for upstream and downstream transmission rates. Estance 6700 meters via copper telephone cables eximum 2.3Mbps download, 2.3Mbps upload. Igher speeds than standard ADSL Eximum 52Mbps download, 16 Mbps upload up to 1200 Interest of two copper cables for 3650 meters	DMZ Sec extented zone) Bastion Host - Dua Screened Subnet - Po Virus Worms	domains Intrusion detection and prevention. and Perimeter ecurity cure network between dernal internet facing and dernal networks. al-Homed - Three-Legged - Proxy Server - PBX - Honey ot - IDS/IPS No Malicious software Self propagating virit be Time or condition location.	(HDLC) Domain name system (DNS) T1 T3 ATM ISDN Reserved BRI B-chan BRI D-chan PRI B & D cha	Use DTE/DCE communications. Extended protocol for SDLC. Map domain names /host names to IP Address and vice versa. Leased Lines 1.544Mbps via telephone line 45Mbps via telephone line 155Mbps 64 or 128 Kbps REPLACED BY xDSL ad 1024-49151 anel 64 Kbps annels 64 Kbps annels 64 Kbps	Nireless person IEEE 802.15 IEEE 802.3 IEEE 802.11 IEEE 802.20 Standard 802.11a 802.11b 802.11g 802.11n 802.11ac • 802.11 use CSMA/CA protocol action of the second of th	th. ensitive. cual circuits therefore less expensive. reless Networking nal area network (WPAN) standards Bluetooth Ethernet Wi-Fi LTE Wi-Fi Speed Frequency (GHz) 54 Mbps 2.4 11 Mbps 5 54 Mbps 2.4 200+ Mbps 2.4/5 1Gbps 5 I as DSSS or FHSS eless Security Protocols	
Types of E Asymmetric Digital Subscriber Line (ADSL) Rate Adaptive DSL (RADSL) Symmetric Digital Subscriber Line (SDSL) Very-high-bit-rate DSL (VDSL) High-bit-rate DSL (HDSL) Committed Information Rate (CIR) Unicast Multicast	Digital Subscriber Lines (DSL) whole which speed higher than upload eximum 5500 meters distance via telephone lines. Eximum download 8Mbps, upload 800Kbps. Ilload speed adjust based on quality of the transmission line eximum 7Mbps download, 1Mbps upload over 5500 meters. The rate for upstream and downstream transmission rates. Estance 6700 meters via copper telephone cables eximum 2.3Mbps download, 2.3Mbps upload. The speeds than standard ADSL eximum 52Mbps download, 16 Mbps upload up to 1200 ers. The provided by service provider.	Firewall a Sec (Demilitarized zone) Bastion Host - Dua Screened Subnet - Po Virus Worms Logic Bomb Trojan Backdoor	Intrusion detection and prevention. and Perimeter ecurity cure network between ernal internet facing and ernal networks. al-Homed - Three-Legged - Proxy Server - PBX - Honey ot - IDS/IPS Nalicious software Self propagating virus of code and/or executable in the code and/o	(HDLC) Domain name system (DNS) T1 T3 ATM ISDN Reserved BRI B-chan BRI D-chan PRI B & D cha PRI B & D cha Ictwork Atta e, code and executa iruses locked virus utables that act as let execution entry	Use DTE/DCE communications. Extended protocol for SDLC. Map domain names /host names to IP Address and vice versa. Leased Lines 1.544Mbps via telephone line 45Mbps via telephone line 155Mbps 64 or 128 Kbps REPLACED BY xDSL and 1024-49151 anel 64 Kbps annels 64 Kbps annels 64 Kbps acks ables	wireless person IEEE 802.15 IEEE 802.3 IEEE 802.11 IEEE 802.20 Standard 802.11a 802.11b 802.11g 802.11n 802.11ac • 802.11 use CSMA/CA protocol acceptable wireless • 802.11b uses only DSSS Wireless person REEE 802.20 Standard 802.11a 802.11b 802.11b 802.11b 802.11c • 802.11 use CSMA/CA protocol acceptable wireless • 802.11 b uses only DSSS	th. ensitive. cual circuits therefore less expensive. ireless Networking nal area network (WPAN) standards Bluetooth Ethernet Wi-Fi LTE Wi-Fi Speed Frequency (GHz) 54 Mbps 2.4 11 Mbps 5 54 Mbps 2.4 200+ Mbps 2.4 200+ Mbps 5 1Gbps 5 I as DSSS or FHSS	
Asymmetric Digital Subscriber Line (ADSL) Rate Adaptive DSL (RADSL) Symmetric Digital Subscriber Line (SDSL) Very-high-bit-rate DSL (VDSL) High-bit-rate DSL (HDSL) Committed Information Rate (CIR) Unicast Multicast Broadcast Carrier-sense Multiple	Digital Subscriber Lines (DSL) winload speed higher than upload aximum 5500 meters distance via telephone lines. aximum download 8Mbps, upload 800Kbps. load speed adjust based on quality of the transmission line aximum 7Mbps download, 1Mbps upload over 5500 meters. me rate for upstream and downstream transmission rates. stance 6700 meters via copper telephone cables aximum 2.3Mbps download, 2.3Mbps upload. gher speeds than standard ADSL aximum 52Mbps download, 16 Mbps upload up to 1200 ers speed for two copper cables for 3650 meters imum guaranteed bandwidth provided by service provider. N Packet Transmission Single source send to single destination Single source send to all the destinations. One workstations retransmits frames until destination	Firewall a Sec (Demilitarized zone) Bastion Host - Dua Screened Subnet - Po Virus Worms Logic Bomb Trojan	Intrusion detection and prevention. and Perimeter ecurity cure network between ernal internet facing and ernal networks. al-Homed - Three-Legged - Proxy Server - PBX - Honey ot - IDS/IPS No Malicious software Self propagating virts of the Code and/or execut malicious Unauthorized code A series of small at scale attack	(HDLC) Domain name system (DNS) T1 T3 ATM ISDN Reserved BRI B-chan BRI D-chan PRI B & D cha PRI B & D cha Ictwork Atta e, code and executa iruses locked virus utables that act as lee execution entry ttacks and network	Use DTE/DCE communications. Extended protocol for SDLC. Map domain names /host names to IP Address and vice versa. Leased Lines 1.544Mbps via telephone line 45Mbps via telephone line 155Mbps 64 or 128 Kbps REPLACED BY xDSL and 1024-49151 anel 64 Kbps annels 16 Kbps annels 64 Kbps annels 64 Kbps acks ables legitimate software, but are not legitimate and are k intrusions that culminate in a cumulative large	Nireless person IEEE 802.15 IEEE 802.3 IEEE 802.11 IEEE 802.20 Standard 802.11a 802.11b 802.11g 802.11n 802.11ac • 802.11 use CSMA/CA protocol action of the second of th	th. ensitive. cual circuits therefore less expensive. ireless Networking nal area network (WPAN) standards Bluetooth Ethernet Wi-Fi LTE Wi-Fi Speed Frequency (GHz) 54 Mbps 2.4 11 Mbps 5 54 Mbps 2.4 200+ Mbps 2.4/5 1Gbps 5 I as DSSS or FHSS eless Security Protocols rectly connects peer-to-peer mode clients without a entral access point.	
Asymmetric Digital Subscriber Line (ADSL) Rate Adaptive DSL (RADSL) Symmetric Digital Subscriber Line (SDSL) Very-high-bit-rate DSL (VDSL) High-bit-rate DSL (HDSL) Committed Information Rate (CIR) Unicast Multicast Broadcast Carrier-sense Multiple Access (CSMA) CSMA with Collision	• Fault tolerance • Expensive to setup Digital Subscriber Lines (DSL) winload speed higher than upload eximum 5500 meters distance via telephone lines. aximum download 8Mbps, upload 800Kbps. Iload speed adjust based on quality of the transmission line eximum 7Mbps download, 1Mbps upload over 5500 meters. Imerate for upstream and downstream transmission rates. Istance 6700 meters via copper telephone cables eximum 2.3Mbps download, 2.3Mbps upload. Igher speeds than standard ADSL Indiana Symbols download, 16 Mbps upload up to 1200 errs Impered for two copper cables for 3650 meters Impered for two copper cables for 3650	Firewall a Sec (Demilitarized zone) Bastion Host - Dua Screened Subnet - Po Virus Worms Logic Bomb Trojan Backdoor Salami, salami si Data diddling Sniffing	Intrusion detection and prevention. and Perimeter ecurity cure network between remal internet facing and ernal networks. al-Homed - Three-Legged - Proxy Server - PBX - Honey ot - IDS/IPS No Malicious software Self propagating virible Time or condition located and/or execut malicious Unauthorized code Slicing A series of small at scale attack ag Alteration of raw day unauthorized monitor and capture and ca	(HDLC) Domain name system (DNS) T1 T3 ATM ISDN Reserved BRI B-chan BRI D-chan PRI B & D cha PRI B & D cha Ictwork Atta e, code and executa iruses locked virus utables that act as let execution entry ttacks and network ata before process itoring of transmitt	Use DTE/DCE communications. Extended protocol for SDLC. Map domain names /host names to IP Address and vice versa. Leased Lines 1.544Mbps via telephone line 45Mbps via telephone line 155Mbps 64 or 128 Kbps REPLACED BY xDSL and 1024-49151 annel 64 Kbps annels 16 Kbps annels 64 Kbps acks ables legitimate software, but are not legitimate and are k intrusions that culminate in a cumulative large sing ted data	Wireless person IEEE 802.15 IEEE 802.3 IEEE 802.11 IEEE 802.20 Standard 802.11a 802.11b 802.11g 802.11n 802.11ac • 802.11 use CSMA/CA protocol at 802.11b uses only DSSS Wireless person Standard 802.11b 802.11c • 802.11b 802.11c • 8	th. ensitive. rual circuits therefore less expensive. ireless Networking nal area network (WPAN) standards Bluetooth Ethernet Wi-Fi LTE Wi-Fi Speed Frequency (GHz) 54 Mbps 2.4 11 Mbps 5 54 Mbps 2.4 200+ Mbps 2.4/5 1Gbps 5 I as DSSS or FHSS eless Security Protocols rectly connects peer-to-peer mode clients without a entral access point. itents connect centrally via access point. brifidentiality, uses RC4 for encryption. ses Temporal Key Integrity Protocol (TKIP) for data	
Asymmetric Digital Subscriber Line (ADSL) Rate Adaptive DSL (RADSL) Symmetric Digital Subscriber Line (SDSL) Very-high-bit-rate DSL (VDSL) High-bit-rate DSL (HDSL) Committed Information Rate (CIR) Unicast Multicast Broadcast Carrier-sense Multiple Access (CSMA) CSMA with Collision Detection (CSMA/CD) COMMITCE ADA DOA Ma DOA DOA DOA DOA DOA DOA DOA DO	• Fault tolerance • Expensive to setup Digital Subscriber Lines (DSL) winload speed higher than upload eximum 5500 meters distance via telephone lines. eximum download 8Mbps, upload 800Kbps. Iload speed adjust based on quality of the transmission line eximum 7Mbps download, 1Mbps upload over 5500 meters. Ime rate for upstream and downstream transmission rates. Istance 6700 meters via copper telephone cables eximum 2.3Mbps download, 2.3Mbps upload. Igher speeds than standard ADSL eximum 52Mbps download, 16 Mbps upload up to 1200 Interest speed for two copper cables for 3650 meters Imum guaranteed bandwidth provided by service provider. N Packet Transmission Single source send to single destinations Source packet send to all the destinations. One workstations retransmits frames until destination workstation receives. Terminates transmission on collision detection. Used by Ethernet. Upon detecting a busy transmission, pauses and then	Pirewall a Sec (Demilitarized zone) Bastion Host - Dua Screened Subnet - Po Virus Worms Logic Bomb Trojan Backdoor Salami, salami si Data diddling Sniffing Session Hijack	Intrusion detection and prevention. and Perimeter ecurity cure network between ernal internet facing and ernal networks. al-Homed - Three-Legged - Proxy Server - PBX - Honey ot - IDS/IPS Nalicious software Self propagating virtime or condition locate and/or execut malicious Unauthorized code A series of small at scale attack and unauthorized monit king Monitor and capture credentials	(HDLC) Domain name system (DNS) T1 T3 ATM ISDN Reserved BRI B-chan BRI D-chan PRI B & D cha PRI B & D cha Ictwork Atta e, code and executa iruses locked virus utables that act as let execution entry ttacks and network ata before process itoring of transmitt re of authentication	Disc DTE/DCE communications. Extended protocol for SDLC. Map domain names /host names to IP Address and vice versa. Leased Lines 1.544Mbps via telephone line 45Mbps via telephone line 155Mbps 64 or 128 Kbps REPLACED BY xDSL dd 1024-49151 nnel 64 Kbps nnel 16 Kbps annels 64 Kbps acks ables Legitimate software, but are not legitimate and are k intrusions that culminate in a cumulative large sing ted data n sessions with the purpose of finding and hijacking	Wireless person IEEE 802.15 IEEE 802.3 IEEE 802.11 IEEE 802.20 Standard 802.11a 802.11b 802.11g 802.11n 802.11ac • 802.11 use CSMA/CA protocol (* 802.11 b uses only DSSS Wire Ad-hoc Mode Infrastructure Mode VEP (Wired Equivalent Privacy) WPA (Wi-Fi Protected Access) WPA2 Use	th. ensitive. tual circuits therefore less expensive. Ireless Networking nal area network (WPAN) standards Bluetooth Ethernet Wi-Fi LTE Wi-Fi Speed Frequency (GHz) 54 Mbps 2.4 11 Mbps 5 54 Mbps 2.4 200+ Mbps 2.4/5 1Gbps 5 I as DSSS or FHSS eless Security Protocols rectly connects peer-to-peer mode clients without a entral access point. itents connect centrally via access point. confidentiality, uses RC4 for encryption. ses Temporal Key Integrity Protocol (TKIP) for data acceptation. ses AES, key management.	
Asymmetric Digital Subscriber Line (ADSL) Rate Adaptive DSL (RADSL) Symmetric Digital Subscriber Line (SDSL) Very-high-bit-rate DSL (VDSL) High-bit-rate DSL (HDSL) Committed Information Rate (CIR) Unicast Multicast Broadcast Carrier-sense Multiple Access (CSMA) CSMA with Collision Detection (CSMA/CD) CSMA with Collision Avoidance (CSMA/CA)	• Fault tolerance • Expensive to setup Digital Subscriber Lines (DSL) winload speed higher than upload aximum 5500 meters distance via telephone lines. aximum download 8Mbps, upload 800Kbps. Iload speed adjust based on quality of the transmission line aximum 7Mbps download, 1Mbps upload over 5500 meters. The rate for upstream and downstream transmission rates. The stance 6700 meters via copper telephone cables aximum 2.3Mbps download, 2.3Mbps upload. The speeds than standard ADSL aximum 52Mbps download, 16 Mbps upload up to 1200 ters. The provided by service provider. In Packet Transmission Single source send to single destination Single source send to all the destinations. One workstations retransmits frames until destination workstation receives. Terminates transmission on collision detection. Used by Ethernet. Upon detecting a busy transmission, pauses and then re-transmits delayed transmission at random interval to minimise two nodes re-sending at same time.	Firewall a Sec (Demilitarized zone) Bastion Host - Dua Screened Subnet - Po Virus Worms Logic Bomb Trojan Backdoor Salami, salami sl Data diddling Sniffing Session Hijack DDoS (Distributed Describe)	Intrusion detection and prevention. and Perimeter ecurity cure network between ernal internet facing and ernal networks. al-Homed - Three-Legged - Proxy Server - PBX - Honey ot - IDS/IPS Nalicious software Self propagating virtime or condition to Code and/or execut malicious Unauthorized code A series of small at scale attack and Unauthorized monit wing Monitor and capture credentials Denial of Overloading a server esulting in failure of Combination of a December 1.	(HDLC) Domain name system (DNS) T1 T3 ATM ISDN Reserved BRI B-chan BRI D-chan PRI B & D cha PRI B & D cha Ictwork Atta e, code and executa iruses locked virus utables that act as letter execution entry ttacks and network ata before process itoring of transmitt re of authentication for service	Use DTE/DCE communications. Extended protocol for SDLC. Map domain names /host names to IP Address and vice versa. Leased Lines 1.544Mbps via telephone line 45Mbps via telephone line 155Mbps 64 or 128 Kbps REPLACED BY xDSL and 1024-49151 anel 64 Kbps annels 64 Kbps annels 64 Kbps acks ables Legitimate software, but are not legitimate and are k intrusions that culminate in a cumulative large sing ted data an sessions with the purpose of finding and hijacking or data packets well beyond its processing capacity	Wireless person IEEE 802.15 IEEE 802.3 IEEE 802.20 Standard 802.11a 802.11b 802.11g 802.11n 802.11ac • 802.11 use CSMA/CA protocol (* 802.11 b uses only DSSS) Wire Ad-hoc Mode Infrastructure Mode VEP (Wired Equivalent Privacy) WPA (Wi-Fi Protected Access) WPA2 WPA2-Enterprise Mode TKIP (Temporal Key Integrity Use	th. ensitive. rual circuits therefore less expensive. ireless Networking nal area network (WPAN) standards Bluetooth Ethernet Wi-Fi LTE Wi-Fi Speed Frequency (GHz) 54 Mbps 2.4 11 Mbps 5 54 Mbps 2.4 200+ Mbps 2.4/5 1Gbps 5 I as DSSS or FHSS eless Security Protocols rectly connects peer-to-peer mode clients without a entral access point. ients connect centrally via access point. ients connect centrally via access point. ients Temporal Key Integrity Protocol (TKIP) for data acceptation.	
Asymmetric Digital Subscriber Line (ADSL) Rate Adaptive DSL (RADSL) Symmetric Digital Subscriber Line (SDSL) Very-high-bit-rate DSL (VDSL) High-bit-rate DSL (HDSL) Committed Information Rate (CIR) Unicast Multicast Broadcast Carrier-sense Multiple Access (CSMA) CSMA with Collision Detection (CSMA/CD) CSMA with Collision Avoidance (CSMA/CA)	Digital Subscriber Lines (DSL) wilload speed higher than upload eximum 5500 meters distance via telephone lines. Eximum download 8Mbps, upload 800Kbps. Iload speed adjust based on quality of the transmission line eximum 7Mbps download, 1Mbps upload over 5500 meters. Imperate for upstream and downstream transmission rates. In stance 6700 meters via copper telephone cables eximum 2.3Mbps download, 2.3Mbps upload. It is greatly speeds than standard ADSL eximum 52Mbps download, 16 Mbps upload up to 1200 errs. In Packet Transmission Single source send to single destination Single source send to multiple destinations. One workstations retransmits frames until destination workstation receives. Terminates transmission on collision detection. Used by Ethernet. Upon detecting a busy transmission, pauses and then re-transmits delayed transmission at random interval to minimise two nodes re-sending at same time. Sender sends only if polling system is free for the destination.	Possion Hijack DMZ (Demilitarized zone) Bastion Host - Dua Screened Subnet - Po Virus Worms Logic Bomb Trojan Backdoor Salami, salami si Data diddling Sniffing Session Hijack	Intrusion detection and prevention. and Perimeter ecurity cure network between ernal internet facing and ernal networks. al-Homed - Three-Legged - Proxy Server - PBX - Honey ot - IDS/IPS Nalicious software Self propagating vir time or condition to Code and/or execut malicious Unauthorized code A series of small at scale attack and Unauthorized monit wing Monitor and capture credentials Denial of Overloading a serve resulting in failure of Service Combination of a Deservice	(HDLC) Domain name system (DNS) T1 T3 ATM ISDN Reserved BRI B-chan BRI D-chan PRI B & D cha PRI B & D cha Ictwork Atta e, code and executa iruses locked virus utables that act as let execution entry ttacks and network ata before process itoring of transmitt re of authentication rer with requests for of service DDoS attack and TO	Use DTE/DCE communications. Extended protocol for SDLC. Map domain names /host names to IP Address and vice versa. Leased Lines 1.544Mbps via telephone line 45Mbps via telephone line 155Mbps 64 or 128 Kbps REPLACED BY xDSL d 1024-49151 nnel 64 Kbps nnel 16 Kbps annels 64 Kbps CKS ables Legitimate software, but are not legitimate and are k intrusions that culminate in a cumulative large sing ted data n sessions with the purpose of finding and hijacking or data packets well beyond its processing capacity CP 3-way handshake exploit that results in denial of	Wireless person IEEE 802.15 IEEE 802.3 IEEE 802.11 IEEE 802.20 Standard 802.11a 802.11b 802.11g 802.11n 802.11n 802.11n 802.11ac • 802.11 use CSMA/CA protocol • 802.11 b uses only DSSS Wire Ad-hoc Mode Infrastructure Mode Uire Cer Infrastructure Mode VEP (Wired Equivalent Privacy) WPA (Wi-Fi Protected Access) WPA2 WPA2-Enterprise Mode TKIP (Temporal Key Integrity Protocol) EAP (Extensible Util	th. ensitive. tual circuits therefore less expensive. Ireless Networking nal area network (WPAN) standards Bluetooth Ethernet Wi-Fi LTE Wi-Fi Speed Frequency (GHz) 54 Mbps 2.4 11 Mbps 5 54 Mbps 2.4 200+ Mbps 2.4/5 1Gbps 5 I as DSSS or FHSS eless Security Protocols rectly connects peer-to-peer mode clients without a entral access point. itents connect centrally via access point. onfidentiality, uses RC4 for encryption. ses Temporal Key Integrity Protocol (TKIP) for data acceyption. ses AES, key management. ses RADIUS ses RC4 stream cipher. illizes PPP and wireless authentication. Compatible with	
Asymmetric Digital Subscriber Line (ADSL) Rate Adaptive DSL (RADSL) Symmetric Digital Subscriber Line (SDSL) Very-high-bit-rate DSL (VDSL) High-bit-rate DSL (HDSL) Committed Information Rate (CIR) Unicast Multicast Broadcast Carrier-sense Multiple Access (CSMA) CSMA with Collision Detection (CSMA/CD) CSMA with Collision Avoidance (CSMA/CA) Polling Token-passing	Digital Subscriber Lines (DSL) whoload speed higher than upload aximum 5500 meters distance via telephone lines. aximum download 8Mbps, upload 800Kbps. load speed adjust based on quality of the transmission line aximum 7Mbps download, 1Mbps upload over 5500 meters. The rate for upstream and downstream transmission rates. The rate for upstream and downstream transmission rates. The rate of 23Mbps download, 2.3Mbps upload. The rate of 23Mbps download, 2.3Mbps upload. The rate of 24Mbps download, 16 Mbps upload up to 1200 the rate of 24Mbps download, 16 Mbps upload up to 1200 the rate of 24Mbps download, 16 Mbps upload up to 1200 the rate of 24Mbps download, 16 Mbps upload up to 1200 the rate of 24Mbps download, 16 Mbps upload up to 1200 the rate of 24Mbps download, 16 Mbps upload up to 1200 the rate of 24Mbps download, 16 Mbps upload up to 1200 the rate of 24Mbps download, 16 Mbps upload up to 1200 the rate of 24Mbps download, 16 Mbps upload up to 1200 the rate of 24Mbps download, 16 Mbps upload up to 1200 the rate of 24Mbps download, 16 Mbps upload up to 1200 the rate of 24Mbps download, 16 Mbps upload up to 1200 the rate of 24Mbps download, 16 Mbps upload up to 1200 the rate of 24Mbps upload up to 1200 the rate	Firewall a Sec (Demilitarized zone) Bastion Host - Dua Screened Subnet - Po Virus Worms Logic Bomb Trojan Backdoor Salami, salami si Data diddling Sniffing Session Hijack DDoS (Distributed E Service) SYN Flood Smurf	Intrusion detection and prevention. and Perimeter ecurity cure network between ernal internet facing and ernal networks. al-Homed - Three-Legged - Proxy Server - PBX - Honey ot - IDS/IPS Nalicious software Self propagating vir to Time or condition low Code and/or execut malicious Unauthorized code A series of small at scale attack and Unauthorized monit with the credentials Denial of Overloading a server resulting in failure of Service Particular kind of Derotocol (ICMP) particular kind	(HDLC) Domain name system (DNS) T1 T3 ATM ISDN Reserved BRI B-chan BRI D-chan PRI B & D chan PRI B & D chan PRI B & D chan e, code and executar iruses locked virus utables that act as let execution entry ttacks and network ata before process itoring of transmitt re of authentication for with requests for of service DDoS attack using I ackets	Use DTE/DCE communications. Extended protocol for SDLC. Map domain names /host names to IP Address and vice versa. Leased Lines 1.544Mbps via telephone line 45Mbps via telephone line 155Mbps 64 or 128 Kbps REPLACED BY xDSL and 1024-49151 anel 64 Kbps annels 64 Kbps annels 64 Kbps acks ables Legitimate software, but are not legitimate and are k intrusions that culminate in a cumulative large sing ted data an sessions with the purpose of finding and hijacking or data packets well beyond its processing capacity	Wireless person IEEE 802.15 IEEE 802.3 IEEE 802.11 IEEE 802.20 Standard 802.11a 802.11b 802.11g 802.11n 802.11ac • 802.11 use CSMA/CA protocol at 802.11 buses only DSSS Wire Ad-hoc Mode Infrastructure Mode VEP (Wired Equivalent Privacy) WPA (Wi-Fi Protected Access) WPA2 WPA2-Enterprise Mode TKIP (Temporal Key Integrity Protocol) EAP (Extensible Authentication Protocol) DEAP (Protected Extensible Encoted Contents of the Cont	th. ensitive. rual circuits therefore less expensive. Ireless Networking nal area network (WPAN) standards Bluetooth Ethernet Wi-Fi LTE Wi-Fi Speed Frequency (GHz) 54 Mbps 2.4 11 Mbps 5 54 Mbps 2.4/5 1Gbps 5 I as DSSS or FHSS eless Security Protocols rectly connects peer-to-peer mode clients without a entral access point. ieints connect centrally via access point. ieints connect centrally via access point. iess Temporal Key Integrity Protocol (TKIP) for data acceptable. Isses RADIUS Isses RC4 stream cipher. Ilizes PPP and wireless authentication. Compatible with ther encryption technologies. Incapsulates EAP within an encrypted and authenticated	
Asymmetric Digital Subscriber Line (ADSL) Rate Adaptive DSL (RADSL) Symmetric Digital Subscriber Line (SDSL) Very-high-bit-rate DSL (VDSL) High-bit-rate DSL (HDSL) Committed Information Rate (CIR) Unicast Multicast Broadcast Carrier-sense Multiple Access (CSMA) CSMA with Collision Detection (CSMA/CD) CSMA with Collision Avoidance (CSMA/CA) Polling Token-passing Broadcast Domain Collision Domain	Digital Subscriber Lines (DSL) winload speed higher than upload aximum 5500 meters distance via telephone lines. aximum download 8Mbps, upload 800Kbps. lload speed adjust based on quality of the transmission line aximum 7Mbps download, 1Mbps upload over 5500 meters. me rate for upstream and downstream transmission rates. stance 6700 meters via copper telephone cables aximum 2.3Mbps download, 2.3Mbps upload. gher speeds than standard ADSL aximum 52Mbps download, 16 Mbps upload up to 1200 ers speed for two copper cables for 3650 meters imum guaranteed bandwidth provided by service provider. N Packet Transmission Single source send to single destination Single source send to multiple destinations. One workstations retransmits frames until destination workstation receives. Terminates transmission on collision detection. Used by Ethernet. Upon detecting a busy transmission, pauses and then re-transmits delayed transmission at random interval to minimise two nodes re-sending at same time. Sender sends only if polling system is free for the destination. Sender can send only when token received indicating free to send. Set of devices which receive broadcasts. Set of devices which receive broadcasts.	Firewall a Sec (Demilitarized zone) Bastion Host - Dua Screened Subnet - Po Virus Worms Logic Bomb Trojan Backdoor Salami, salami sl Data diddling Sniffing Session Hijack DDoS (Distributed D Service) SYN Flood	Intrusion detection and prevention. and Perimeter ecurity cure network between ernal internet facing and ernal networks. al-Homed - Three-Legged - Proxy Server - PBX - Honey ot - IDS/IPS Nalicious software Self propagating vir Code and/or execut malicious Unauthorized code A series of small at scale attack and Unauthorized monit wind in the code and capture credentials Denial of Overloading a server resulting in failure of Combination of a Derivative of Combination of Combi	(HDLC) Domain name system (DNS) T1 T3 ATM ISDN Reserved BRI B-chan BRI D-chan PRI B & D cha PRI B & D cha Ictwork Atta e, code and executa iruses locked virus utables that act as let execution entry ttacks and network ata before process itoring of transmitt re of authentication rer with requests for of service DDoS attack and TC DDOS attack using I ackets stead of TCP	Use DTE/DCE communications. Extended protocol for SDLC. Map domain names /host names to IP Address and vice versa. Leased Lines 1.544Mbps via telephone line 45Mbps via telephone line 155Mbps 64 or 128 Kbps REPLACED BY xDSL d 1024-49151 nnel 64 Kbps nnel 16 Kbps annels 64 Kbps CKS ables Legitimate software, but are not legitimate and are k intrusions that culminate in a cumulative large sing ted data n sessions with the purpose of finding and hijacking or data packets well beyond its processing capacity CP 3-way handshake exploit that results in denial of	Wireless person IEEE 802.15 IEEE 802.3 IEEE 802.20 Standard 802.11a 802.11b 802.11g 802.11n 802.11a 802.11a 802.11b 802.11b 802.11b 802.11b 802.11b 802.11b 802.11c • 802.11 use CSMA/CA protocol and a second seco	th. ensitive. tual circuits therefore less expensive. Ireless Networking nal area network (WPAN) standards Bluetooth Ethernet Wi-Fi LTE Wi-Fi Speed Frequency (GHz) 54 Mbps 2.4 11 Mbps 5 54 Mbps 2.4 200+ Mbps 2.4/5 1Gbps 5 I as DSSS or FHSS eless Security Protocols rectly connects peer-to-peer mode clients without a entral access point. ients connect centrally via access point. onfidentiality, uses RC4 for encryption. ses Temporal Key Integrity Protocol (TKIP) for data incryption. ses AES, key management. ses RADIUS ses RC4 stream cipher. illizes PPP and wireless authentication. Compatible with ther encryption technologies.	
Asymmetric Digital Subscriber Line (ADSL) • Ma • M	Digital Subscriber Lines (DSL) winload speed higher than upload aximum 5500 meters distance via telephone lines. aximum download 8Mbps, upload 800Kbps. lload speed adjust based on quality of the transmission line aximum 7Mbps download, 1Mbps upload over 5500 meters. me rate for upstream and downstream transmission rates. stance 6700 meters via copper telephone cables aximum 2.3Mbps download, 2.3Mbps upload. gher speeds than standard ADSL aximum 52Mbps download, 16 Mbps upload up to 1200 ers speed for two copper cables for 3650 meters imum guaranteed bandwidth provided by service provider. N Packet Transmission Single source send to single destination Single source send to all the destinations. One workstations retransmits frames until destination workstation receives. Terminates transmission on collision detection. Used by Ethernet. Upon detecting a busy transmission, pauses and then re-transmits delayed transmission at random interval to minimise two nodes re-sending at same time. Sender sends only if polling system is free for the destination. Sender can send only when token received indicating free to send. Set of devices which receive broadcasts.	Firewall a Sec (Demilitarized zone) Bastion Host - Dua Screened Subnet - Po Virus Worms Logic Bomb Trojan Backdoor Salami, salami si Data diddling Sniffing Session Hijack DDoS (Distributed Deservice) SYN Flood Smurf Fraggle LOKI	Intrusion detection and prevention. and Perimeter ecurity cure network between ernal internet facing and ernal networks. al-Homed - Three-Legged - Proxy Server - PBX - Honey ot - IDS/IPS Nalicious software Self propagating vir to Time or condition to Code and/or execut malicious Unauthorized code A series of small at scale attack and Unauthorized monitor and capture credentials Denial of Overloading a server resulting in failure of Combination of a Deservice Particular kind of Deservice	(HDLC) Domain name system (DNS) T1 T3 ATM ISDN Reserved BRI B-chan BRI D-chan PRI B & D cha PRI B & D cha Icked virus Itacks and network ata before process itoring of transmitt re of authentication re with requests for of service DDoS attack and TC DDoS attack and TC DDoS attack using Itackets stead of TCP ICMP tunnelling process ack that exploits a	Use DTE/DCE communications. Extended protocol for SDLC. Map domain names /host names to IP Address and vice versa. Leased Lines 1.544Mbps via telephone line 45Mbps via telephone line 155Mbps 64 or 128 Kbps REPLACED BY xDSL d 1024-49151 nnel 64 Kbps nnel 16 Kbps annels 64 Kbps acks ables Legitimate software, but are not legitimate and are k intrusions that culminate in a cumulative large sing ted data an sessions with the purpose of finding and hijacking or data packets well beyond its processing capacity CP 3-way handshake exploit that results in denial of large numbers of Internet Control Message rogram to establish a covert channel on the network bug in TCP/IP fragmentation reassembly by	Wireless person IEEE 802.15 IEEE 802.3 IEEE 802.11 IEEE 802.20 Standard 802.11a 802.11b 802.11g 802.11n 802.11ac • 802.11 use CSMA/CA protocol 8• 802.11 b uses only DSSS Wire Ad-hoc Mode Infrastructure Mode VEP (Wired Equivalent Privacy) WPA (Wi-Fi Protected Access) WPA2 WPA2 WPA2-Enterprise Mode TKIP (Temporal Key Integrity Protocol) EAP (Extensible Authentication Protocol) PEAP (Protected Extensible Authentication Protocol) Port Based Authentication Wire	th. ensitive. rual circuits therefore less expensive. Freless Networking nal area network (WPAN) standards Bluetooth Ethernet Wi-Fi LTE Wi-Fi Speed Frequency (GHz) 54 Mbps 2.4 11 Mbps 5 54 Mbps 2.4/5 1Gbps 5 I as DSSS or FHSS eless Security Protocols rectly connects peer-to-peer mode clients without a entral access point. ieints connect centrally via access point. ieints connect centrally via access point. ieints connect centrally via access point. iess AES, key management. iess RADIUS ies RADIUS ies RC4 stream cipher. iilizes PPP and wireless authentication. Compatible with the encryption technologies. icapsulates EAP within an encrypted and authenticated in the encryption technologies. Stunnel. Incapsulates EAP in switching environment recless Spread Spectrum	
Asymmetric Digital Subscriber Line (ADSL) Rate Adaptive DSL (RADSL) Symmetric Digital Subscriber Line (SDSL) Very-high-bit-rate DSL (VDSL) High-bit-rate DSL (HDSL) Committed Information Rate (CIR) Unicast Multicast Broadcast Carrier-sense Multiple Access (CSMA) CSMA with Collision Detection (CSMA/CD) CSMA with Collision Avoidance (CSMA/CA) Polling Token-passing Broadcast Domain Collision Domain Layer 2 Switch	Digital Subscriber Lines (DSL) wilload speed higher than upload aximum 5500 meters distance via telephone lines. aximum download 8Mbps, upload 800Kbps. load speed adjust based on quality of the transmission line aximum 7Mbps download, 1Mbps upload over 5500 meters. me rate for upstream and downstream transmission rates. stance 6700 meters via copper telephone cables aximum 2.3Mbps download, 2.3Mbps upload. gher speeds than standard ADSL aximum 52Mbps download, 16 Mbps upload up to 1200 ers. Sepeed for two copper cables for 3650 meters are simum guaranteed bandwidth provided by service provider. N Packet Transmission Single source send to single destination Single source send to all the destinations. One workstations retransmits frames until destination workstation receives. Terminates transmission on collision detection. Used by Ethernet. Upon detecting a busy transmission, pauses and then re-transmits delayed transmission at random interval to minimise two nodes re-sending at same time. Sender sends only if polling system is free for the destination. Sender can send only when token received indicating free to send. Set of devices which receive broadcasts. Set of devices which can create collisions during simultaneous transfer of data. Creates VLANs Interconnects VLANs	Firewall a Sec (Demilitarized zone) Bastion Host - Dua Screened Subnet - Po Virus Worms Logic Bomb Trojan Backdoor Salami, salami sl Data diddling Sniffing Session Hijack DDoS (Distributed D Service) SYN Flood Smurf Fraggle	Intrusion detection and prevention. and Perimeter ecurity Cure network between ernal internet facing and ernal networks. al-Homed - Three-Legged - Proxy Server - PBX - Honey ot - IDS/IPS Note that the properties of small at scale and/or execut malicious Unauthorized code A series of small at scale attack and Unauthorized monitor and capture credentials Denial of Overloading a server resulting in failure of the combination of a Diservice Particular kind of Diservice Protocol (ICMP) particular kind of Dise	(HDLC) Domain name system (DNS) T1 T3 ATM ISDN Reserved BRI B-chan BRI D-chan PRI B & D cha PRI B & D cha Ictwork Atta e, code and executa iruses locked virus utables that act as let execution entry ittacks and network ata before process itoring of transmitt re of authentication for with requests for of service DDOS attack and TC DDOS attack and TC DDOS attack using I ackets stead of TCP ICMP tunnelling process and packets to exhause	Use DTE/DCE communications. Extended protocol for SDLC. Map domain names /host names to IP Address and vice versa. Leased Lines 1.544Mbps via telephone line 45Mbps via telephone line 155Mbps 64 or 128 Kbps REPLACED BY xDSL d 1024-49151 nnel 64 Kbps nnel 16 Kbps annels 64 Kbps acks ables Legitimate software, but are not legitimate and are k intrusions that culminate in a cumulative large sing ted data an sessions with the purpose of finding and hijacking or data packets well beyond its processing capacity CP 3-way handshake exploit that results in denial of large numbers of Internet Control Message rogram to establish a covert channel on the network bug in TCP/IP fragmentation reassembly by	Wireless person IEEE 802.15 IEEE 802.3 IEEE 802.11 IEEE 802.20 Standard 802.11a 802.11b 802.11g 802.11n 802.11a 802.11a **802.11b **80	th. ensitive. rual circuits therefore less expensive. Freless Networking nal area network (WPAN) standards Bluetooth Ethernet Wi-Fi LTE Wi-Fi Speed Frequency (GHz) 54 Mbps 2.4 11 Mbps 5 54 Mbps 2.4 200+ Mbps 2.4/5 16bps 5 I as DSSS or FHSS eless Security Protocols rectly connects peer-to-peer mode clients without a entral access point. Find the connect centrally via access point. For fidentiality, uses RC4 for encryption. Find Ses RADIUS Find	
Asymmetric Digital Subscriber Line (ADSL) Rate Adaptive DSL (RADSL) Symmetric Digital Subscriber Line (SDSL) Very-high-bit-rate DSL (VDSL) High-bit-rate DSL (HDSL) Committed Information Rate (CIR) Unicast Multicast Broadcast Carrier-sense Multiple Access (CSMA) CSMA with Collision Detection (CSMA/CD) CSMA with Collision Avoidance (CSMA/CA) Polling Token-passing Broadcast Domain Collision Domain Layer 2 Switch Layer 3 Switch	• Expensive to setup Digital Subscriber Lines (DSL) whoload speed higher than upload aximum 5500 meters distance via telephone lines. aximum download 8Mbps, upload 800Kbps. load speed adjust based on quality of the transmission line aximum 7Mbps download, 1Mbps upload over 5500 meters. In me rate for upstream and downstream transmission rates. Stance 6700 meters via copper telephone cables aximum 2.3Mbps download, 2.3Mbps upload. gher speeds than standard ADSL aximum 52Mbps download, 16 Mbps upload up to 1200 ers speed for two copper cables for 3650 meters imum guaranteed bandwidth provided by service provider. N Packet Transmission Single source send to single destination Single source send to multiple destinations. One workstations retransmits frames until destination workstation receives. Terminates transmission on collision detection. Used by Ethernet. Upon detecting a busy transmission, pauses and then re-transmits delayed transmission at random interval to minimise two nodes re-sending at same time. Sender sends only if polling system is free for the destination. Sender can send only when token received indicating free to send. Set of devices which receive broadcasts. Set of devices which can create collisions during simultaneous transfer of data. Creates VLANs Interconnects VLANs Interconnects VLANs	Firewall a Sec (Demilitarized zone) Bastion Host - Dua Screened Subnet - Po Virus Worms Logic Bomb Trojan Backdoor Salami, salami si Data diddling Sniffing Session Hijack DDoS (Distributed Deservice) SYN Flood Smurf Fraggle LOKI Teardrop	Intrusion detection and prevention. and Perimeter ecurity cure network between ernal internet facing and ernal networks. al-Homed - Three-Legged - Proxy Server - PBX - Honey of - IDS/IPS Note that the propagating viries to the condition look of the condition l	(HDLC) Domain name system (DNS) T1 T3 ATM ISDN Reserved BRI B-chan BRI D-chan PRI B & D cha PRI B & D cha Ictwork Atta e, code and executa iruses locked virus utables that act as let execution entry ttacks and network ata before process itoring of transmitt re of authentication rer with requests for of service DDOS attack and TO DOS attack using I ackets stead of TCP ICMP tunnelling process and packets to exhautormant or previous	Use DTE/DCE communications. Extended protocol for SDLC. Map domain names /host names to IP Address and vice versa. Leased Lines 1.544Mbps via telephone line 45Mbps via telephone line 155Mbps 64 or 128 Kbps REPLACED BY xDSL dd 1024-49151 nnel 64 Kbps nnel 16 Kbps annels 64 Kbps acks ables legitimate software, but are not legitimate and are k intrusions that culminate in a cumulative large sing ted data in sessions with the purpose of finding and hijacking or data packets well beyond its processing capacity CP 3-way handshake exploit that results in denial of large numbers of Internet Control Message rogram to establish a covert channel on the network bug in TCP/IP fragmentation reassembly by ust channels	Wireless person IEEE 802.15 IEEE 802.3 IEEE 802.11 IEEE 802.20 Standard 802.11a 802.11b 802.11g 802.11n 802.11ac • 802.11 use CSMA/CA protocol at 802.11 buses only DSSS Wireless Ad-hoc Mode Infrastructure Mode VEP (Wired Equivalent Privacy) WPA (Wi-Fi Protected Access) WPA2 WPA2-Enterprise Mode TKIP (Temporal Key Integrity Protocol) EAP (Extensible Authentication Protocol) TLS Port Based Authentication Port Based Authentication SSS (Direct Sequence Spread Spectrum) Wireless Wi	th. ensitive. rual circuits therefore less expensive. reless Networking nal area network (WPAN) standards Bluetooth Ethernet Wi-Fi LTE Wi-Fi Speed Frequency (GHz) 54 Mbps 2.4 11 Mbps 5 54 Mbps 2.4 200+ Mbps 2.4/5 16bps 5 I as DSSS or FHSS rectly connects peer-to-peer mode clients without a entral access point. ieints connect centrally via access point. ieints connect centrally via access point. ieints connect centrally via access point. ieses Temporal Key Integrity Protocol (TKIP) for data access RADIUS sees RADIUS sees RC4 stream cipher. iilizes PPP and wireless authentication. Compatible with her encryption technologies. icapsulates EAP within an encrypted and authenticated activation. Streams and spread access process access spread Spectrum sees all available frequencies, but only a single frequency	
Asymmetric Digital Subscriber Line (ADSL) • Ma • M	Digital Subscriber Lines (DSL) wilload speed higher than upload aximum 5500 meters distance via telephone lines. aximum download 8Mbps, upload 800Kbps. load speed adjust based on quality of the transmission line aximum 7Mbps download, 1Mbps upload over 5500 meters. me rate for upstream and downstream transmission rates. stance 6700 meters via copper telephone cables aximum 2.3Mbps download, 2.3Mbps upload. gher speeds than standard ADSL aximum 52Mbps download, 16 Mbps upload up to 1200 ers. Sepeed for two copper cables for 3650 meters are simum guaranteed bandwidth provided by service provider. N Packet Transmission Single source send to single destination Single source send to all the destinations. One workstations retransmits frames until destination workstation receives. Terminates transmission on collision detection. Used by Ethernet. Upon detecting a busy transmission, pauses and then re-transmits delayed transmission at random interval to minimise two nodes re-sending at same time. Sender sends only if polling system is free for the destination. Sender can send only when token received indicating free to send. Set of devices which receive broadcasts. Set of devices which can create collisions during simultaneous transfer of data. Creates VLANs Interconnects VLANs	Firewall a Sec (Demilitarized zone) Bastion Host - Dua Screened Subnet - Po Virus Worms Logic Bomb Trojan Backdoor Salami, salami sl Data diddling Sniffing Session Hijack DDoS (Distributed Deservice) SYN Flood Smurf Fraggle LOKI Teardrop Zero-day	Intrusion detection and prevention. and Perimeter recurity cure network between remal internet facing and remal networks. al-Homed - Three-Legged - Proxy Server - PBX - Honey of - IDS/IPS Malicious software Self propagating vir Time or condition to Code and/or execut malicious Unauthorized code A series of small at scale attack regulating in failure of Combination of a Denial of Overloading a server resulting in failure of Combination of a Denial of Overloading a server resulting in failure of Combination of a Denial of Overloading a server resulting in failure of Combination of a Denial of Overloading a server resulting in failure of Combination of a Denial of Overloading a server resulting in failure of Combination of a Denial of Overloading a server resulting in failure of Combination of a Denial of Overloading a server resulting in failure of Combination of a Denial of Overloading failure of Combination of a Denial of Overloading a server resulting in failure of Combination of a Denial of Overloading a server resulting in failure of Combination of a Denial of Overloading a server resulting in failure of Combination of a Denial of Overloading a server resulting in failure of Combination of a Denial of Overloading a server resulting in failure of Combination of a Denial of Overloading a server resulting in failure of Combination of a Denial of Overloading a server resulting in failure of Combination of a Denial of Overloading a server resulting in failure of Combination of a Denial of Overloading a server resulting in failure of Combination of a Denial of Overloading a server resulting in failure of Combination of a Denial of Overloading a server resulting in failure of Combination of a Denial of Overloading a server resulting in failure of Combination of a Denial of Overloading a server resulting in failure of Combination of a Denial of Overloading a server resulting in failure of Combination of a Denial of Overloading a server resulting in failure of Combination of a Denial of Overloading a server resu	(HDLC) Domain name system (DNS) T1 T3 ATM ISDN Reserved BRI B-chan BRI D-chan PRI B & D cha PRI B & D cha Icked virus Itacks and network ata before process itoring of transmitt re of authentication re with requests for of service DDOS attack and TC	Use DTE/DCE communications. Extended protocol for SDLC. Map domain names /host names to IP Address and vice versa. Leased Lines 1.544Mbps via telephone line 45Mbps is telephone line 155Mbps 64 or 128 Kbps REPLACED BY xDSL id 1024-49151 innel 64 Kbps innel 16 Kbps annels 64 Kbps acks ables Clegitimate software, but are not legitimate and are k intrusions that culminate in a cumulative large sing ted data in sessions with the purpose of finding and hijacking or data packets well beyond its processing capacity CP 3-way handshake exploit that results in denial of large numbers of Internet Control Message rogram to establish a covert channel on the network bug in TCP/IP fragmentation reassembly by ust channels sly unknown software bug	Wireless person IEEE 802.15 IEEE 802.3 IEEE 802.11 IEEE 802.20 Standard 802.11a 802.11b 802.11g 802.11n 802.11ac • 802.11 use CSMA/CA protocol • 802.11 buses only DSSS Wire Ad-hoc Mode Infrastructure Mode VEP (Wired Equivalent Privacy) WPA (Wi-Fi Protected Access) WPA2 WPA2-Enterprise Mode TKIP (Temporal Key Integrity Protocol) EAP (Extensible Authentication Protocol) TLS Port Based Authentication Port Based Authentication SSS (Direct Sequence Spread Spectrum) OFDM (Orthogonal Frequency-Division Ort	th. ensitive. rual circuits therefore less expensive. Freless Networking nal area network (WPAN) standards Bluetooth Ethernet Wi-Fi LTE Wi-Fi Speed Frequency (GHz) 54 Mbps 2.4 11 Mbps 5 54 Mbps 2.4 200+ Mbps 2.4/5 16bps 5 I as DSSS or FHSS eless Security Protocols rectly connects peer-to-peer mode clients without a entral access point. Fients connect centrally via access point. Fients connect centrally via access point. Fients connect centrally via companient. Fients experience of the protocol (TKIP) for data corryption. Fients experience of the protocol (TKIP) for data corryption. Fients experience of the protocol (TKIP) for data corryption. Fients experience of the protocol (TKIP) for data corryption. Fients experience of the protocol (TKIP) for data corryption. Fients experience of the protocol (TKIP) for data corryption. Fients experience of the protocol (TKIP) for data corryption. Fients experience of the protocol of the pro	
Types of E Asymmetric Digital Subscriber Line (ADSL) Rate Adaptive DSL (RADSL) Symmetric Digital Subscriber Line (SDSL) Very-high-bit-rate DSL (VDSL) Committed Information Rate (CIR) Unicast Multicast Broadcast Carrier-sense Multiple Access (CSMA) CSMA with Collision Detection (CSMA/CD) CSMA with Collision Avoidance (CSMA/CA) Polling Token-passing Broadcast Domain Collision Domain Layer 2 Switch Layer 3 Switch Twisted Pair Unshielded Twisted Pair (UTP) Less in	Pigital Subscriber Lines (DSL) winload speed higher than upload aximum 5500 meters distance via telephone lines. Aximum download 8Mbps, upload 800Kbps. load speed adjust based on quality of the transmission line aximum 7Mbps download, 1Mbps upload over 5500 meters. Immerate for upstream and downstream transmission rates. Stance 6700 meters via copper telephone cables aximum 2.3Mbps download, 2.3Mbps upload. Igher speeds than standard ADSL aximum 52Mbps download, 16 Mbps upload up to 1200 ers. In Packet Transmission Single source send to single destination Single source send to multiple destinations. One workstations retransmits frames until destination workstation receives. Terminates transmission on collision detection. Used by Ethernet. Upon detecting a busy transmission, pauses and then retransmits delayed transmission at random interval to minimise two nodes re-sending at same time. Sender sends only if polling system is free for the destination. Sender can send only when token received indicating free to send. Set of devices which receive broadcasts. Set of devices which can create collisions during simultaneous transfer of data. Creates VLANs Interconnects VLANs Interconnects VLANs Interconnects Open wires. Used in ETHERNET. Cat5/5e/6. Cat5	Firewall a Sec (Demilitarized zone) Bastion Host - Dua Screened Subnet - Po Virus Worms Logic Bomb Trojan Backdoor Salami, salami si Data diddling Sniffing Session Hijack DDoS (Distributed Deservice) SYN Flood Smurf Fraggle LOKI Teardrop Zero-day Land Attack	Intrusion detection and prevention. and Perimeter ecurity cure network between ernal internet facing and ernal networks. al-Homed - Three-Legged - Proxy Server - PBX - Honey of - IDS/IPS Nalicious software Self propagating vir Time or condition to Code and/or execut malicious Unauthorized code A series of small at scale attack of Monitor and capture credentials Denial of Overloading a serve resulting in failure of Combination of a D service Particular kind of D Protocol (ICMP) pase Smurf with UDP insometical sending fragmented Exploitation of a door kan an anonymously sending anonymously sending Information of a door kan anonymously sending Informatio	(HDLC) Domain name system (DNS) T1 T3 ATM ISDN Reserved BRI B-chan BRI D-chan PRI B & D cha PRI B & D cha Icked virus Itables that act as less execution entry Itacks and network ata before process itoring of transmitt re of authentication Icer with requests for of service DDOS attack and TC DDOS attack and TC DDOS attack using Itackets Istead of TCP ICMP tunnelling process and packets to exhaute or a packet that has a pa	Use DTE/DCE communications. Extended protocol for SDLC. Map domain names /host names to IP Address and vice versa. Leased Lines 1.544Mbps via telephone line 45Mbps via telephone line 155Mbps 64 or 128 Kbps REPLACED BY xDSL dd 1024-49151 del Kbps del Kintrusions that culminate in a cumulative large sing ted data n sessions with the purpose of finding and hijacking or data packets well beyond its processing capacity del arge numbers of Internet Control Message rogram to establish a covert channel on the network bug in TCP/IP fragmentation reassembly by ust channels sty unknown software bug the same source and destination IP	Wireless person IEEE 802.15 IEEE 802.3 IEEE 802.20 Standard 802.11a 802.11b 802.11b 802.11b 802.11c 802.11b 802.11c 802.11b 802.11b 802.11c 802.11b 802.11c Vire Ad-hoc Mode Infrastructure Mode VEP (Wired Equivalent Privacy) WPA (Wi-Fi Protected Access) WPA2 WPA2-Enterprise Mode TKIP (Temporal Key Integrity Protocol) EAP (Extensible Authentication Protocol) PEAP (Protected Extensible Authentication Protocol) PEAP (Protected Extensible Authentication Protocol) POrt Based Authentication Wire FHSS (Frequency Hopping Spectrum System) DSSS (Direct Sequence Spread Spectrum) OFDM (Orthogonal Frequency-Division Multiplexing)	th. ensitive. tual circuits therefore less expensive. Ireless Networking nal area network (WPAN) standards Bluetooth Ethernet Wi-Fi LTE Wi-Fi Speed Frequency (GHz) 54 Mbps 2.4 11 Mbps 5 54 Mbps 2.4 200+ Mbps 2.4/5 1Gbps 5 I as DSSS or FHSS eless Security Protocols rectly connects peer-to-peer mode clients without a entral access point. ieints connect centrally via access point. ieints connect c	
Asymmetric Digital Subscriber Line (ADSL) Rate Adaptive DSL (RADSL) Symmetric Digital Subscriber Line (SDSL) Very-high-bit-rate DSL (VDSL) Committed Information Rate (CIR) Unicast Multicast Broadcast Carrier-sense Multiple Access (CSMA) CSMA with Collision Detection (CSMA/CD) CSMA with Collision Avoidance (CSMA/CA) Polling Token-passing Broadcast Domain Collision Domain Layer 2 Switch Layer 3 Switch Twisted Pair Unshielded Twisted Pair (UTP) Shielded Twisted Pair (UTP) Shielded Twisted Pair is to speed	Pigital Subscriber Lines (DSL) winload speed higher than upload aximum 5500 meters distance via telephone lines. Aximum download 8Mbps, upload 800Kbps. Idoad speed adjust based on quality of the transmission line aximum 7Mbps download, 1Mbps upload over 5500 meters. Ime rate for upstream and downstream transmission rates. Stance 6700 meters via copper telephone cables aximum 2.3Mbps download, 2.3Mbps upload. Igher speeds than standard ADSL aximum 52Mbps download, 16 Mbps upload up to 1200 ers. Impered for two copper cables for 3650 meters. Impered for two copper felephone cables at the formation for the destination. Impered for two copper felephone cables at the formation for the destination. Impered for two copper felephone cables at the formation for the	Firewall a Sec (Demilitarized zone) Bastion Host - Dua Screened Subnet - Po Virus Worms Logic Bomb Trojan Backdoor Salami, salami si Data diddling Sniffing Session Hijack DDoS (Distributed Deservice) SYN Flood Smurf Fraggle LOKI Teardrop Zero-day Land Attack Bluejacking, Bluesi DNS Spoofing, I	Intrusion detection and prevention. and Perimeter ecurity cure network between ernal internet facing and ernal networks. al-Homed - Three-Legged - Proxy Server - PBX - Honey of - IDS/IPS Malicious software Self propagating virit of Time or condition to Code and/or execut malicious Unauthorized code A series of small at scale attack of Monitor and capture credentials Denial of Overloading a server resulting in failure of Combination of a Derivice Particular kind of Der	(HDLC) Domain name system (DNS) T1 T3 ATM ISDN Reserved BRI B-chan BRI D-chan PRI B & D cha PRI B & D cha Icked virus Itables that act as less execution entry Ittacks and network ata before process itoring of transmitt re of authentication for with requests for of service DDOS attack and TC	Use DTE/DCE communications. Extended protocol for SDLC. Map domain names /host names to IP Address and vice versa. Leased Lines 1.544Mbps via telephone line 45Mbps via telephone line 155Mbps 64 or 128 Kbps REPLACED BY xDSL dd 1024-49151 nnel 64 Kbps nnel 16 Kbps annels 64 Kbps acks ables legitimate software, but are not legitimate and are k intrusions that culminate in a cumulative large sing ted data n sessions with the purpose of finding and hijacking or data packets well beyond its processing capacity CP 3-way handshake exploit that results in denial of large numbers of Internet Control Message rogram to establish a covert channel on the network bug in TCP/IP fragmentation reassembly by ust channels sity unknown software bug the same source and destination IP ssages or injecting code via bluetooth to	Wireless person IEEE 802.15 IEEE 802.3 IEEE 802.11 IEEE 802.20 Standard 802.11a 802.11b 802.11g 802.11n 802.11ac • 802.11 use CSMA/CA protocol (corrected Access) Wireless only DSSS Wi	th. ensitive. ual circuits therefore less expensive. ireless Networking mal area network (WPAN) standards Bluetooth Ethernet Wi-Fi LTE Wi-Fi Speed Frequency (GHz) 54 Mbps 2.4 11 Mbps 5 54 Mbps 2.4/5 16bps 5 1 as DSSS or FHSS eless Security Protocols rectly connects peer-to-peer mode clients without a entral access point. ients connect centrally via access point. ients connect centrally via access point. ients expendency (TKIP) for data acception. iese AES, key management. iese RADIUS iese RC4 stream cipher. ilizes PPP and wireless authentication. Compatible with the encryption technologies. incapsulates EAP within an encrypted and authenticated as tunnel. io2.1x, use with EAP in switching environment reless Spread Spectrum is all available frequencies, but only a single frequency in be used at a time. ioanallel use of all the available frequencies leads to higher roughput of rate compared to FHSS. ithogonal Frequency-Division Multiplexing III Generation Evolution Filter Firewalls: Examines source/destination address,	
Asymmetric Digital Subscriber Line (ADSL) Rate Adaptive DSL (RADSL) Symmetric Digital Subscriber Line (SDSL) Subscriber Line Subscriber Subscr	Pigital Subscriber Lines (DSL) winload speed higher than upload aximum 5500 meters distance via telephone lines. aximum download 8Mbps, upload 800Kbps. load speed adjust based on quality of the transmission line aximum 7Mbps download, 1Mbps upload over 5500 meters. The rate for upstream and downstream transmission rates. The rate for upstream and downstream transmission rates. The rate of 200 meters via copper telephone cables aximum 2.3Mbps download, 2.3Mbps upload. The respect of the respect	Firewall a Sec (Demilitarized zone) Bastion Host - Dua Screened Subnet - Po Virus Worms Logic Bomb Trojan Backdoor Salami, salami si Data diddling Sniffing Session Hijack DDoS (Distributed Deservice) SYN Flood Smurf Fraggle LOKI Teardrop Zero-day Land Attack Bluejacking, Bluesi DNS Spoofing, It Poisoning Session hijack (Spoofing) A TCP sequence pro-	Intrusion detection and prevention. and Perimeter ecurity Cure network between ernal internet facing and ernal networks. al-Homed - Three-Legged - Proxy Server - PBX - Honey of - IDS/IPS Malicious software Self propagating virit of Time or condition to Code and/or execut malicious Unauthorized code A series of small at scale attack of Monitor and capturated entials Denial of Overloading a serve resulting in failure of Combination of a Derivation of a D	(HDLC) Domain name system (DNS) T1 T3 ATM ISDN Reserved BRI B-chan BRI D-chan PRI B & D cha PRI B & D cha ce, code and executa iruses locked virus utables that act as leterated of transmitted at the process itoring of tr	Des DIE/DCE communications. Extended protocol for SDLC. Map domain names /host names to IP Address and vice versa. Leased Lines 1.544Mbps via telephone line 45Mbps via telephone line 155Mbps 64 or 128 Kbps REPLACED BY xDSL do 1024-49151 do 16 Kbps do 4 Kbps do 5 Kbps do 6 Kbps do 7	Wireless person IEEE 802.15 IEEE 802.3 IEEE 802.11 IEEE 802.20 Standard 802.11a 802.11b 802.11g 802.11n 802.11a 802.11b 802.11c • 802.11 use CSMA/CA protocol and the privacy) Wireless only DSSS Wireless Wir	th. ensitive. ual circuits therefore less expensive. ireless Networking mal area network (WPAN) standards Bluetooth Ethernet Wi-Fi LTE Wi-Fi Speed Frequency (GHz) 54 Mbps 2.4 11 Mbps 5 54 Mbps 2.4/5 16bps 5 1 as DSSS or FHSS eless Security Protocols rectly connects peer-to-peer mode clients without a entral access point. ients connect centrally via access point. ients connect centrally via access point. ients connect centrally via access point. ients connect management. iese AES, key management. iese RADIUS iese RC4 stream cipher. iilizes PPP and wireless authentication. Compatible with her encryption technologies. incapsulates EAP within an encrypted and authenticated actumel. 12.1x, use with EAP in switching environment reless Spread Spectrum is seall available frequencies, but only a single frequency in be used at a time. irrule use of all the available frequencies leads to higher roughput of rate compared to FHSS. Ithogonal Frequency-Division Multiplexing II Generation Evolution	
Types of E Asymmetric Digital Subscriber Line (ADSL) Rate Adaptive DSL (RADSL) Symmetric Digital Subscriber Line (SDSL) Very-high-bit-rate DSL (VDSL) High-bit-rate DSL (HDSL) Committed Information Rate (CIR) Unicast Multicast Broadcast Carrier-sense Multiple Access (CSMA) CSMA with Collision Detection (CSMA/CD) CSMA with Collision Avoidance (CSMA/CA) Polling Token-passing Broadcast Domain Collision Domain Layer 2 Switch Layer 3 Switch Twisted Pair Unshielded Twisted Pair (UTP) Shielded Twisted Pair (STP) Coaxial Cable Thick and 10 Uses I	Pigital Subscriber Lines (DSL) whload speed higher than upload aximum 5500 meters distance via telephone lines. aximum download 8Mbps, upload 800Kbps. load speed adjust based on quality of the transmission line aximum 7Mbps download, 1Mbps upload over 5500 meters. The rate for upstream and downstream transmission rates. Stance 6700 meters via copper telephone cables aximum 2.3Mbps download, 2.3Mbps upload. gher speeds than standard ADSL aximum 52Mbps download, 16 Mbps upload up to 1200 ers. Speed for two copper cables for 3650 meters. Imaginated bandwidth provided by service provider. N Packet Transmission Single source send to single destination Single source send to multiple destinations. One workstations retransmits frames until destination workstation receives. Terminates transmission on collision detection. Used by Ethernet. Upon detecting a busy transmission, pauses and then re-transmits delayed transmission at random interval to minimise two nodes re-sending at same time. Sender sends only if polling system is free for the destination. Sender can send only when token received indicating free to send. Set of devices which can create collisions during simultaneous transfer of data. Creates VLANs Interconnects VLANs LAN / WAN Media of twisted copper wires. Used in ETHERNET. Cat5/5e/6. Cat5 of up to 100Mbps over 100 meters. Cat5e/6 speed 1000Mbps. Immune to Electromagnetic Interference (EMI) art to UTP but includes a protective shield. conduit instead of two copper wires. 10BASE-T, 100BASE-T, 100BASE-T	Firewall a Sec DMZ (Demilitarized zone) Bastion Host - Dua Screened Subnet - Po Virus Worms Logic Bomb Trojan Backdoor Salami, salami sl Data diddling Sniffing Session Hijack DDoS (Distributed Deservice) SYN Flood Smurf Fraggle LOKI Teardrop Zero-day Land Attack Bluejacking, Blues DNS Spoofing, I Poisoning Session hijack (Spoofing)	Intrusion detection and prevention. and Perimeter ecurity cure network between ernal internet facing and ernal networks. al-Homed - Three-Legged - Proxy Server - PBX - Honey of - IDS/IPS Nalicious software Self propagating vir Code and/or execut malicious Unauthorized code A series of small at scale attack In Monitor and capture credentials Denial of Overloading a server resulting in failure of Combination of a Deservice Particular kind of Deservice A type of DDos attaction of a dos kind attaction	(HDLC) Domain name system (DNS) T1 T3 ATM ISDN Reserved BRI B-chan BRI D-chan PRI B & D cha PRI B & D cha ce, code and executa iruses locked virus utables that act as leterated of transmitted at the process itoring of tr	Des DIE/DCE communications. Extended protocol for SDLC. Map domain names /host names to IP Address and vice versa. Leased Lines 1.544Mbps via telephone line 45Mbps via telephone line 155Mbps 64 or 128 Kbps REPLACED BY xDSL do 1024-49151 do 1024-49151 do 16 Kbps do 4 Kbps do 5 Kbps do 6 Kbps d	Wireless person IEEE 802.15 IEEE 802.3 IEEE 802.11 IEEE 802.20 Standard 802.11a 802.11b 802.11g 802.11n 802.11ac *802.11 use CSMA/CA protocol : 802.11 uses only DSSS Wireless Ad-hoc Mode Infrastructure Mode Very (Wired Equivalent Privacy) WPA (Wi-Fi Protected Access) WPA2 WPA2-Enterprise Mode TKIP (Temporal Key Integrity Protocol) EAP (Extensible Authentication Protocol) PEAP (Protected Extensible Authentication Protocol) PEAP (Protected Extensible Authentication Protocol) PEAP (Protected Extensible Authentication Protocol) POrt Based Authentication Port Based Authentication Spectrum System) DSSS (Direct Sequence Spread Spectrum) OFDM (Orthogonal Frequency-Division Multiplexing) Firewall Second Generation Firewalls Second Generation - Application - Applicati	th. ensitive. tual circuits therefore less expensive. ireless Networking mal area network (WPAN) standards Bluetooth Ethernet Wi-Fi LTE Wi-Fi Speed Frequency (GHz) 54 Mbps 2.4 11 Mbps 5 54 Mbps 2.4/ 200+ Mbps 2.4/5 16bps 5 I as DSSS or FHSS eless Security Protocols rectly connects peer-to-peer mode clients without a entral access point. ients connect centrally via access point. onfidentiality, uses RC4 for encryption. ses Temporal Key Integrity Protocol (TKIP) for data coryption. ses AES, key management. ses RADIUS ses RC4 stream cipher. ses RADIUS ses RC4 stream cipher. ses RADIUS ses RC4 stream cipher. ses RADIUS ses RC5 per and wireless authentication. Compatible with ther encryption technologies. ses RC4 stream cipher. ses all available frequencies, but only a single frequency on be used at a time. ses all available frequencies, but only a single frequency on be used at a time. serallel use of all the available frequencies leads to higher roughput of rate compared to FHSS. III Generation Evolution Filter Firewalls: Examines source/destination address, and ports of the incoming packets. And deny or permit	
Types of E Asymmetric Digital Subscriber Line (ADSL) Rate Adaptive DSL (RADSL) Symmetric Digital Subscriber Line (SDSL) Very-high-bit-rate DSL (VDSL) High-bit-rate DSL (HDSL) Committed Information Rate (CIR) Unicast Multicast Broadcast Carrier-sense Multiple Access (CSMA) CSMA with Collision Detection (CSMA/CD) CSMA with Collision Avoidance (CSMA/CA) Polling Token-passing Broadcast Domain Collision Domain Layer 2 Switch Layer 3 Switch Layer 3 Switch Twisted Pair Unshielded Twisted Pair (UTP) Shielded Twisted Pair (STP) Coaxial Cable Fiber Optic Thick and 10 Over a	Digital Subscriber Lines (DSL) winload speed higher than upload aximum 5500 meters distance via telephone lines. aximum 5500 meters distance via telephone lines. aximum 5500 meters distance via telephone lines. aximum download 8Mbps, upload 800Kbps. load speed adjust based on quality of the transmission line aximum 7Mbps download, 1Mbps upload over 5500 meters. me rate for upstream and downstream transmission rates. stance 6700 meters via copper telephone cables aximum 2.3Mbps download, 2.3Mbps upload. gher speeds than standard ADSL aximum 52Mbps download, 16 Mbps upload up to 1200 ers. In Packet Transmission Single source send to single destination Single source send to single destination Source packet send to all the destinations. One workstations retransmits frames until destination workstation receives. Terminates transmission on collision detection. Used by Ethernet. Upon detecting a busy transmission, pauses and then re-transmits delayed transmission at random interval to minimise two nodes re-sending at same time. Sender sends only if polling system is free for the destination. Sender can send only when token received indicating free to send. Set of devices which receive broadcasts. Set of devices which can create collisions during simultaneous transfer of data. Creates VLANs Interconnects VLANs LAN / WAN Media of twisted copper wires. Used in ETHERNET. Cat5/5e/6. Cat5 dup to 100Mbps over 100 meters. Cat5e/6 speed 1000Mbps. immune to Electromagnetic Interference (EMI) art o UTP but includes a protective shield. conduit instead of two copper wires. 10BASE-T, 100BASE-T, 100BASE-T, 100BASE-T. light as the media to transmit signals. Gigabit speed at long	Firewall a Sec (Demilitarized zone) Bastion Host - Dua Screened Subnet - Po Virus Worms Logic Bomb Trojan Backdoor Salami, salami si Data diddling Sniffing Session Hijack DDoS (Distributed Deservice) SYN Flood Smurf Fraggle LOKI Teardrop Zero-day Land Attack Bluejacking, Bluesi DNS Spoofing, Italy Poisoning Session hijack (Spoofing) A TCP squence product of the poisoning Session hijack (Spoofing) A TCP squence product of the poisoning Session hijack (Spoofing) A TCP squence product of the poisoning Session hijack (Spoofing) A TCP squence product of the poisoning Session hijack (Spoofing) A TCP squence product of the poisoning Session hijack (Spoofing) A TCP squence product of the poisoning Session hijack (Spoofing)	Intrusion detection and prevention. and Perimeter ecurity cure network between ternal internet facing and ternal networks. al-Homed - Three-Legged - Proxy Server - PBX - Honey to - IDS/IPS Nalicious software Self propagating virit of Time or condition to Code and/or execut malicious Unauthorized code A series of small at scale attack and Unauthorized monit with the scale attack and Unauthorized monit of the service Particular kind of Derotocol (ICMP) passervice Particular kind of Derotocol (ICMP) pa	(HDLC) Domain name system (DNS) T1 T3 ATM ISDN Reserved BRI B-chan BRI D-chan PRI B & D cha PRI B & D cha Ictwork Atta e, code and executa iruses locked virus utables that act as leterate and network ata before process itoring of transmitt re of authentication for with requests for of service DDOS attack and TO DOS attack using I ackets stead of TCP ICMP tunnelling process and packets to exhautorment or previous g a packet that has and packets to exhautorment or previous and pac	Des DIE/DCE communications. Extended protocol for SDLC. Map domain names /host names to IP Address and vice versa. Leased Lines 1.544Mbps via telephone line 45Mbps via telephone line 155Mbps 64 or 128 Kbps REPLACED BY xDSL do 1024-49151 do 1024-49151 do 16 Kbps do 4 Kbps do 5 Kbps do 6 Kbps d	Wireless person IEEE 802.15 IEEE 802.3 IEEE 802.11 IEEE 802.20 Standard 802.11a 802.11b 802.11g 802.11n 802.11a 802.11b Ad-hoc Mode Cer Infrastructure Mode Clie WEP (Wired Equivalent Privacy) WPA (Wi-Fi Protected Access) WPA2 WPA2-Enterprise Mode Use TKIP (Temporal Key Integrity Protocol) EAP (Extensible Authentication Protocol) PEAP (Protected Extensible Authentication Protocol) PEAP (Protected Extensible Authentication Protocol) PEAP (Protected Extensible Authentication Protocol) POrt Based Authentication Spectrum System) DSSS (Direct Sequence Spread Spectrum) OFDM (Orthogonal Frequency-Division Multiplexing) Firewal First Generation Firewalls - Packet Fi protocol ar according: - Application during pace	th. ensitive. cual circuits therefore less expensive. Ireless Networking Inal area network (WPAN) standards Bluetooth Ethernet Wi-Fi LTE Wi-Fi Speed Frequency (GHz) 54 Mbps 2.4 11 Mbps 5 54 Mbps 2.4/5 16bps 5 I as DSSS or FHSS eless Security Protocols rectly connects peer-to-peer mode clients without a entral access point. ients connect centrally via access point. onfidentiality, uses RC4 for encryption. ses Temporal Key Integrity Protocol (TKIP) for data coryption. ses RADIUS ses RC4 stream cipher. iilizes PPP and wireless authentication. Compatible with the encryption technologies. Incapsulates EAP within an encrypted and authenticated as tunnel. 102.1x, use with EAP in switching environment reless Spread Spectrum ses all available frequencies, but only a single frequency in be used at a time. Ireless Spread Spectrum ses all available frequencies, but only a single frequency in be used at a time. Ireless Spread Spectrum ses all available frequencies, but only a single frequency in be used at a time. Ireless Spread Spectrum ses all available frequencies, but only a single frequency in be used at a time. Ireless Spread Spectrum ses all available frequencies leads to higher roughput of rate compared to FHSS. Ithogonal Frequency-Division Multiplexing II Generation Evolution Filter Firewalls: Examines source/destination address, and for the incoming packets. And deny or permit to ACL. Network layer, stateless. ion Level Firewall / Proxy Server: Masks the source cket transfer. Operating at Application layer, stateful. Inspection Firewall: Faster. State and context of the	
Asymmetric Digital Subscriber Line (ADSL) Rate Adaptive DSL (RADSL) Symmetric Digital Subscriber Line (SDSL) Very-high-bit-rate DSL (VDSL) High-bit-rate DSL (HDSL) Committed Information Rate (CIR) Unicast Multicast Broadcast Carrier-sense Multiple Access (CSMA) CSMA with Collision Detection (CSMA/CD) CSMA with Collision Avoidance (CSMA/CA) Polling Token-passing Broadcast Domain Collision Domain Layer 2 Switch Layer 3 Switch Twisted Pair Unshielded Twisted Pair (UTP) Shielded Twisted Pair (STP) Coaxial Cable Fiber Optic Frame Relay WAN Over a fault service of the control o	Pault tolerance Expensive to setup Digital Subscriber Lines (DSL) winload speed higher than upload aximum 5500 meters distance via telephone lines. aximum download 8Mbps, upload 800Kbps. load speed adjust based on quality of the transmission line aximum 7Mbps download, 1Mbps upload over 5500 meters. me rate for upstream and downstream transmission rates. stance 6700 meters via copper telephone cables aximum 2.3Mbps download, 2.3Mbps upload. gher speeds than standard ADSL aximum 52Mbps download, 16 Mbps upload up to 1200 ers speed for two copper cables for 3650 meters imum guaranteed bandwidth provided by service provider. N Packet Transmission Single source send to single destination Single source send to multiple destinations Source packet send to all the destinations. One workstations retransmits frames until destination workstation receives. Terminates transmission on collision detection. Used by Ethernet. Upon detecting a busy transmission, pauses and then re-transmits delayed transmission at random interval to minimise two nodes re-sending at same time. Sender sends only if polling system is free for the destination. Sender can send only when token received indicating free to send. Set of devices which receive broadcasts. Set of devices which can create collisions during simultaneous transfer of data. Creates VLANs Interconnects VLANs LAN / WAN Media of twisted copper wires. Used in ETHERNET. Cat5/5e/6. Cat5 du to 100Mbps over 100 meters. Cat5e/6 speed 1000Mbps. immune to Electromagnetic Interference (EMI) art to UTP but includes a protective shield. conduit instead of two copper wires. 10BASE-T, 100BASE-T, 1000BASE-T. light as the media to transmit signals. Gigabit speed at long nee. Less errors and signal loss. Immune to EMI. Multimode ingle mode. Single mode for outdoor long distance. a public switched network. High Fault tolerance by relaying segments to working.	Firewall a Sec (Demilitarized zone) Bastion Host - Dua Screened Subnet - Po Virus Worms Logic Bomb Trojan Backdoor Salami, salami si Data diddling Sniffing Session Hijack DDoS (Distributed Deservice) SYN Flood Smurf Fraggle LOKI Teardrop Zero-day Land Attack Bluejacking, Bluess DNS Spoofing, It Poisoning Session hijack (Spoofing) A TCP sequence produced for the protection of the prote	Intrusion detection and prevention. and Perimeter recurity cure network between remainer internet facing and remained and proxy Server - PBX - Honey of - IDS/IPS Malicious software Self propagating virity of the Time or condition to Code and/or execut malicious Unauthorized code A series of small at scale attack and Unauthorized monitor and capture credentials Denial of Overloading a server resulting in failure of Combination of a Deservice Particular kind of Deservice Parti	(HDLC) Domain name system (DNS) T1 T3 ATM ISDN Reserved BRI B-chan BRI D-chan PRI B & D cha PRI B & D cha Ictwork Atta e, code and executa iruses locked virus utables that act as leterate and network ata before process itoring of transmitt re of authentication for with requests for of service DDOS attack and TO DOS attack using I ackets stead of TCP ICMP tunnelling process and packets to exhautorment or previous g a packet that has and packets to exhautorment or previous and pac	Just Dis PIDE communications. Extended protocol for SDLC. Map domain names /host names to IP Address and vice versa. Leased Lines 1.544Mbps via telephone line 45Mbps via telephone line 155Mbps 64 or 128 Kbps REPLACED BY xDSL dd 1024-49151 nnel 64 Kbps nnel 16 Kbps annels 64 Kbps annels 64 Kbps Begittimate software, but are not legitimate and are k intrusions that culminate in a cumulative large sing ted data an sessions with the purpose of finding and hijacking or data packets well beyond its processing capacity CP 3-way handshake exploit that results in denial of large numbers of Internet Control Message rogram to establish a covert channel on the network bug in TCP/IP fragmentation reassembly by ust channels sity unknown software bug the same source and destination IP ssages or injecting code via bluetooth to a into a DNS servers cache, causing it to serve to show the source as trusted to gain access to P number sequence resulting in an ability to mmunications rity ertificate management for email authentication.	Wireless person IEEE 802.15 IEEE 802.3 IEEE 802.11 IEEE 802.20 Standard 802.11a 802.11b 802.11g 802.11n 802.11ac • 802.11 use CSMA/CA protocol at Access) Wireless only DSSS Wireless on	th. ensitive. ensitive. ensitive. ensitive. ensitive. ensitive. enal circuits therefore less expensive. Ireless Networking Inal area network (WPAN) standards Bluetooth Ethernet Wi-Fi LTE Wi-Fi Speed Frequency (GHz) 54 Mbps 2.4 11 Mbps 5 54 Mbps 2.4/5 16bps 5 I as DSSS or FHSS eless Security Protocols rectly connects peer-to-peer mode clients without a entral access point. entral access entral access entral access point. entral access entral access entral access entral acce	
Types of E Asymmetric Digital Subscriber Line (ADSL) Rate Adaptive DSL (RADSL) Symmetric Digital Subscriber Line (SDSL) Very-high-bit-rate DSL (VDSL) High-bit-rate DSL (HDSL) Committed Information Rate (CIR) Unicast Multicast Broadcast Carrier-sense Multiple Access (CSMA) CSMA with Collision Detection (CSMA/CD) CSMA with Collision Avoidance (CSMA/CA) Polling Token-passing Broadcast Domain Collision Domain Layer 2 Switch Layer 3 Switch Twisted Pair Unshielded Twisted Pair (UTP) Shielded Twisted Pair (STP) Coaxial Cable Fiber Optic Frame Relay WAN Secure Note Secure Note Secure Note Twisted Pair Secure Note Secu	Pigital Subscriber Lines (DSL) winload speed higher than upload aximum 5500 meters distance via telephone lines. aximum 5500 meters distance via telephone lines. aximum download 8Mbps, upload 800Kbps. load speed adjust based on quality of the transmission line aximum 7Mbps download, 1Mbps upload over 5500 meters. me rate for upstream and downstream transmission rates. stance 6700 meters via copper telephone cables stance 6700 meters via copper telephone cables stance 3Mbps download, 2.3Mbps upload. gher speeds than standard ADSL aximum 52Mbps download, 16 Mbps upload up to 1200 ers speed for two copper cables for 3650 meters imum guaranteed bandwidth provided by service provider. N Packet Transmission Single source send to single destination Single source send to all the destinations. One workstations retransmits frames until destination workstation receives. Terminates transmission on collision detection. Used by Ethernet. Upon detecting a busy transmission, pauses and then re-transmits delayed transmission at random interval to minimise two nodes re-sending at same time. Sender sends only if polling system is free for the destination. Sender can send only when token received indicating free to send. Set of devices which receive broadcasts. Set of devices which raceive broadcasts. Set of devices which can create collisions during simultaneous transfer of data. Creates VLANs Interconnects VLANs LAN / WAN Media of twisted copper wires. Used in ETHERNET. Cat5/5e/6. Cat5 due to 100Mbps over 100 meters. Cat5e/6 speed 1000Mbps. immune to Electromagnetic Interference (EMI) art to UTP but includes a protective shield. conduit instead of two copper wires. 10BASE-T, 100BASE-T, 100BASE-T. light as the media to transmit signals. Gigabit speed at long ince. Less errors and signal loss. Immune to EMI. Multimode ingle mode. Single mode for outdoor long distance. a public switched network. High Fault tolerance by relaying	Firewall a Sec (Demilitarized zone) Bastion Host - Dua Screened Subnet - Po Virus Worms Logic Bomb Trojan Backdoor Salami, salami sl Data diddling Sniffing Session Hijack DDoS (Distributed E Service) SYN Flood Smurf Fraggle LOKI Teardrop Zero-day Land Attack Bluejacking, Bluesi DNS Spoofing, I Poisoning Session hijack (Spoofing) A TCP sequence produced for the produced service) SASL (Simple Au Securit Client SSL	Intrusion detection and prevention. and Perimeter decurity cure network between dernal internet facing and dernal networks. al-Homed - Three-Legged - Proxy Server - PBX - Honey of - IDS/IPS Nalicious software Self propagating virity of Time or condition to Code and/or execut malicious Unauthorized code Slicing A series of small at scale attack of Unauthorized monitor and capture credentials Denial of Overloading a server resulting in failure of Combination of a Deservice Particular kind of Deservice	In the control of the process it or ing of transmitt re of authentication of service DDOS attack and TODOS a	Discovery Communications. Extended protocol for SDLC. Map domain names /host names to IP Address and vice versa. Leased Lines 1.544Mbps via telephone line 45Mbps via telephone line 155Mbps 64 or 128 Kbps REPLACED BY xDSL dd 1024-49151 nnel 64 Kbps nnel 16 Kbps annels 64 Kbps annels 64 Kbps annels 64 Kbps annels 67 Kbps annels 68 Kbps annels 69 Kbps acks ables Begitimate software, but are not legitimate and are k intrusions that culminate in a cumulative large sing ted data an sessions with the purpose of finding and hijacking or data packets well beyond its processing capacity CP 3-way handshake exploit that results in denial of large numbers of Internet Control Message rogram to establish a covert channel on the network bug in TCP/IP fragmentation reassembly by ust channels sity unknown software bug the same source and destination IP ssages or injecting code via bluetooth to a into a DNS servers cache, causing it to serve to show the source as trusted to gain access to P number sequence resulting in an ability to mmunications rity ertificate management for email authentication.	Wireless person IEEE 802.15 IEEE 802.3 IEEE 802.11 IEEE 802.20 Standard 802.11a 802.11b 802.11g 802.11n 802.11ac • 802.11 use CSMA/CA protocol • 802.11 uses only DSSS Wirel Ad-hoc Mode Infrastructure Mode WEP (Wired Equivalent Privacy) WPA (Wi-Fi Protected Access) WPA2 WPA2-Enterprise Mode TKIP (Temporal Key Integrity Protocol) EAP (Extensible Authentication Protocol) TLS Authentication Protocol) PEAP (Protected Extensible Authentication Protocol) PEAP (Protected Extensible Authentication Protocol) TLS Spectrum System) DSSS (Direct Sequence Spread Spectrum) OFDM (Orthogonal Frequency-Division Multiplexing) FireWal First Generation Firewalls Second Generation Firewalls Packet Fi protocol araccording • Application Protocol in packets are Dynamic Packet Fi protocol araccording • Stateful I packets are Dynamic Packet Fi Includes packets are Dynamic	th. ensitive. cual circuits therefore less expensive. Ireless Networking Inal area network (WPAN) standards Bluetooth Ethernet Wi-Fi LTE Wi-Fi Speed Frequency (GHz) 54 Mbps 2.4 11 Mbps 5 54 Mbps 2.4/5 16bps 5 I as DSSS or FHSS eless Security Protocols rectly connects peer-to-peer mode clients without a entral access point. Infidentiality, uses RC4 for encryption. Sees Temporal Key Integrity Protocol (TKIP) for data connect centrally via access point. Infidentiality, uses RC4 for encryption. Sees RADIUS Sees RC4 stream cipher. Illizes PPP and wireless authentication. Compatible with her encryption technologies. Incapsulates EAP within an encrypted and authenticated Stunnel. 12.1x, use with EAP in switching environment reless Spread Spectrum sees all available frequencies, but only a single frequency on be used at a time. Inallel use of all the available frequencies leads to higher roughput of rate compared to FHSS. Ithogonal Frequency-Division Multiplexing II Generation Evolution Filter Firewalls: Examines source/destination address, and ports of the incoming packets. And deny or permit to ACL. Network layer, stateless. In Calculation Indicated and context of the re inspected.	
Types of E Asymmetric Digital Subscriber Line (ADSL) Rate Adaptive DSL (RADSL) Symmetric Digital Subscriber Line (SDSL) Very-high-bit-rate DSL (VDSL) High-bit-rate DSL (HDSL) Committed Information Rate (CIR) Unicast Multicast Broadcast Carrier-sense Multiple Access (CSMA) CSMA with Collision Detection (CSMA/CD) CSMA with Collision Avoidance (CSMA/CA) Polling Token-passing Broadcast Domain Collision Domain Layer 2 Switch Layer 3 Switch Twisted Pair Unshielded Twisted Pair (UTP) Shielded Twisted Pair (STP) Coaxial Cable Thick and 10 Uses I Fiber Optic Secure Note Secure Not	Pault tolerance PExpensive to setup Digital Subscriber Lines (DSL) winload speed higher than upload aximum 5500 meters distance via telephone lines. aximum download 8Mbps, upload 800Kbps. load speed adjust based on quality of the transmission line aximum 7Mbps download, 1Mbps upload over 5500 meters. me rate for upstream and downstream transmission rates. stance 6700 meters via copper telephone cables eximum 2.3Mbps download, 2.3Mbps upload. gher speeds than standard ADSL aximum 52Mbps download, 16 Mbps upload up to 1200 ers speed for two copper cables for 3650 meters imum guaranteed bandwidth provided by service provider. N Packet Transmission Single source send to single destination Single source send to multiple destinations Source packet send to all the destinations. One workstations retransmits frames until destination workstation receives. Terminates transmission on collision detection. Used by Ethernet. Upon detecting a busy transmission, pauses and then re-transmits delayed transmission at random interval to minimise two nodes re-sending at same time. Sender sends only if polling system is free for the destination. Sender can send only when token received indicating free to send. Set of devices which can create collisions during simultaneous transfer of data. Creates VLANs Interconnects VLANs LAN / WAN Media of twisted copper wires. Used in ETHERNET. Cat5/5e/6. Cat5 dup to 100Mbps over 100 meters. Cat5e/6 speed 1000Mbps. immune to Electromagnetic Interference (EMI) art to UTP but includes a protective shield. conduit instead of two copper wires. 10BASE-T, 100BASE-T, 100BASE-T, 100BASE-T. ilight as the media to transmit signals. Gigabit speed at long noe. Less errors and signal loss. Immune to EMI. Multimode ingle mode. Single mode for outdoor long distance. a public switched network. High Fault tolerance by relaying segments to working. etwork Design - Components	Firewall a Sec (Demilitarized zone) Bastion Host - Dua Screened Subnet - Po Virus Worms Logic Bomboon Trojan Backdoor Salami, salami si Data diddling Sniffing Session Hijack DDoS (Distributed Deservice) SYN Flood Smurf Fraggle LOKI Teardrop Zero-day Land Attack Bluejacking, Bluess DNS Spoofing, It Poisoning Session hijack (Spoofing) A TCP sequence production of the product of	Intrusion detection and prevention. and Perimeter ecurity cure network between ernal internet facing and ernal networks. al-Homed - Three-Legged - Proxy Server - PBX - Honey of - IDS/IPS Malicious software Self propagating virit of Time or condition to Code and/or execut malicious Unauthorized code Silicing A series of small at scale attack and Unauthorized monit with Monitor and capturate dentials Denial of Overloading a server resulting in failure of Combination of a Deservice Particular kind of Deserv	HDLC) Domain name system (DNS) T1 T3 ATM ISDN Reserved BRI B-chan BRI D-chan PRI B & D chan PRI	Just Discharge Communications. Extended protocol for SDLC. Map domain names /host names to IP Address and vice versa. Leased Lines 1.544Mbps via telephone line 45Mbps via telephone line 155Mbps 64 or 128 Kbps REPLACED BY xDSL od 1024-49151 nnel 64 Kbps nnel 16 Kbps annels 64 Kbps annels 64 Kbps acks ables legitimate software, but are not legitimate and are k intrusions that culminate in a cumulative large sing ted data in sessions with the purpose of finding and hijacking or data packets well beyond its processing capacity CP 3-way handshake exploit that results in denial of large numbers of Internet Control Message rogram to establish a covert channel on the network bug in TCP/IP fragmentation reassembly by ust channels sly unknown software bug is the same source and destination IP seages or injecting code via bluetooth to into a DNS servers cache, causing it to serve to show the source as trusted to gain access to P number sequence resulting in an ability to mmunications rity ertificate management for email authentication.	Wireless person IEEE 802.15 IEEE 802.3 IEEE 802.11 IEEE 802.20 Standard 802.11a 802.11b 802.11g 802.11n 802.11a 802.11b 802.11b 802.11b 802.11b 802.11b 802.11b 802.11c 802.11b 802.11b 802.11b 802.11b 802.11c 802.11b 802.11c Pacer Infrastructure Mode Uire Ad-hoc Mode Infrastructure Mode WEP (Wired Equivalent Privacy) WPA (Wi-Fi Protected Access) WPA2 WPA2-Enterprise Mode Use TKIP (Temporal Key Integrity Protocol) EAP (Extensible Authentication Protocol) PEAP (Protected Extensible Authentication Protocol) PEAP (Protected Extensible Authentication Protocol) Port Based Authentication Port Based Authentication Port Based Authentication Firewalls First Generation Firewalls Second Generation Firewalls Fourth Generation Firewalls Packet Fincludes parts of the Company Packets and Packets and Packets and Packets and Packets and Packets Fincludes	th. ensitive. usal circuits therefore less expensive. Ireless Networking mal area network (WPAN) standards Bluetooth Ethernet Wi-Fi LTE Wi-Fi Speed Frequency (GHz) 54 Mbps 2.4 11 Mbps 5 54 Mbps 2.4, 200+ Mbps 2.4/5 1Gbps 5 I as DSSS or FHSS eless Security Protocols rectly connects peer-to-peer mode clients without a entral access point. Indidentiality, uses RC4 for encryption. Iters connect centrally via access point. Indidentiality, uses RC4 for encryption. Iters Expended Frequencies authentication. Compatible with here encryption technologies. Incapsulates EAP within an encrypted and authenticated as tunnel. 12.1 x, use with EAP in switching environment reless Spread Spectrum ses all available frequencies, but only a single frequency in the used at a time. Intelled use of all the available frequencies leads to higher roughput of rate compared to FHSS. Ithogonal Frequency-Division Multiplexing II Generation Evolution Filter Firewalls: Examines source/destination address, and ports of the incoming packets. And deny or permit to ACL. Network layer, stateful. Inspection Firewall: Proxy Server: Masks the source code to the incoming packets. And deny or permit to ACL. Network layer, stateless. In Generation Evolution Filter Firewalls: Examines source/destination address, and ports of the incoming packets. And deny or permit to ACL. Network layer, stateless. In Section Firewall: Dynamic ACL modification inspected. Packet Filtering Firewall: Dynamic ACL modification inspected. Packet Filtering Firewall: Used in networks facing both internal med Host Firewall: Used in networks facing both internal	
Types of E Asymmetric Digital Subscriber Line (ADSL) Rate Adaptive DSL (RADSL) Symmetric Digital Subscriber Line (SDSL) Very-high-bit-rate DSL (VDSL) High-bit-rate DSL (HDSL) Committed Information Rate (CIR) Unicast Multicast Broadcast Carrier-sense Multiple Access (CSMA) CSMA with Collision Detection (CSMA/CD) CSMA with Collision Avoidance (CSMA/CA) Polling Token-passing Broadcast Domain Collision Domain Layer 2 Switch Layer 3 Switch Twisted Pair Unshielded Twisted Pair (UTP) Shielded Twisted Pair (STP) Coaxial Cable Thick and 10 Uses I Fiber Optic Thick Allow S Secure No.	Pault tolerance PExpensive to setup Digital Subscriber Lines (DSL) winload speed higher than upload aximum 5500 meters distance via telephone lines. Eximum download 8Mbps, upload 800Kbps. load speed adjust based on quality of the transmission line aximum 7Mbps download, 1Mbps upload over 5500 meters. The reason of the proper telephone cables aximum 2.3Mbps download, 2.3Mbps upload. The speeds than standard ADSL aximum 52Mbps download, 16 Mbps upload up to 1200 ers. Packet Transmission Single source send to single destination. Single source send to multiple destination. Source packet send to all the destinations. Source packet send to all the destinations. One workstations retransmits frames until destination workstation receives. Terminates transmission on collision detection. Used by Ethernet. Upon detecting a busy transmission, pauses and then retransmits delayed transmission at random interval to minimise two nodes re-sending at same time. Sender sends only if polling system is free for the destination. Sender can send only when token received indicating free to send. Set of devices which can create collisions during simultaneous transfer of data. Creates VLANs LAN / WAN Media of twisted copper wires. Used in ETHERNET. Cat5/5e/6. Cat5 du pto 100Mbps over 100 meters. Cat5e/6 speed 1000Mbps. Interconnects VLANs LAN / WAN Media. Greates errors and signal loss. Immune to Electromagnetic Interference (EMI) art to UTP but includes a protective shield. conduit instead of two copper wires. 10BASE-T, 100BASE-T, 100BASE-T. [light as the media to transmit signals. Gigabit speed at long ince. Less errors and signal loss. Immune to prelaying segments to working.	Firewall a Sec (Demilitarized zone) Bastion Host - Dua Screened Subnet - Po Virus Worms Logic Bomb Trojan Backdoor Salami, salami sl Data diddling Sniffing Session Hijack DDoS (Distributed Deservice) SYN Flood Smurf Fraggle LOKI Teardrop Zero-day Land Attack Bluejacking, Bluese DNS Spoofing, Iteration Poisoning Session hijack (Spoofing) A TCP sequence produmber atta LDAP (Lightweight Protest SASL (Simple August Security Client SSL S/MIME Commons Syn Minester State Signal Syn Minester State Signal Syn Minester State Syn Minester Syn Minester State Syn Minester State Syn Minester	Intrusion detection and prevention. and Perimeter ecurity cure network between ernal internet facing and ernal networks. al-Homed - Three-Legged - Proxy Server - PBX - Honey of - IDS/IPS Malicious software Self propagating virit of Time or condition to Code and/or execut malicious Unauthorized code A series of small at scale attack of Monitor and capturated resulting in failure of Combination of a Derivation of a Derivati	HDLC) Domain name system (DNS) T1 T3 ATM ISDN Reserved BRI B-chan BRI D-chan PRI B & D cha PRI B & D cha Ictwork Atta e, code and executa iruses locked virus atables that act as let execution entry attacks and network ata before process itoring of transmitt are of authentication are with requests for of service DDOS attack using I ack that exploits a led packets to exhautormant or previous and packets to exhautormant or previous and packet that has led packets to exhautormant or previous and packets to exhautormant or previous and packet that has led packets to exhautormant or previous and packet that has led packets to exhautormant or previous and packets to exhautormant or previous and packet that has led packets to exhautormant or previous and packet that has led packets to exhautormant or previous and packet that has led packets to exhautormant or previous and packet that has led packets to exhautormant or previous and packets to exhautormant or	Just Dis PIDEs communications. Extended protocol for SDLC. Map domain names /host names to IP Address and vice versa. Leased Lines 1.544Mbps via telephone line 45Mbps via telephone line 155Mbps 64 or 128 Kbps REPLACED BY xDSL dd 1024-49151 nnel 64 Kbps nnel 16 Kbps annels 64 Kbps annels 64 Kbps albles Legitimate software, but are not legitimate and are k intrusions that culminate in a cumulative large sing ted data n sessions with the purpose of finding and hijacking or data packets well beyond its processing capacity CP 3-way handshake exploit that results in denial of large numbers of Internet Control Message rogram to establish a covert channel on the network bug in TCP/IP fragmentation reassembly by ust channels sity unknown software bug the same source and destination IP ssages or injecting code via bluetooth to a into a DNS servers cache, causing it to serve to show the source as trusted to gain access to P number sequence resulting in an ability to mmunications rity ertificate management for email authentication.	Wireless person IEEE 802.15 IEEE 802.3 IEEE 802.11 IEEE 802.20 Standard 802.11a 802.11b 802.11g 802.11n 802.11a 802.11a 802.11b Ad-hoc Mode Clie WEP (Wired Equivalent Privacy) WPA (Wi-Fi Protected Use Access) WPA2 WPA2-Enterprise Mode Use TKIP (Temporal Key Integrity Protocol) EAP (Extensible Authentication Protocol) PEAP (Protected Extensible Authentication Protocol) PEAP (Protected Extensible Authentication Protocol) PEAP (Protected Extensible Authentication Protocol) PORT Based Authentication POSS (Direct Sequence Spread Spectrum) OFDM (Orthogonal Frequency-Division Multiplexing) Firewall First Generation Firewalls Second Generation Firewalls Packet Fiprotocol ar according to the Packet Fiprotocol are accordin	the ensitive. usal circuits therefore less expensive. Ireless Networking nal area network (WPAN) standards Bluetooth Ethernet Wi-Fi LTE Wi-Fi Speed Frequency (GHz) 54 Mbps 2.4 11 Mbps 5 54 Mbps 2.4 200+ Mbps 2.4/5 1Gbps 5 I as DSSS or FHSS eless Security Protocols rectly connects peer-to-peer mode clients without a entral access point. Idents connect centrally via access point. Indidentiality, uses RC4 for encryption. I as RADIUS I as RSS, key management. I as RSS AES, key management. I as RC4 stream cipher. I alizes PPP and wireless authentication. Compatible with here encryption technologies. I accepsulates EAP within an encrypted and authenticated activation. I a survival access point and a unital access of the encryption of the	
Types of E Asymmetric Digital Subscriber Line (ADSL) Rate Adaptive DSL (RADSL) Symmetric Digital Subscriber Line (SDSL) Very-high-bit-rate DSL (VDSL) High-bit-rate DSL (HDSL) Committed Information Rate (CIR) Unicast Multicast Broadcast Carrier-sense Multiple Access (CSMA) CSMA with Collision Detection (CSMA/CD) CSMA with Collision Avoidance (CSMA/CA) Polling Token-passing Broadcast Domain Collision Domain Layer 2 Switch Layer 3 Switch Layer 3 Switch Twisted Pair Unshielded Twisted Pair (UTP) Shielded Twisted Pair (UTP) Shielded Twisted Pair (STP) Coaxial Cable Fiber Optic Fiber Optic Fiber Optic Secure Notes	Pault tolerance Pault tolerance Pault tolerance Pigital Subscriber Lines (DSL) Winload Speed higher than upload eximum 5500 meters distance via telephone lines. Eximum download 8Mbps, upload 800Kbps. Hoad speed adjust based on quality of the transmission line aximum 7Mbps download, 1Mbps upload over 5500 meters. The stance 6700 meters via copper telephone cables aximum 2.3Mbps download, 2.3Mbps upload. Upload by the speeds than standard ADSL eximum 52Mbps download, 16 Mbps upload up to 1200 ers. Packet Transmission Single source send to single destination Single source send to multiple destinations Source packet send to all the destinations. One workstations retransmits frames until destination workstation receives. Terminates transmission on collision detection. Used by Ethernet. Upon detecting a busy transmission, pauses and then retransmits delayed transmission pauses and then set and the set of devices which receive broadcasts. Sender sends only if polling system is free for the destination. Sender can send only when token received indicating free to send. Set of devices which can create collisions during simultaneous transfer of data. Creates VLANs Interconnects VLANs LAN / WAN Media of twisted copper wires. Used in ETHERNET. Cat5/5e/6. Cat5 dup to 100Mbps over 100 meters. Cat5e/6 speed 1000Mbps. immune to Electromagnetic Interference (EMI) art to UTP but includes a protective shield. conduit instead of two copper wires. 10BASE-T, 100BASE-T, 100BASE-T. light as the media to transmit signals. Gigabit speed at long nec. Less errors and signal loss. Immune to EMI. Multimode ingle mode. Single mode for outdoor long distance. a public switched network. High Fault tolerance by relaying segments to working. etwork Design - Components heternal public IP address from external internet sharing of public IP address from internal devices and attions using a g	Firewall a Sec (Demilitarized zone) Bastion Host - Dua Screened Subnet - Po Virus Worms Logic Bomb Trojan Backdoor Salami, salami sl Data diddling Sniffing Session Hijack DDoS (Distributed E Service) SYN Flood Smurf Fraggle LOKI Teardrop Zero-day Land Attack Bluejacking, Bluese DNS Spoofing, I Poisoning Session hijack (Spoofing) A TCP sequence pro / number atta LDAP (Lightweigh Prot SASL (Simple All Securit Client SSL S/MIME Object PEM (Privacy-	Intrusion detection and prevention. and Perimeter recurity cure network between dernal internet facing and ernal networks. al-Homed - Three-Legged - Proxy Server - PBX - Honey of - IDS/IPS Malicious software Self propagating virities of Self propagating virities Code and/or execut malicious Unauthorized code Unauthorized monitor and capture credentials Denial of Overloading a server resulting in failure of Combination of a Dervice Particular kind of Derotocol (ICMP) passervice In the passervice passervice passervice passervice passervice passerv	HDLC) Domain name system (DNS) T1 T3 ATM ISDN Reserved BRI B-chan BRI D-chan PRI B & D cha PRI B & D cha Ictwork Atta e, code and executa iruses locked virus utables that act as lettered authentication for service DDOS attack and To DDOS attack and To DDOS attack using I ackets stead of TCP ICMP tunnelling price ack that exploits a led packets to exhautormant or previous g a packet that has along malicious mester within range of corrupt DNS data ture of the packet to the packet to exhautormant or previous g a packet that has along malicious mester within range of the packet to exhautormant or previous g a packet that has along malicious mester within range of the packet to exhautormant or previous and packets and packe	use DIE/DC communications. Extended protocol for SDLC. Map domain names /host names to IP Address and vice versa. Leased Lines 1.544Mbps via telephone line 45Mbps via telephone line 155Mbps 64 or 128 Kbps REPLACED BY xDSL d 1024-49151 finel 64 Kbps finel 16 Kbps finel 64 Kbps finel 65 Kbps finel 65 Kbps finel 65 Kbps finel 66 Kbps finel 67 Kbps finel 68 Kbps finel 69 Kbps finel 69 Kbps finel 60 Kbps fi	Wireless person IEEE 802.15 IEEE 802.3 IEEE 802.11 IEEE 802.20 Standard 802.11a 802.11b 802.11g 802.11n 802.11ac • 802.11 use CSMA/CA protocol = 802.11 buses only DSSS Wirel Ad-hoc Mode Infrastructure Mode WEP (Wired Equivalent Privacy) WPA (Wi-Fi Protected Access) WPA2 WPA2-Enterprise Mode TKIP (Temporal Key Integrity Protocol) EAP (Extensible Authentication Protocol) TLS Wirel Authentication Protocol) PEAP (Protected Extensible Authentication Protocol) TEAP (Protected Extensible Authentication Protocol) POTH Based Authentication Port Based Authentication Spectrum System) DSSS (Direct Sequence Spread Spectrum) OFDM (Orthogonal Frequency-Division Multiplexing) FireWall First Generation Firewalls Fourth Generation Firewalls	th. ensitive. unal circuits therefore less expensive. Ireless Networking mal area network (WPAN) standards Bluetooth Ethernet Wi-Fi LTE Wi-Fi Speed Frequency (GHz) 54 Mbps 2.4 11 Mbps 5 54 Mbps 2.4/5 16bps 5 1as DSSS or FHSS eless Security Protocols rectly connects peer-to-peer mode clients without a normal access point. Interest connect centrally via access point. Interest central via access point. Interest centr	
Types of E Asymmetric Digital Subscriber Line (ADSL) Rate Adaptive DSL (RADSL) Symmetric Digital Subscriber Line (SDSL) Very-high-bit-rate DSL (VDSL) Committed Information Rate (CIR) Unicast Multicast Broadcast Carrier-sense Multiple Access (CSMA) CSMA with Collision Detection (CSMA/CD) CSMA with Collision Avoidance (CSMA/CA) Polling Token-passing Broadcast Domain Collision Domain Layer 2 Switch Layer 3 Switch Twisted Pair Unshielded Twisted Pair (UTP) Shielded Twisted Pair (STP) Coaxial Cable Thick and 10 Fiber Optic Fiber Optic Secure No Network address translation (PAT) Port Address Translation (PAT) Stateful NAT Static NAT One to devices	Preventive to setup Digital Subscriber Lines (DSL) winload speed higher than upload eximum 5500 meters distance via telephone lines. Saimum download 8Mbps, upload 800Kbps. load speed adjust based on quality of the transmission line eximum 7Mbps download, 1Mbps upload over 5500 meters. The rate for upstream and downstream transmission rates. Stance 6700 meters via copper telephone cables winimum 2.3Mbps download, 2.3Mbps upload. gher speeds than standard ADSL eximum 2.5Mbps download, 16 Mbps upload up to 1200 ers. Speed for two copper cables for 3650 meters simum guaranteed bandwidth provided by service provider. N Packet Transmission Single source send to single destination Single source send to multiple destinations. One workstations retransmits frames until destination workstation receives. Terminates transmission on collision detection. Used by Ethernet. Upon detecting a busy transmission, pauses and then re-transmits delayed transmission at random interval to minimise two nodes re-sending at same time. Sender sends only if polling system is free for the destination. Set of devices which can create collisions during simultaneous transfer of data. Creates VLANs Interconnects VLANs LAN / WAN Media of twisted copper wires. Used in ETHERNET. Cat5/5e/6. Cat5 of up to 100Mbps over 100 meters. Cat5e/6 speed 1000Mbps. Interconnects VLANs LAN / WAN media of two copper wires. 10BASE-T, 100BASE-T, 100BASE-	Firewall a Sec (Demilitarized zone) Bastion Host - Dua Screened Subnet - Po Virus Worms Logic Bomb Trojan Backdoor Salami, salami si Data diddling Sniffing Session Hijack DDoS (Distributed Deservice) SYN Flood Smurf Fraggle LOKI Teardrop Zero-day Land Attack Bluejacking, Bluese DNS Spoofing, In Poisoning Session hijack (Spoofing) A TCP sequence produmber atta LDAP (Lightweight Protesta) SASL (Simple And Security Client SSL S/MIME Object PEM (Privacy- DKIM (Domainket)	Intrusion detection and prevention. and Perimeter ecurity cure network between ernal internet facing and ernal networks. al-Homed - Three-Legged - Proxy Server - PBX - Honey of - IDS/IPS Nalicious software Self propagating virity of Time or condition to Code and/or execut malicious Unauthorized code A series of small at scale attack of Unauthorized monity king Alteration of raw day unauthorized monity king Combination of a Derivation of	HDLC) Domain name system (DNS) T1 T3 ATM ISDN Reserved BRI B-chan BRI D-chan PRI B & D cha PRI B & D cha Ietwork Atta Is code and executation It code and executation	Just Discrete Communications. Extended protocol for SDLC. Map domain names /host names to IP Address and vice versa. Leased Lines 1.544Mbps via telephone line 45Mbps via telephone line 155Mbps 64 or 128 Kbps REPLACED BY xDSL dd 1024-49151 del 16 Kbps del 17 Kbps del 18 Kbps del	Wireless person IEEE 802.15 IEEE 802.3 IEEE 802.11 IEEE 802.20 Standard 802.11a 802.11b 802.11b 802.11b 802.11b 802.11c 802.11b 802.11c Cor Privacy Wirel Ad-hoc Mode Infrastructure Mode WEP (Wired Equivalent Privacy) WPA (Wi-Fi Protected Access) WPA2 WPA2-Enterprise Mode TKIP (Temporal Key Integrity Protocol) EAP (Extensible Authentication Protocol) FAP (Protected Extensible Authentication Protocol) PEAP (Protected Extensible Authentication Protocol) Port Based Authentication Wirel FHSS (Frequency Hopping Spectrum System) DSSS (Direct Sequence Spread Spectrum) OFDM (Orthogonal Frequency-Division Multiplexing) Firewalls First Generation Firewalls First Generation Firewalls Packet Fincludes parts of the protocol according in the Corporation of the Corporation Protocol in Corporation Protocol Protocol in Corporation	the ensitive. ual circuits therefore less expensive. Ireless Networking nal area network (WPAN) standards Bluetooth Ethernet Wi-Fi LTE Wi-Fi Speed Frequency (GHz) 54 Mbps 2.4 11 Mbps 5 54 Mbps 2.4 200+ Mbps 2.4/5 16bps 5 I as DSSS or FHSS eless Security Protocols rectly connects peer-to-peer mode clients without a entral access point. Interest connect centrally via access point. Interest connect centrally via access point. Interest connect seer-to-peer mode clients without a entral access point. Interest connect centrally via access point. Interest centrally centrall central point centra	

Domain 5: Id	Domain 5: Identity & Access Management CISSP Cheat Sheet Series							
Three	e-factor Authentication (3FA)		To	erminolog	у	Δ	ccess Contro	ol Requirements
	Something that is known by the user		<u> </u>		tion flow between objects. ict or allow access to systems.	CIA Triad: C or		ity - A vailability (See Domain 1 cheat eet!!!!!)
Ownership factor					to an object or objects.		Identity M	Management
Characteristic A user characteristic, such as biometrics; fingerprints, face scan, signature.		,		f Access 8		IAAA – Iden	• Registration	on verification of user identity and add an
Knowledge –Type/category 1 – something you know		Centralized administration	•	nponent can cor control done cen	ntrol access. Highly restricted	Identificatio	Assign use	er the proper controls y use user ID or username.
	ication, Secret questions such as mother's maiden name,	Decentralized			mation owners, Can be less	Authenticati	• User verifi	cation process y used passwords
favorite food, date of birth, key combination / PIN. Terminology and concepts		Hybrid Combination of centralized and decentralized.		Authorization • Defining resources for user access Accountability • Person responsible for the controls, uses log		esources for user access		
	Random data added to a password before hashing and	Access star		allow-by-defa	ault or deny-by-default		•	n System for Applications in
Salted hash	storing in a database on a server. Used instead of plaintext storage that can be verified without revealing password.	Single Sign-On		nplEg. password	s, easy administration, faster	Dublic Kov or et		or Environment)
Commiltee	Alphanumeric, more than 10 characters. Includes a	(SSO)		k of all systems	comprised by unauthorized	authenticating fu	ıll message. Two sep	ates initial segment without parate tickets are in use one for the access privileges for user. Both
ComplEg. password	combination of upper and lower case letters, numbers and symbols.		Αι	uthorizatio	on		symmetric encryptio	. •
One-time password (OTP)	Dynamically generated to be used for one session or transaction.	Access control policies: Level of access and controls granted for a user.		SAML - (SOAP/XML)	between security	domains and systems. rincipal User • Identity provider • Service		
Static password	Password does not change. To be avoided.	Separation of Assigning different users different levels of access to		(SUAP/XIVIL)	provider. • Use in directory	federation SSO.		
Cognitive personard	Something used to identify a person, i.e. pets name,	duties		acy and security perform specific	functions is granted to two or	Authorization Concepts		
Cognitive password	favorite color, mother's maiden name etc, place of birth etc.	Dual Controls	more users.			Security domain Set of resources having the same security policies.		
Password Hacking	Unauthorized access of a password file	Split Knowledge Principle of Least	_		information to perform a task.		Organization having a vithin the federation.	a common set of policies and standards
Brute force attack	Multiple attempts using all possible password or pin combinations to guess the password.	Privilege	task.	ii iiiiiiiiiiiiii acce	ess level fleeded to perform a	Federation Models		
Dictionary attack	Type of brute force attack that uses all the words from the dictionary.	Need-to-Know			o perform a task.	Cross-Certificatio	organizations wit	n is certified and trusted by the other hin the standards defined internally by
Social engineering	Gain access by impersonating a user by establishing	No Access		•	cess for any object. e for user objects management.	Trusted	said organization	s. n adheres to the standards set by a third
attack	legitimate user credentials through social manipulation of trusted parties or authorities.	Directory Service	i.e. LDAP	_	•	Third-Party / Bridge Model	party.	
Rainbow Tables	Precomputed table for reversing cryptographic hash functions and cracking passwords.		• Symmetric	c Key Cryptograp	-	IDaaS (Identity as a Service)	party organization	
Ownership	-Type/category 2 - Something you have	Kerberos	Confidential	oution Center (KI ality and integrit key cryptography	y and authentication,	SSO (Single sign-on)	systems. Primaril	nent for multiple similar, yet independant ly used for the cloud and SaaS based
Synchronous token	Create password at regular time intervals.	Deales	-		ve domain. Uses symmetric-key	Cloud Identity	system access. User account ma	nagement (Office 365)
Asynchronous token	Generate a password based on the challenge-response technique.	Realm	cryptograph			Directory Synchronization		ntity provider (Microsoft Active directory)
Memory card	A swipe card containing user information.	KDC (Key Distribution	* Stores secret keys of all clients and servers in the network		Federated Identit	On-premises iden (MS AD)	itity provider for managing login request.	
Smart Cards or	A card or dongle that includes a chip and memory, like	Center) • AS (Authentication Server) • TGS (Ticket Granting Server)			Access Co	entrol Models		
Integrated Circuit Card (ICC)	bank cards or credit cards.		• KDC create a symmetric key and time-stamped 1G1 to be		Implicit Deny	By default access granted.	s to an object is denied unless explicitly	
Contact Cards	Swiped against a hardware device.	The Kerberos			-	Access Control Matrix	controls / privileg	
Contactless Cards or Proximity Cards	Simply need to be within proximity to the reader device.	logon process			Capability Tables	• ACLs focus on o	ols and privileges assigned to a subject. objects whereas capability lists focus on	
Hybrid Cards	Allows a card to be used in both contact and contactless systems.	Client installs the TGT and decrypts the symmetric key using a hash.		Permissions	subjects. Access granted for	,		
USB drive	Bespoke USB with access credentials	Authorization Methods		Rights Privileges		perform an action on an object. ghts and permissions.		
Static password Simplest type of security token where the password is stored within the token.		Discretionary Access Control (DAC) • Mandatory Access Control (MAC) •				Access Cont	trol Categories	
Challenge/respons A challenge has to be met by the correct user response.		Role-based Access Control (role-BAC) • Rule-based Access Control (Rule-BAC). Discretionary Access Control Uses access control lists (ACLs -			Category	Scope / Purpos	Two keys or key and	
e token Characteristic	-Type/category 3 - Something you do / are	(DAC)		Access-control lists). Subject authorize according to security labels.		Compensative	Risk mitigation actio	locker.
	gy allows the user to be authenticated based on	Mandatory Access Contro (MAC)		,			Reduce attack impac	оттыте дата раскирѕ.
• Physiological i.e.	vior or characteristics. Iris, retina, and fingerprints.					Detective	Detect an attack bef happens.	systems (IDS).
Behavioral i.e. Vo	·	Role-BAC (RBAC)		access an object based on its role or assigned tasks.		Deterrent	Discourages an attac	authentication, tences
Fingerprint	Physiological Characteristics Scans the thumb or edge of the finger.	Rule-BAC		Uses a set of rules or filters to define what can or cannot be done on a system.		Directive	Define and documen acceptable practices	
	Size, shape, bone length, finger length, or other layout	Hybrid RE	BAC	Limited RBAC	be done on a system.		an organization. Stop an attack.	Locks, biometric systems,
Hand Geometry Hand Topography	attributes of a user's hand are taken. Hand peaks and valleys pattern.	Lattice based	/ Label	Objects are cla	assified based on control level	Recovery	Recovery of a syster an attack.	encryption, IPS, passwords. m after Disaster recovery plans, data backups etc.
Palm or Hand Scan	Fingerprint and geometry combination of palm.	Non-discretionar	•	Based on polic	cies defined by a central			·
Facial Scan	Facial features such as bone, eye length, nose, chin shape	Mandatory-Acce			based or task based.	Vulnerability Assessment Personnel Testing • Physical Testing • System and Network Testing		
Retina Scan	etc. Retina blood vessel scan.	Auth Constrained Interf			s / Concepts can be performed with given			g and Threat Modeling probability of the attack to the application
Retina blood vessel	Scans the colored part of the eye around the pupil.	Applications	privileg Restric	ges.	depends on the content of an		•	stems tion about the system
scan Vascular Scans	Scans the pattern of the veins in the users hand or face.	Content-Depende	object.	•	after a specific condition. Eg.		2. Collect informat	ion about attack against the system system vulnerabilities
Vascular Scans Voice print	Verify speech sound patterns.	Context-Depende	after s	pecific date/time kt-dependent cor	e	Steps		against the system attempting to gain
	Scanning Behaviors	Subjects are given access to object only to perform Least Privilege what they need to have.		ess to object only to perform		5. Document the o	utcome of the penetration test	
Signature Dynamics	Pen pressure and acceleration is measured.	No more or no less! Separation of Duties			Blind Test	Organization know	on Test Types vs about possible attack but very limited	
Keystroke Dynamics	Scan the typing pattern.	and Responsibilit	ies lasks		rmed by two or more people. y • Vulnerability Assessment •	Double-Blind	knowledge. Organization does	n't know about incoming attack except for
Voice Pattern /	Measures the sound pattern of a user read particular	User Accountability Penetration Testing • Threat Modeling Users are responsible for what actions they have		Test	very few people in information.	the organization who do not exchange		
Print Biometric	word. Does not change throughout human life and unique. High	Auditing and Repo	-	to be monitored	for reporting: Network Events •	Target Test	Organization has p key details	orior knowledge of the attack, including
Considerations	accuracy rate.	Application Events • System Events • User Events • Keystroke Activity		Zero-Knowledae		on Strategies know any information about the target		
Enrollment Time	Sample processing for use by the biometric system. The process of obtaining the information from a	Access Control Types		Test Partial	network A.K.A. bla	ck box testing. nows public knowledge about the		
Feature Extraction	collected sample.	Type Scope / Purpose Example			Knowledge Test Full Knowledge	organization's netv		
Accuracy Throughput Rate	Scan the most important elements for correctness. The rate which the system can scan and analyze.	Administrative Controls		ation of on assets and	Data classification, data labeling, security awareness training	Test	the organization's I	network.
False Rejection	The percentage of valid users that will be falsely rejected.	personal. training. Logical / Firewalls, IDS's/ IPS's,			Password types			
Rate (FRR)	Type 1 error.	Logical / Technical Controls Restrict access. Restrict access. acrds, and passwords.		Simple Passwords Single word usually a mixture of and lowercase letters. Combination / Composition Combination of two unmatchine				
False Acceptance Rate (FAR)	The percentage invalid users that will be falsely accepted. Type 2 error.	Protect organization's Physical Controls infrastructure and			Combination / Composition Combination of two unmatching dictionary words. Passphrase Passwords Requires that a long phrase here.			
	TI I. I. EDD EAD TI	personnel. biometrics and cabling.			One-Time or Dynamic Passwords Passwords that are valid for		Requires that a long phrase be used.	
Crossover Error Rate (CER)	The point at which FRR equals FAR. This is expressed as a percentage - lower CER is better.					One-Time or Dv	namic Passwords	Passwords that are valid for a single
	·				nt management		vnamic Passwords swords (CAPCHA)	Passwords that are valid for a single session login. Uses of character images or graphics as a part of the authentication.

Domain 6: Security Assessment & Testing

Sc	oftware Testing
Static Testing	Software security analysis using automated tools. Do not analyze either the source code or the compiled application. Eg. Buffer overflow
Dynamic Testing	Analyze and test using running environment. Use to test software provided by third parties where no access to software code. Eg. cross-site scripting, SQL injection
Fuzz Testing	Type of dynamic testing which use specific inputs to detect flaws under stress/load. Eg. input invalid parameters to test
Mutation / Dumb Fuzzing	Using already modified input values to test.
Generational / Intelligent Fuzzing	Inputs models of expected inputs.
Misuse Case Testing	Evaluate the vulnerability of known risks and attacks.
Interface Testing	Evaluate performance of software modules against the interface specifications to validate working status.
Application Programming Interfaces (APIs)	Test APIs to verify web application meets all security requirements.
User Interfaces (UIs)	Includes graphic user interfaces (GUIs) and command-line interfaces (CLI). Review of user interfaces against requirement specifications.
Physical Interfaces	Eg. in physical machines such as ATM, card readers etc.
Unit Testing	Testing a small part of the system to test units are good for integration into final product.
Integration Level Testing	Transfer of data and control between program interfaces.
System Level Testing	Verify system has all the required specifications and functions.

Log Management System						
OPSEC process	Analyze daily operations and review possible attacks to apply countermeasures.					
Pen-test	Testing of network security in view of a hacker.					
Port scanner	Check any port or port range open in a computer.					
Ring zero	Internal code of the system.					
Operational assurance	Verify software meets security requirements.					
Supervisor mode	Processes running in internal protected ring.					

Threat Assessment Wodeling						
STRIDE	Evaluate threats against applications or operating systems.					
Spoofing	Use of false identity to gain access to system identity. Can use IP/ MAC address, usernames, wireless network SSIDs.					
Tampering	Cause unauthorized modifications of data in transit or in storage. Results in violation of integrity as well as					

Threat Assessment Modeling

STRIDE	Evaluate threats against applications or operating systems.				
Spoofing	Use of false identity to gain access to system identity. Can use IP/ MAC address, usernames, wireless network SSIDs.				
Tampering	Cause unauthorized modifications of data in transit or in storage. Results in violation of integrity as well as availability.				
Repudiation	Deny an action or activity carried out by an attacker.				
Information disclosure	Distribution of private/confidential or restricted information to unauthorized parties.				
Elevation of privilege	Attack result in increase the level privileges for a limited user account.				
Regular monitoring of key performance and risk indicators including	Number of open vulnerabilities and compromised accounts, vulnerability resolve time, number of detected software flaws etc.				
Vulnerability scans	Automatically probe systems, applications, and networks.				
TCP SYN Scanning	Sends a packet with SYN flag set. Also known as "half-open" scanning.				
TCP Connect Scanning	Perform when a user running the scan does not have the necessary permissions to run a half-open scan.				
TCP ACK Scanning	Sends a packet with the ACK flag set.				
Xmas Scanning	Sends a packet with the FIN, PSH, and URG flags set.				
Passive Scanning	Detect rogue scanning devices in wireless networks.				

Read-only account to access configuration files.

Authenticated scans

CISSP Cheat Sheet Series

Software Development Security Best Practices

0011110110	zorospinioni cocumity zooti idonoco
WASC	Web Application Security Consortium
OWASP	Open Web Application Security Project
BSI	the Build Security In initiative
IFC	The International Electrotechnical Commission

Security Testing

To make sure security controls are properly applied and in use. Automated scans, vulnerability assessments and manual testing.

Software Threats						
Viruses	Stealth virus • Polymorphic virus • Macro virus • • Spyware/Adware • Botnet • worm					
Rootkit	Kernel-mode Rootkit • Bootkit • User-mode Rootkit • Virtual Rootkit • Firmware Rootkit					
Source Code Issues	Buffer Overflow • Escalation of Privileges • Backdoor					
Malware Protection	Antivirus software • Antimalware software • Security Policies					

Considerations

- Resources availability
- · Level of critical and sensitiveness of the system under testing
- Technical failures
- · Control misconfigurations result in security loopholes
- · Security attack risks
- · Risk of performance changes
- · Impact on normal operations

Verification & Validation

- Verification SDLC design output meets requirements
- · Validation Test to ensure software meets requirements

Security Software

- Antimalware and Antivirus Scan and log malware and virus detection
- IDS/IPS = Real time and promiscuous monitoring for attacks
- Network-based IDS
- · Local network monitoring and passive and header level scanning . No host level scan.
- HOST BASED
- Monitor hosts using event logs
- Intrusion prevention system (IPS) Attack detects and prevent
- Remote Access Software Should be access via a VPN
- Vulnerability assessment Software should be updated and patched
- Routers policy based access control

Logs

	Network Flow	Network traffic capture
	Audit logging	Events related to hardware device login and access
	Network Time Protocol (NTP)	Should synchronize across entire network to have correct and consistent time in logs and device traffic flows.
	Syslog	Device event message log standard.
	Event types	Errors, Warnings, Information, Success Audits, Failure
	Simple Network Management Protocol (SNMP)	Support for different devices such as Cisco.

Monitoring and auditing

Define a clipping level. A.K.A BASELINE

- Audit trails event/transaction date/time, author /owner of the event
- Availability Log archival
- Log Analysis examine logs

Code Review and Testing

Person other than the code writer/developer check the code to find errors

Fagan inspections – steps	Planning • Overview • Preparation • Inspection • Rework • Follow-up
Code Coverage Report	Details of the tested code structure
Use cases	Percentage of the tested code against total cases
Code Review Report	Report create in manual code testing
Black-box testing	Test externally without testing internal structure
Dynamic Testing	Test code in run time
White-box testing	Detailed testing by accessing code and internal structure
CVE	Common Vulnerability and Exposures dictionary
CVSS	Common Vulnerability Scoring System
NVD	National Vulnerability Database
Regression Testing	Verify the installations required for testing do not have any issues with running system
Integration Testing	Test using two or more components together

Internal /external communications

Detailed plans by team members

HR involvement

Costs

	Operations					
	cident Scene	O. ff. i.u.t	Characteristics of Evidence	Evidence Lifecycle		figuration Management (CM)
	ent environment protection • ID and possible ect evidence • Avoid or minimize evidence	Sufficient Reliable	Validity can be acceptable. Consistent facts. Evidence not tampered or modified.	Discovery Protection	An ITILVZ and an ITSI	M process that tracks all of the individual Configuration Items (CI)
	contamination	Relevant	Reasonable facts, with proof of crimes, acts and methods used,	3. Recording	_	ersion: state of the Cl, Configuration - collection of component
Locard's In a crime the	suspected person leaves something and takes		event documentation	4. Collection and identification	, ,	I's that makes another Cl
Exchange	e leftovers can be used to identify the suspect.	Permissible	Evidence obtained lawfully	5. Analysis	R	ecovery procedures. Eg. system restart. Should be accessed
	ve Evidence		Interviewing and Interrogation	6. Storage, preservation, transportation7. Present in court	Armacis	y authorized users from authorized terminals.
Most reliable	and used by trial		Collect facts to determine matters of the incident.	8. Return to owner		Incident Response
• Original document	ments-Eg. Legal contracts	Interrogation	Obtain a confession by evidence retrieval method. The Process: Prepare questions and topics, summarize information	Digital Evidence	Lifecycle	Response Capability • Incident response and handling •
• No copies or	duplicates Il and reliable than primary evidence.	Opinion Rule	Witnesses test only the facts of the case, not used as evidence.	Digital Evidence	•	Recovery • Feedback
-	originals, witness oral evidence.	Expert Witnesses	Can be used as evidence.	Six principles to guide digital evidence technicians	Mitigation	Limit the impact of an incident.
Evidence • If primary evidis not valid.	dence is available secondary of the same content	Withlesdes			F	Root Cause Analysis (RCA)
	out a backup support.		Network Analysis	 All general forensic and procedural principles apply. 	Fault tree analysis (F)	TA) Top down deductive failure analysis using boolean logic.
• Eg. witness to	estimony by his/her own 5 senses.	Use of existing logs	controls to inspect a security breach incident. Eg. IDS/IPS, firewall	Upon seizure, all actions should not	Failure mode and	Review of as many components, assemblies, and
Conclusive evidence requir	adict, conditional evidence, no other supportive res	Software An	alysis: Forensic investigation of applications which was running while		effects analysis (FME	subsystems as possible to identify potential failure modes.
	ed to directly prove a fact	the incident ha	ppened. nbedded Device Analysis: Eg. review of Personal computers &	All people accessing the data should		Looks at the predominant likely causes to deal with them
Corroborative Evidence • Use as substa	antiate for other evidence	Smartphones		be trained	Pareto Analysis	first.
Hearsay • Something he	eard by the witness where another person told		Governing Laws	All actions performed on the data should be fully documented and	Cause mapping	Connects individual cause-and-effect relationships to give insights into the system of causes within an issue.
Evidence	'		• Common law - USA, UK Australia, Canada	accessible.		Nice and an December Models and a
Asse	et Management	• Islami	• Civil law - Europe, South America c and other Religious laws – Middle East, Africa, Indonesia, USA	Anyone that possesses evidence is	L	Disaster Recovery Methods
•	on and Integrity • Redundancy and Fault Tolerance •		Legislative: Statutory law - Make the laws	responsible for all actions taken with it	Hot Site	A real-time mirror of your system and network activity running in sync. Allows for minimum disruption and
	stems • Identity and Access Management Storage Management (HSM): continuous online	The 3 Branch		while in their possession.		downtime.
Storage backup system	Using optical storage.		Juridical: Interpret the laws Criminal law -violate government laws result in	Any agency that possesses evidence is is responsible for compliance with	Cold Site	An alternative workspace with power and HVAC setup, but no hardware. All recovery efforts will be technician heavy.
Management • Media History • Media Labelir	y: Media usage log ng and Storage: safe store of media after labeling		commonly imprisonment	these principles.	Warm Site	A middle-ground solution which includes skeletal hardware,
sequentially		Oatama:	Civil law – Wrong act against individual or organization which results in a damage or loss. Result in financial		Service Bureau	software and connectivity to restore critical functionality. Contract with a service bureau to provide backup services.
• Data Purging:	Temperature and heat Eg. Magnetic media degaussing Archived data not usable for	Categories	penalties. • Administrative/Regulatory law – how the industries,	Media Analysis	Multiple centers /	
Sanitizing and forensics			organizations and officers should act. Punishments can	Part of computer forensic analysis	sites	Process between multiple data centers
Data • Data Cleaning	: Cannot recover using keyboard Data left in media deleted	Liniforms O	be imprisonment or financial penalties	used for identification and extraction of information from storage media.	Rolling / mobile sites	Mobile homes or HVAC trucks.
• Redundant ha		Uniform Co	Lommon tramework for the conduct of computer-related	Eg. Magnetic media, Optical media,	D	Hot site RTO: 5 minutes or hours
Network and • Fault-tolerant Resource • Service Level	technologies Agreements (SLA's)	Transaction (UCIT	Ins ACT licensing	Memory (e.g., RAM)	Recovery Time Objectives (RTOs)	Warm site RTO: 1-2 daysMobile site RTO: 3-5 days
Management • MTBF and MT	rtr ,	,	• Unauthorized intrusion	Admissible Evidence		Cold site RTO: 1 to 2 weeks
Incident	of Failure (SPOF)	Computer Cr 3 types o	• Unauthorized alteration or destruction	Relevant to the incident. The evidence		RAID, SAN, & NAS
Response -	Respond • 3. Report • 4. Recover • 5. Remediate • 6. Review		• Relevant sufficient reliable does not have to be	must be obtained legally.	RAID	Redundant Array of Independent / Inexpensive Disks
• Changes show	uld be formally requested	Admissible	tangible	Digital Forencies	Disk Mirroring	Writing the same data across multiple hard disks, slower as data is written twice, doubles up on storage requirements
• Analyze reque	ests against goals to ensure validity	Hears	 Second hand data not admissible in court Is the legal action of luring an intruder, like in a 	Digital Forensics Five rules of evidence:	Disk Striping	Writes data across multiple disks simultaneously, provides
_	rt estimation before approval nange steps after approval	Enticer	honeypot	Be authentic • Be accurate • Be complete	Disk Striping	higher write speed.
• Incremental to	esting during implementation	Entrapr	• Is the illegal act of inducing a crime, the individual had no intent of committing the crime at first	Be convincing • Admissible	RAID 0	 Writes files in stripes across multiple disks without using parity information
Complete doc Clipping level	s: Define a baseline for normal user errors,		-	Investigation - To	RAID 0	2 or more disks requiredFast reading and writing but no redundancy
Threats and • Modification	from Standards Eg. DDOS		Data Loss Prevention (DLP)	Determine Suspects		Creates identical copies of drives - has redundancy
Preventative • Unusual patte Measures • Unscheduled	reboots: Eg. Hardware or operating system issue	Scans data Network-bas	for keywords and data patterns. Protects before an incident occurs. Data in motion. Scans all outbound data looking for anomalies. Place	Types:	RAID 1	 Space is effectively utilized, since half will be given to another disk
• Input/output	Controls	ed DLP	in edge of the network to scan all outgoing data.	Operational • Criminal • Civil • eDiscovery		• Expensive
Intrusion Detection	& Prevention Systems (IDS &	Endpoint-bas Data in use. Scans all internal end-user workstations, servers and devices.		Security Incident and	RAID 3	Byte level data striping across multiple
minusion Detection	IPS)	eu DLP		Event Management	RAID 4	Block level data striping across multiple Data and parity Information is striped together across all
	11 3)		Digital Data States	(SIEM)	RAID 5	drives
I I II)S (Intriigión	d inspection of logs and real-time system events ntrusion attempts and system failures. IDSs are an	Data at Rest Data in	Data that is stored on a device or a backup medium. Data that is currently travelling across a network or on a device's	Log review automating	RAID 0+1	Stripes data across available drives and mirrors to a seperate set of disks
I DATACTION SVETAMI	nethod of detecting many DoS and DDoS attacks.	Motion	RAM ready to be read, updated, or processed.	Real-time analysis of events occurring on systems	DAID 1 (0 (DAID 10)	Each drive in a set is mirrored to an equivalent drive in
IPS (Intrusion		Data in Use	Data that is being inputted, processed, used or altered.		RAID 1+0 (RAID 10)	another set
Prevention System) A IDS with	additional caabilities to stop intrusions.		Backup Types	Transaction Redundancy	Storage Area Network (SAN)	Typically use Fibre Channel and iSCSI. High speed blick level storage.
	Circuralla	Full All files backed up, archive bit and modify bit will be deleted		Implementations	Network-Attached	Typically an NFS server, file-level computer data storage
	Firewalls	Increment		Electronic Vaulting • Remote Journaling • Database shadowing	Storage (NAS)	server connected to a computer network.
including i	and analyze the internals of a compating system,		Only modified files are backed up, do not delete archive bit. Need last full backup and last incremental backup for a full	System Hardening	Disaster Recovery Terminology & Concepts	
(Host-based IDS) computer		restore.		" • Uninstall unnecessary applications	MTTF	Mean Time To Failure
KIII)C	based device or software applications used to	Redundant se		Disable unnecessary services	MTTR MTBF	Mean Time To Repair Mean Time Between Failures, MTTF + MTTR
(Network-based IDS) monitor ai	nd analyse network activity, specifically scanning ous activities and policy violations.	John Ver Cluste	g	Deny unwanted portsExternal storage device restriction	Transaction Redund	
	· · ·		Disaster Recovery Test	Monitoring and Reporting Wilhershillty Management System	Implementations	
Hierarchical Recove	Types of System Failure	Desk Che	•	Vulnerability Management SystemIDP/IPS: Attack signature engine	D.	Isings Continuity Planning
Types		Table-top exe	Disaster recovery team members gather and roleplay a	should be updated regularly	Б	usiness Continuity Planning
1 Manual	System rebootEmergency restart		More intense than a rolenlay all support and tech staff meet	System Recovery	Business Continuity	Concerns the preservation and recovery of business in the event of
Manual Automatic Recovery	System cold start	Simulation	est and practice against disaster simulations	1. Rebooting system in single user	Plan (BCP)	outages to normal business operations.
		■ Parallel tes	Personnel are taken to an alternative site and commence operations of critical systems, while original site continues	mode, recovery console 2. Recovering all file systems active	Business Impact	The process of assessing the impact of an IT disruption.
Data Des	struction and Reuse	raiallei les	operating operations of critical systems, while original site continues	before crash 3. Restore missing / damaged files	Analysis (BIA)	BIA is part of BCP
Object reuse Use after in		Full-implemen	tation Personnel are taken to an alternative site and commence operations of all systems, main site is shut down	4. Recover security and access		A framework of steps and actions that need to be taken to achieve business continuity and disaster recovery
Data remanence	g data after erasure Format magnetic media 7 ange book	tests		controls	Disaster Recovery Plants (DRP)	an goals. End Goal – Revert back to normal operations - planning
Clearing Overwriting media to be reused			BCP Plan Development		(DIXI)	and development must be done before the disaster - BIA
	ng or overwriting to be removed	Define the com	Computing: strategy to protect - hardware, software, communication by Eacilities: use of primary or alternate/remote site buildings.	cation links, applications, data		should be complete
Destruction Complete destruction, preferably by burning		Define the continuity • Facilities: use of primary or alternate/remote site buildings • People: operational and management				 Scope and plan initiation BIA - assess impact of disruptive processes
Disaster Recovery Planning			Supplies and equipment		Business Continuity	3. Business Continuity Plan development - Use BIA to
Disaster Teams responsible for DR implementation - Salvage team - Work		Roles and responsibilities • BCP committee: senior staff, business units, information systems, security administrator, officials departments			Steps	develop BCP - Testing
recovery	mary site to make suitable for normal operations	• CCTV				4. Plan approval and implementation - management
• Interfacing with other groups		• Fences-Small mesh and high gauge • Alarms				approval
• Fraud and Cri	me: Eg. vandalism, looting		• Intrusion detection: electromechanical, photoelectric, passive i	nfrared, acoustical detection		Trusted Recovery
Financial disbursementDocumenting the Plan - Required documentation		Physical sec	 Motion: wave pattern motion detectors, proximity detector Locks: warded lock, combination lock, cipher lock, device lock, 	preset / ordinary door lock, programmable	Breach Confirmation	•
	d recovery procedures	1 1				

• Audit trails: date and time stamps, successful/unsuccessful attempts, who attempted, who

• Wireless proximity cards: user activated or system sensing field powered device

• Security access cards: Photo ID card, swipe cards, smartcards

granted/modified access controls

CISSP Cheat Sheet Series

System Recovery

secure state

After a failure of operating system or application, the

system should work enough to have the system in a

primary key and different data in the table.

Service Pack

system

Collection of patches for a complete operating

Domain 0	. So teware Development Seediley						at offeet oches	
Software Development Lifecycle (SDLC)		Programming Language Types		Data Warehousing and Data Mining		Change Management Process		
Understand and integrate security throughout the software development		Machine Lenguage Direct instructions to processor - binary representation		Data Warehousing	Combine data from multiple sources		Request request modifications, conduct cost/ benefit analysis by	
	lifecycle (SDLC)		Languages Assembly Use of symbols, mnemonics to represent binary codes -		Arrange the data into a format easier to make business	mana	agement, and task prioritization by developers	
	Development Methodologies • No key architecture design	Language ADD, PUSH and POP Processor independent programming languages - use			decisions based on the content.		lop organizational framework where developers can e and test a solution before implementation in a	
• Problems fixed as they occur		High-Level IF,	THEN and ELSE statements as	Aggregation	Database Threats The act of combining information from various sources.	· ·	uction environment.	
	No formal feedback cycleReactive not proactive	Generation 4 languages further reduce amount of code		Aggregation Inference	Process of information piecing	Release Control	ge approval before release	
	Linear sequential lifecycleEach phase is completed before moving on	language	Very high-level language required - programmers can focus on algorithms. Python, C++, C# and Java		• Content Dependent Access Control: access is based on the sensitivity of the data	Configur	Configuration Management Process	
wateriali	 No formal way to make changes during cycle 	Natural Ge	neration 5 languages enable system to learn and	Access Control	Context Dependent Access Control: access via	Software Version	A methodology for storing and tracking changes	
	 Project ends before collecting feedback and re-starting Based on the waterfall model 		language change on its own - Al		 Database Views: set of data a user or group can see 	Control (SVC) Configuration	to software The labelling of software and hardware	
v-snaned	Each phase is complete before moving onVerification and validation after each phase	Databa	se Architecture and Models	Access Control Mechanisms	 Database Locks: prevent simultaneous access Polyinstantiation: prevent data interference violations 	Identification	configurations with unique identifiers Verify modifications to software versions	
	No risk analysis phase Panid protetyping, quick complete test the current.	Relational Model	Relational Model Uses attributes (columns) and tuples (rows) to organize data		in databases	Configuration Contro	ol comply with the change control and	
	Rapid prototyping - quick sample to test the current project	Hierarchical	Parent child structure. An object can have one child,	-	A·C·I·D	Configuration Audit	configuration management policies. Ensure that the production environment is	
Prototyping	• Evolutionary prototyping - incremental improvements to a design	Model	multiple children or no children. Similar to hierarchical model but objects can have	ATOMICITY	Database roll back if all operations are not completed, transactions must be completed or not completed at all	-	consistent with the accounting records	
	 Operational prototypes - incremental improvements intended for production 	Network Model	multiple parents.		Preserve integrity by maintaining consistent transactions	•	pability Maturity Model	
	 Multiple cycles (~ multiple waterfalls) Restart at any time as a different phase 	Object-Oriented Model	Has the capability to handle a variety of data types and is more dynamic than a relational database.	Isolation	Transaction keeps separate from other transactions until complete	Reactive	tiating – informal processes, peatable – project management processes	
Incremental	Easy to introduce new requirements	Wodel	and is more dynamic than a relational database.	Durability (Committed transaction cannot be roll backed	qualit	fined – engineering processes, project planning, ty assurance, configuration management practices	
	Delivers incremental updates to software Iterative	Object-Relational Model	Combination of object oriented and relational models.		Traditional SDLC	Proactive 4. Ma	anaged – product and process improvement timizing – continuous process improvement	
	Risk analysis during developmentFuture information and requirements considered for risk			Stens	Analysis, High-level design, Detail Design, Construction, testing, Implementation		ject Management Tools	
	analysis • Allows for testing early in development	Data	base Interface Languages		Initiation: Feasibility, cost analysis, risk analysis, Management approval, basic security controls		Type of bar chart that illustrates the relationship	
Rapid	Rapid prototyping	Open Databas Connectivity (DC	I ocal or remote communication via API		Functional analysis and planning: Requirement definition, review proposed security controls	Gantt chart	between projects and schedules over time.	
Application Development	Designed for quick developmentAnalysis and design are quickly demonstrated	Java Databas	•	Phases	System design specifications: detailed design specs,	Program Evaluation Review Technique	capacity of a software product in development	
` '	 Testing and requirements are often revisited Umbrella term - multiple methods 	Connectivity (JE	·		Examine security controls Software development: Coding. Unit testing Prototyping,	(PERT)	which uses to calculate risk.	
Agile	Highlights efficiency and iterative development	XML	DB API allows XML applications to interact with more traditional databases		Verification, Validation • Acceptance testing and implementation: security	OORA (Requirement	s of object-oriented design	
	User stories describe what a user does and whyPrototypes are filtered down to individual features	Object Linking			testing, data validation	Analysis)	Define classes of objects and interactions	
DevC	Ops (Development & Operations)	Embedding Databa DB)	se (OLE is a replacement for ODBC	Obje	ct-oriented technology (OOT) -	OOA (Analysis)	Identify classes and objects which are common to any applications in a domain - process of	
	are Development • Quality Assurance • IT			Terminology		OOD (Design)	discovery Objects are instances of classes	
	Operations	Knowledge Management		Objects contain both data and the instructions that work on the data.		OOP (Programming)	-	
Software Development Methods			o main components: 'Knowledge base' and the ference engine'	Encapsulation		ORBs (Object Reques Brokers)	st Work as middleware locators and distributors for the objects	
Contivate Development internedo		Expert • Use human reasoning		Message	Informs an object to perform an action. Performs an action on an object in response to a	CORBA (Common	Architecture and standards that use ORBS to	
	Database Systems		tule based knowledge base -then statements	Method	message.	object request)	allow different systems and software on a system to interfce with eachother	
Database Define storing and manipulating data		Interference system		Rehavior n	Results shown by an object in response to a message. Defined by its methods, which are the		Work independently without help from other programs	
DBMS (datab	ase Software program control access to data stored	• Forward chaining: Begins with known facts and applies inference rule to extract more data unit it reaches to the goal. A bottom-up approach. Breadth-first search strategy. • Backward chaining: Begins with the goal, works backward through inference rules to deduce the		Denavior	functions and subroutines defined within the object class.	Cohesion	High cohesion – No integration or interaction with other modules	
manageme system)	nt in a database.			Class	Set of methods which defines the behavior of objects	Low cohesion – Have interaction with of modules		
	Hierarchical • Network • Mesh • Object-orientated			Object	An instance of a class containing methods		• Coupling - Level of interaction between objects	
DBMS Type	• Relational	re	quired facts that support the goal. A top-down	Inheritance Multiple	Subclass accesses methods of a superclass Inherits characteristics from more than one parent		Virus Types	
DDL	Data definition language defines structure and schema DML	approach. Depth-first search strategy.		Inheritance	Inheritance class			
Degree of D		Accumulates knowledge by observing events, Neural measuring their inputs and outcome, then predicting Networks outcomes and improving through multiple iterations over time.		Two or more rows in the same relational database Polyinstantiation table appear to have identical primary key elements		BOOLSECIOE	Boot record infectors, gain the most privaleged access and can be the most damaging	
Degree of D	· ·				but contain different data Object users do not need to know the information	System intector	nfects executable system files, BIOS and system	
Tuple	row			Abstraction	about how the object works		commands	
DDE	Dynamic data exchange	Covert Channels (Storage & Timing)		Process isolation Allocation of separate memory spaces for process's instructions and data by the operating system.			Infects a system's factory installed UEFI (firmware)	
DCL	Data control language. Subset of SQL.	Executable conte Mobile code	ActiveX controls, Java applets, browser scripts	Tri	usted Computer Base (TCB)	Lompanion	Virus stored in a specific location other than in the main system folder. Example NOTEPAD.EXE	
Semantic inte	grity ensure semantic rules are enforced between data types	Virus Propagates with help from the host			The set of all hardware, firmware, and/or software components that are		Any modifications to files or boot sector are hidden	
Referential inte	egrity all foreign keys reference existing primary keys	Worm Propagates without any help from the host Logic Bomb/Code Propagates without any help from the host		critical to its security. Any compromises here are critical to system security.			by the virus Infects both boot sector and executable files	
	an attribute that is a unique identifier within a	Bomb	Run when a specific event happens	Input/outp	May need to interact with higher rings of			
Candidate K	Gey given table, one of the candidates key becomes primary key and others are alternate keys	Buffer Overflow	Memory buffer exhaustion Malicious code install at back end with the	operation	protection - such communications must be	Seit-darnlind	Attempts to hide from anti-virus by changing the encoding of its own code, a.k.a. 'garbling'	
Primary Ke		Backdoor	help of a front end user	Execution do	main Applications that invoke applications or	Polymorphic T	The virus modifies the "garble" pattern as it spreads	
1 milary ite	reference to another table which include primary	Covert Channel	0 0	switching		Resident L	Loads as and when a program loads to the memory	
Foreign Ke	key. Foreign and primary keys link is known as	Botnet	Zombie code used to compromise thousands of systems	Memory prote	Monitoring of memory references to verify confidentiality and integrity in storage	Master boot record / sector	Infects the bootable section of the system	
	referential integrity.	Trojan	Malicious code that outwardly looks or	Process activ	Monitor registers, process status information,	(MBR)	meets the bootable section of the system	
	• Incorrect Summaries • Dirty Reads • Lost	behaves as harmless or necesary code		and file access lists for vulnerabilities			Anti-Viruo Typoo	
	Updates • Dynamic Lifetime Objects: Objects developed		Security Assessment Browser site trust is exploited by trying to				Anti-Virus Types	
	using software in an Object Oriented	Cross-site reque forgery (CSRF / XS	submit authenticated requests forcefully to	Penetration Te	sting A process of identifying and determining the true nature if system vulnerabilities	Signature pased	Not able to detect new malware a.k.a. Zero-day attacks	
	ODBC - Open Database Connectivity. Database	ODBC - Open Database Connectivity. Database Cross-site scripting		Patch manage	·	Heuristic based S	Static analysis without relying on signatures	
DBMS term	feature where applications to communicate with different types of databases without a program	(XSS)	execute untrusted code from a trusted site Attempts to obtain previously authenticated	system	prevent known attack vectors			
22.70 (0111	code. • Database contamination - Mixing data with	Session Hijacki	ng sessions without forcing browser requests	Open system	m System with published APIs - third parties can use system		Protection Rings	
	different classification levels • Database partitioning - splitting a single	QOI Inication	Submission Directly attacks a database through a web app	Closed evet	Proprietary system - no third-party	Layer 0 Operat	ting system kernel	
	database into multiple parts with unique contents	SQL Injection Hotfix / Update	•	Closed syste	involvement Source code can be viewed, edited and	Layer 1 Parts of	of the operating system other than the kernel	
	 Polyinstantiation - two or more rows in the same relational database table appear to have identical 	Security fix	applications	Open-source	distributed free or with attribution or fees	Laver 2 I/O driv	vers and utilities	

API Keys

Used to access API. Highly sensitive - same

as passwords

Layer 2 I/O drivers and utilities

Layer 3 Applications and programs

CISSP Cheat Sheet Series